HP Pavilion 24cw 60.45 cm (23.8") IPS LED **Backlit Monitor**

Family-Friendly Viewing



It's time for a monitor that's worthy of your family's content. When you're looking for the best specs at the right price, the 60.45 cm (23.8") diagonal full HD Pavilion display delivers with trusted HP performance and an all new sleek design.



Always the best angle

 This affordable 60.45 cm (23.8") diagonal panel comes with IPS technology for a high-color, wide viewing angle. Now everyone in your family can have the best seat in the house.

Clean, contemporary design

 Easy access to the ports lets you quickly connect and tuck away those cords with the convenient open wedge stand. And the sleek, bezel-less design looks stylish enough to show off.

Screen that will delight

• This FHD resolution display brings impressive definition and a more vivid color spectrum to every pixel. Rest assured, with a screen this brilliant you'll never miss a single detail.

Featuring:

- Dual HDMI ports means more options and more devices you can connect for big screen, HD visuals.
- Be prepared for brilliant visuals and crisp images with the unforgettable quality of this stunning FHD
- · Quickly connect to your screen with simple and easy access to all your ports for a more convenient experience.
- The display is equipped with standard VESA mounting for showcasing on a wall or swivel arm.²

¹ High definition (HD) content is required to view high-definition images.

² VESA mounting arm or wall mounting assembly sold separately.

Datasheet

HP Pavilion 24cw 60.45 cm (23.8") IPS LED Backlit Monitor



Display Size	60.45 cm (23.8")
Aspect Ratio	16:9
Display type	IPS w/LED backlight
Pixel pitch	0.2745 mm
Refresh response time	8 ms gray to gray
Brightness	250 cd/m²
Contrast ratio	1000:1 static; 5000000:1 dynamic
Viewing angle	178° horizontal; 178° vertical
Video input signal	1 VGA; 2 HDMI (with HDCP support)
Resolution	1920 x 1080
Display Scan Frequency (horizontal)	Up to 80 kHz
Display Scan Frequency (vertical)	Up to 76 Hz
Display features	Plug and Play; Anti-Glare; User programmable; Language selection; On-screen controls; LED Backlights; In plane switching
Physical security features	Security lock-ready (lock is sold separately)
Display moving angle	Tilt: -2 to +25°
Environmental Specifications	Mercury-free LED backlighting; Arsenic-Free Display Glass; Low Halogen
Power Supply and Power Requirements	Input voltage: 100-240 VAC at 50 - 60 Hz; Power consumption: 26W maximum; 24W typical; Standby mode: < 0.5 W
Energy Efficiency	Energy Efficiency class: A; Visible Screen Diagonal: 60.45 cm (23.8"); On-mode power consumption: 20 W; Annual energy consumption: 29 kWh; Power consumption (off-mode): 0.29 W; Screen Resolution: 1920 x 1080
Display User Control Options	Menu (Select/OK); Brightness ("-"); Auto ("+"); Next Input (Back/Cancel/Exit); Power
Dimensions (W x D x H)	53.98 x 16.41 x 40.83 cm (with stand); 53.98 x 5.06 x 32.73 cm (without stand)
Weight	4.3 kg (with stand); 3.11 kg (without stand)
Operating Temperature Range	5°-35°C
Operating Humidity Range	20% - 70% (non-condensing)
Storage Temperature Range	-20° - 60°C
Non-operating Humidity Range	20% - 90%
Certifications and compliances	CB; CE; FCC marking; ErP; CSA; C-UL; C-ETL Mark; UL; CSA-NTRL; ETL-NRTL Mark; ICES; Argentina S-Mark; Japan VCCI; CCC; China CEL; Taiwan BSMI; Bauart; CECP; ISO9241-307; GOST 25861; HRN N N0.201; GOST R 50377-1992; GOST 25861; EEI certificate; IS 1121; SASO; SABS IEC 60950-1; NOM-019-SCFI-1998; KC Mark; KCC Mark; PSB mark; ISC mark; C-Tick
Product colour	Natural Silver (Bezel) and Black (Rear cover)
Warranty	1-year HP Commercial Guarantee
Box Content	A/C power cable, Power adapter, HDMI Cable, Documentation CD (include U.G., warranty, drivers), Quick Setup Poster, Cable management clip
VESA Mount	VESA Mount Bracket Kit Optional
Ordering info	L5N90AA#AZN: 889296216049; L5N90AA#ABB: 889296215967; L5N90AA#ABT: 889296216001; L5N90A#ABU: 889296215974; L5N90AA#ABV: 889296216025; L5N90AA#ABV: 889296215974; L5N90AA#ACO: 889296216035; L5N90AA#ABV: 889296216036; L5N90AA#ACO: 889296216036; L5N90ACO: 889296216036; L5N90ACO: 889296216036; L5N90ACO: 889296216036; L5N90ACO: 889296216036; L5N90ACO: 889296216036; L5N90ACO:

