



Barcode  
MC.JPE11.005



**HDMI**™  
HIGH-DEFINITION MULTIMEDIA INTERFACE



P/N: 4J.3J605.002

# SPECIFICATIONS

Projection system	DLP™
Resolution	<ul style="list-style-type: none"> <li>XGA: Native: XGA (1024 x 768) Maximum: UXGA (1600 x 1200), 1080p (1920 x 1080), WUXGA (1920 x 1200) (supports reduce blanking only)</li> <li>WXGA: Native: WXGA (1280 x 800) Maximum: UXGA (1600 x 1200), 1080p (1920 x 1080), WUXGA (1920 x 1200) (supports reduce blanking only)</li> </ul>
Computer compatibility	<p>IBM PC and compatibles, Apple Macintosh, iMac and VESA standards: VGA, SVGA, XGA, SXGA, SXGA+, WXGA, WXGA+, WSXGA+, HD720, HD1080, WUXGA (VGA source)</p> <p>IBM PC and compatibles, Apple Macintosh, iMac and VESA standards: VGA, SVGA, XGA, SXGA, SXGA+, WXGA, WXGA+, WSXGA+, HD720, HD1080, WUXGA (HDMI source)</p>
Video compatibility	NTSC (3.58/4.43), PAL (M/N), PAL 60, SECAM, HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect ratio	<ul style="list-style-type: none"> <li>XGA: Auto, 4:3 (native), 16:9</li> <li>WXGA: Auto, 4:3, 16:9, Full, L.Box</li> </ul>
Displayable colors	1.07 billion colors
Projection lens	<ul style="list-style-type: none"> <li>XGA: F = 2.59 – 2.87, f = 16.88 mm – 21.88 mm, 1:1.3 Manual Zoom and Manual Focus</li> <li>WXGA: F = 2.59 – 2.87, f = 16.88 mm – 21.88 mm, 1:1.3 Manual Zoom and Manual Focus</li> </ul>
Projection screen size (diagonal)	60" – 300" (152 cm – 762 cm)
Projection distance with clear focus	<ul style="list-style-type: none"> <li>XGA: W: 1.85 m – 5.54 m (6.1' – 18.2') T: 2.40 m – 7.20 m (7.9' – 23.6')</li> <li>WXGA: W: 1.57 m – 4.71 m (5.2' – 15.5') T: 2.04 m – 6.12 m (6.7' – 20.1')</li> </ul>
Throw ratio	<ul style="list-style-type: none"> <li>XGA: 1.51 – 1.97 (65" ± 3% @ 2 m)</li> <li>WXGA: 1.21 – 1.57 (77" ± 3% @ 2 m)</li> </ul>
Horizontal scan rate	15 – 100 KHz
Vertical refresh scan rate	24 – 120 Hz
Keystone correction	+/-30 Degrees (Vertical) / +/-20 Degrees (Horizontal), Manual & Auto
Digital zoom	0.8 – 2 X
Audio	10W speaker x 1
Weight	Approximate 2.4 kg (5.29 lbs.)

Dimensions (W x D x H)	299.5 x 220 x 91.6 mm (11.8" x 8.7" x 3.6") 299.5 x 220 x 105.1 mm (11.8" x 8.7" x 4.1") (with tilt adjusting wheels)
Power supply	Universal AC input 100 - 240 V, input frequency 50/60 Hz
Power consumption	Standard mode: 260 W @100 VAC ECO mode: 205 W @ 100 VAC Standby mode: < 0.5 W
Operating temperature	0°C to 40°C / 32°F to 104°F
I/O connectors	<ul style="list-style-type: none"> <li>Power socket x 1</li> <li>USB (Type mini B) x 1</li> <li>VGA input x 2</li> <li>VGA output x 1</li> <li>RS232 x 1</li> <li>3.5 mm audio jack input x 1</li> <li>3.5 mm audio jack output x 1</li> <li>Composite video x 1</li> <li>HDMI/MHL x 1</li> <li>HDMI x 1</li> <li>USB A input x 1</li> <li>RJ45 LAN input x 1</li> <li>Wireless dongle input x 1</li> </ul>

## Note:

- The specifications listed above are subject to change without notice.
- For final specifications, please refer to Acer's published marketing specifications.
- Find manuals and other documents for your Acer product on the official Acer support website.



Scan to get user's manual.