Specifications



APC Smart-UPS 5000VA 230V Rackmount/Tower

SUA5000RMI5U

① Discontinued

Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually Ships within 4 Weeks
Main	

Product or component type

Uninterruptible power supply (UPS)

Complementary

Communication port type

SmartSlot

Batteries & Runtime

Run Time	View Runtime Graph □
Battery type	Lead-acid battery
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	2
Battery life	35 year(s)
Replacement battery	RBC55 🗗
Battery charger power	542 W rated

General

Provided equipment	CD with software Documentation CD Installation guide Rack mounting hardware Rack mounting support rails Smart UPS signalling RS-232 cable User manual Web/SNMP management card
Number of power module	0
Number of power module filled slots	0



Number of power module free slots	0
Redundant	No

Physical

Number of rack unit	5U
Colour	Black
Height	8.74 in (22.2 cm)
Width	19.02 in (48.3 cm)
Depth	25.98 in (66 cm)
Net weight	215.46 lb(US) (97.73 kg)
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	No

Input

Main Input Voltage	230 V
Input voltage limits	151302 V adjustable 160286 V
Number of input connectors	1 hard wire 3-wire
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

230 V
220 V
240 V
4000 W
5000 VA
8 IEC 320 C13
4 IEC Jumpers
2 IEC 320 C19
3:1
Less than 5 % at full load
5000 VA
4000 W
2 ms typical : 4 ms maximum
Line interactive
Sine wave
96 % full load)
4753 Hz for 50 Hz nominal sync to mains

Conformance

Product certifications	C-Tick CE GOST VDE
Marking	GS Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Acoustic level	53 dBA
Heat dissipation	430 Btu/h
Operating altitude	010000 ft
ambient air temperature for operation	32104 °F (040 °C)
Ambient air temperature for storage	5113 °F (-1545 °C)
Storage altitude	050000 ft (0.00000000015240.000000000 m)
Relative humidity	095 %
Storage Relative Humidity	095 %

Communications & Management

Alarm	Audible and visible alarms : configurable delays
Free slots	0
Preinstalled device	Network management card
Control panel	LED status display with on line : on battery : replace battery and overload indicators

Surge Protection and Filtering

Surge energy rate	480 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.00 in (63.5 cm)
Package 1 Width	24.02 in (61 cm)
Package 1 Length	30.00 in (76.2 cm)
Package 1 Weight	235.50 lb(US) (106.82 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	4
Package 2 Height	46.85 in (119 cm)
Package 2 Width	39.37 in (100 cm)
Package 2 Length	47.24 in (120 cm)
Package 2 Weight	1022.9 lb(US) (464 kg)

Contractual warranty



Warranty

2 years repair or replace

C Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

${\mathcal Q}$ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	4487
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	080b8d64-796e-42e7-a17d-31b86e55d143
REACh Regulation	REACh Declaration
Inergy efficiency	
Optimized Energy Efficiency	Energy efficient product

Use Again

$^{\circlearrowright}$ Repack and remanufacture	
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins



Product data sheet SUA5000RMI5U

Image of product / Alternate images

Alternative







Product data sheet SUA5000RMI5U





