



On-person printing

Tackle the most challenging environments with Brother's 4" mobile label and receipt printer

RJ-4230B

brother.co.uk/mobile-printers

Print / media

Printing technology

Direct thermal

Print resolution

203dpi

Print speed*

Maximum 127/second (5ips)

Maximum print width

104mm

Maximum print length

3000mm

Tear bar

Double

Media width

45-113mm

Roll diameter

58mm max

LCD

Type

Mono LCD with backlight

Connectivity

USB

USB version 2.0 (mini-B type)

Bluetooth

Bluetooth version 4.2
(low-energy support)

Bluetooth Profiles

SPP (Serial Port Profile)
OPP (Object Push Profile)
HCRP (Hard Copy cable replacement profile)
IAP supported

MF i Support

(Made for iPad, iPhone and iPad)

Yes

NFC

Yes (passive)

General

Operating system support

Microsoft® Windows® 7 / Windows® 8 /
Windows® 8.1 / Windows® 10

SDK availability (visit <http://www.brother.eu/developer>)

Brother Print SDK for Android™
(for Android 4.0.3 or later)
Brother Print SDK for iPhone/iPad
(for iOS 7 or later)

Supported printer commands

P-touch template
ZPLII emulation
CPCL emulation
ESC/P
Raster

Memory

RAM

256MB

Flash

64MB

Environmental

Drop protection tested

Up to 2.1 metres

Sealing

IP54

Operating temperature

Operating: -20°C to +55°C / charging: 0°C to +40°C

Storage temperature

-20°C to 60°C

Power

Battery (optional accessory)

USB version 2.0 (mini-B type)

AC adapter (optional accessory)

110/220V AC (50/60Hz) to 15V DC

Car adapter (optional accessory)

12V DC

Weights/dimensions

Dimensions

153(w) x 68(h) x 159(d) mm

Weight (with battery)

850g

* Brother standard test environment