

<b>PIXMA iP100</b>	
<b>PRINTER FUNCTIONS</b>	
<b>Print Resolution</b>	Up to 9600[1] x 2400 dpi
<b>Print Engine</b>	InkJet 5-ink with minimum 1 pl Micro-Nozzles & FINE print head
<b>Photo Lab Quality Speed</b>	Borderless 10 x 15cm: Approx. 50 seconds (Standard)
<b>Mono Print Speed</b>	Up to 20ppm (Max), 15.6ppm (Standard)
<b>Colour Print Speed</b>	Text & Graphics: Up to 14ppm (Max.), 11.2ppm (Standard)
<b>Ink Cartridge Configuration</b>	Cartridge - PGI-35 Black, CLI-36 Color
<b>Ink Cartridge Life</b>	PGI-35 Black: 191 pages, CLI-36 Colour: 249 pages [2] PGI-35 Black: 2080 photos*, CLI-36 Colour: 111 photos [3]
<b>Media Type</b>	Plain Paper, Envelopes, Photo Paper Pro (PR-101), Photo Paper Plus Glossy (PP-101/PP-201), Photo Paper Plus Double Sided (PP-101D), Photo Paper Plus Semi-gloss (SG-201), Glossy Photo Paper (GP-401), Glossy Photo Paper "Everyday Use" (GP-501), Matte Photo Paper (MP-101), High Resolution Paper (HR-101N), T-shirt Transfer (TR-301), Photo Stickers (PS-101), Super White Paper (SW-201)
<b>Media Input</b>	Sheet Feeder: Max. 50 sheets
<b>Media Size</b>	Sheet Feeder: A4, B5, A5, Letter, Legal, Envelopes (DL size or Commercial 10), 10 x 15cm, 13 x 18cm, 10x18cm (wide), 20x25cm, Credit Card (54 x 86mm)
<b>Media Weight</b>	Sheet Feeder: 64 to 105 g/m <sup>2</sup> and supported Canon special media up to 273 g/m <sup>2</sup>
<b>Two Sided Printing</b>	Available by manual operation using Photo Paper Plus Double Sided, Super White Paper or plain paper in A4, B5, A5, Letter & 13 x 18cm sizes (Windows only)
<b>Borderless Printing</b>	Yes (A4, 13 x 18cm, 10 x 15cm & Credit Card sizes)
<b>INTERFACE AND CONNECTIVITY</b>	
<b>Interface Type - PC</b>	USB 2.0 Hi-Speed [4] IrDA IR Bluetooth v2.0: Max speed 1.44Mbps (optional, HCRP) [5] (with optional Bluetooth unit BU-30).
<b>Interface Type - Camera</b>	Direct Print Port: Camera direct photo printing from PictBridge compliant digital cameras & camcorders
<b>Interface Type - Mobile Phone / PDA</b>	IrDA IR (JPEG/PNG only) Bluetooth v2.0: Max speed 1.44Mbps (optional, JPEG/PNG only, OPP, BIP, BPP) [5] (with optional Bluetooth unit BU-30). Direct Print Port: PictBridge
<b>DRIVERS AND SOFTWARE</b>	
<b>Supported Operating System</b>	Windows Vista / Windows XP SP2 / Windows 2000 Professional SP4 Mac OS X v.10.3.9 - v.10.4 - v.10.5
<b>Minimum System Requirements</b>	Windows ® Vista™, XP, 2000 / Internet Explorer 6.0 / Pentium ® II 300 MHz including compatible processors / 128 MB RAM / 800 MB Hard disk space / CD-ROM drive / Display XGA 1024x768 Mac OS X v.10.5 / Intel ® processor, PowerPC G4 / 512 MB RAM Mac OS X v.10.4 / Intel ® processor, PowerPC G3 / 256 MB RAM Mac OS X v.10.3.9 / PowerPC G3 / 128 MB RAM Safari / 650 MB Hard disk space / CD-ROM drive / Display XGA 1024x768
<b>Driver Features</b>	Windows: Photo Optimizer PRO, Image Optimizer, Photo Noise Reduction, Vivid Photo Mac: Photo Optimizer PRO, Photo Noise Reduction, Vivid Photo
<b>Software Included</b>	Windows: Easy-PhotoPrint EX Mac: Easy-PhotoPrint EX
<b>GENERAL FEATURES</b>	
<b>Power Source</b>	AC: 100-240V, 50/60Hz Car adapter (optional): PU-200U, Input voltage 12-24V DC (negative ground) Battery & attachment: LK-62 Li-ion
<b>Power Consumption</b>	Standby: 1.5 W Off: Approx. 0.4 W Printing: Approx. 9 W
<b>Temperature Range</b>	Operating environment: 5° - 35° C
<b>Humidity</b>	Operating humidity: 10 - 90%RH (no condensation)
<b>Acoustic Noise Levels</b>	Printing: Approx. 38.5 dB(A) in best quality mode
<b>Dimensions (W x D x H)</b>	322 x 185 x 61.7mm
<b>Weight</b>	Approx. 2.0kg
<b>Options</b>	Bluetooth® Unit BU-30 Rechargeable Battery & attachment LK-62 Automobile Power Unit PU-200U

#### Standard disclaimers

All specifications subject to change without notice.

Borderless 10x15cm photo lab quality print speed based on Standard driver setting using Canon Photo Paper Plus Glossy media.

Print speed (ppm) based on Canon standard pattern. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used and does not take into account data processing time on host

\* Estimated supplemental yield

Ink yield may vary depending on texts/photos printed, applications software used, print mode and type of paper used.

All brand and product names are trademarks of their respective companies.

Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

For more information on ChromaLife100 please visit [www.canon-europe.com/chromalife100](http://www.canon-europe.com/chromalife100)

#### Footnotes

[1] Ink droplets can be placed with a minimum pitch of 1/9600 inch

[2] Printing ISO/IEC 24712:2006 Colour document. Declared yield value in accordance with ISO/IEC 2471. Values obtained by continuous printing.

[3] Printing Canon standard photos on 10x15cm (4x6in) Photo Paper Plus Glossy II continuously with the default settings of Photo Paper Plus Glossy II using Windows Vista printer driver in borderless printing mode and Windows Vista Home Premium Photo Gallery. Declared yield value determined based on Canon standard method referring to ISO/IEC 24711.

[4] Operation can only be guaranteed on a PC with built-in USB or USB 2.0 Hi-Speed Port and pre-installed Windows Vista, Windows XP, Windows 2000, Windows Me or Windows 98.

[5] PCs with Windows XP Service Pack 1 or later with Microsoft "Support for Bluetooth Wireless Devices", or Toshiba Windows XP computers with Bluetooth Settings Version 3.00.10 or later (HCRP only). Mac OS X v10.3.3 or later. Compatible Devices: PC, PDA, Mobile phone and any other Bluetooth enabled device (Bluetooth operation depends on the devices and software version used.)