

PIXMA iP1900

PRINTER FUNCTIONS	
Print Resolution	Up to 4800[1] x 1200 dpi
Print Engine	InkJet 4-ink with minimum 2 pl ink droplets and FINE Cartridges
Photo Lab Quality Speed	Borderless 10 x 15cm: Approx. 55 seconds (Standard)
Mono Print Speed	Up to 21ppm (Max.), 13ppm (Standard)
Colour Print Speed	Text & Graphics: Up to 17ppm (Max.), 7.7ppm (Standard)
Ink Cartridge Configuration	FINE Cartridge - PG-37, CL-38 (Optional - PG-40, CL-41)
Black Ink Tank Life	Black: 215 pages (PG-37), 327 pages (PG-40) [2] Black: 1215 photos* (PG-37), 2110 photos* (PG-40) [3] * Estimated supplemental yield
Colour Ink Tank Life	Colour: 206 pages (CL-38), 303 pages (CL-41) [2] Colour: 79 photos (CL-38), 112 photos (CL-41) [3]
Media Type	Plain Paper, Envelopes, Photo Paper Pro II (PR-201), Photo Paper Plus Glossy II (PP-201), Photo Paper Plus Semi-gloss (SG-201), Glossy Photo Paper "Everyday Use" (GP-501), Matte Photo Paper (MP-101), High Resolution Paper (HR-101N), T-shirt Transfer (TR-301), Photo Stickers (PS-101)
Media Input	Sheet Feeder: Max. 100 sheets
Media Size	Sheet Feeder: A4, B5, A5, Letter, Legal, Envelopes (DL size or Commercial 10), 10 x 15cm, 13 x 18cm, 20 x 25cm
Media Weight	Sheet Feeder: 64 to 105 g/m ² and supported Canon special media up to 260 g/m ²
Two Sided Printing	Available by manual operation using plain paper in A4, B5, A5, Letter & 13 x 18cm sizes (Windows only)
Borderless Printing	Yes (A4, 20 x 25cm, 13 x 18cm, 10 x 18cm, 10 x 15cm)
INTERFACE AND SOFTWARE	
Interface Type - PC	USB (B Port)
Supported Operating System	Windows Vista™ (32bit, 64bit) / Windows XP SP2 / Windows 2000 Professional SP4 Mac OS X v.10.3.9 - v.10.5
Minimum System Requirements	Windows: PC: Windows Vista™, XP, 2000 Professional / Internet Explorer 6.0 / CD-ROM drive / SVGA Display 800 x 600 Mac OS X v.10.3.9, v.10.4, v.10.5 / Safari / CD-ROM drive / XGA Display 1024x768
Driver Features	Photo Optimizer PRO (Windows only), Image Optimizer (Windows only), Photo Noise Reduction, Vivid Photo
Software Included	Windows: Easy-PhotoPrint EX, Mac: Easy-PhotoPrint EX
GENERAL FEATURES	
Power Source	AC 100-240V, 50/60Hz
Power Consumption	Standby: Approx. 1.0W Off: Approx. 0.6W Printing: 8.0W [4]
Temperature Range	Operating environment: 5° - 35° C
Humidity	Operating humidity: 10 - 90%RH (no condensation)
Acoustic Noise Levels	Printing: Approx. 44 dB(A) When printing ISO/JIS-SCID N2 pattern on 10x15cm Photo Paper Plus Glossy II using default settings
Dimensions (W x D x H)	442 x 237 x 152mm
Weight	Approx. 3.3kg

Standard disclaimers

All specifications subject to change without notice.

Borderless 10x15cm photo lab quality print speed based on Standard driver setting using ISO/JIS-SCID N2 on Canon Photo Paper Plus Glossy II media

PPM print speed is based on the highest speed mode setting using Canon standard patterns on plain paper.

Photo print speed is based on the default setting using "ISO/JIS-SCID N2" on 10x15cm Photo Paper Plus Glossy II.

Print speed measured as soon as first page begins to feed into printer and may vary depending upon a number of factors. Print speed does not take into account data processing time on host computer

Ink yield may vary depending on texts/photos printed, applications software used, print mode and type of paper used. For yield information see www.canon-europe.com/ink/yield

All brand and product names are trademarks of their respective companies.

Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

For more information on ChromaLife100 please visit www.canon-europe.com/chromalife100

Footnotes

[1] Ink droplets can be placed with a minimum pitch of 1/4800 inch

[2] Declared yield value in accordance with ISO/IEC 24711. Values obtained by continuous printing.

[3] When printing Canon standard photos continuously on 10x15cm Canon Photo Paper Plus Glossy II with the default settings, using Windows Vista printer driver in borderless printing mode and Windows Vista Home Premium Photo Gallery.

Declared yield value determined based on Canon standard method referring to ISO/IEC 24711.

[4] When printing ISO/JIS-SCID N2 pattern bordered on A4 plain paper with the default settings.