

PIXMA iP3600	
PRINTER FUNCTIONS	
Print Resolution	Up to 9600[1] x 2400 dpi
Print Engine	InkJet 5-ink with minimum 1 pl ink droplets & FINE print head
Photo Lab Quality Speed	Borderless 10 x 15cm: Approx. 41 seconds (Standard)
Mono Print Speed	Up to 26ppm (Max.), 12.8ppm (Standard)
Colour Print Speed	Text & Graphics: Up to 17ppm (Max.), 10.5ppm (Standard)
Ink Cartridge Configuration	Single Ink technology - 5 separate ink tanks (PGI-520BK, CLI-521BK, CLI-521C, CLI-521M, CLI-521Y)
Black Ink Tank Life	Black: 324 pages (PGI-520BK), 3425 pages* (CLI-521BK) [2] Black: 4520 photos* (PGI-520BK), 815 photos* (CLI-521BK) [3] *Estimated Supplemental Yield
Colour Ink Tank Life	Cyan: 535 pages (CLI-521C), Magenta: 510 pages (CLI-521M), Yellow: 530 pages (CLI-521Y)[2] Cyan: 241 photos (CLI-521C), Magenta: 236 photos (CLI-521M), Yellow: 220 photos (CLI-521Y)[3]
Media Type	Plain Paper, Envelopes, Photo Paper Pro Platinum (PT-101), Photo Paper Pro II (PR-201), Photo Paper Plus Glossy II (PP-201), Photo Paper Plus Semi-gloss (SG-201), Glossy Photo Paper "Everyday Use" (GP-501), Matte Photo Paper (MP-101), High Resolution Paper (HR-101N), T-shirt Transfer (TR-301), Photo Stickers (PS-101)
Media Input	Rear Tray: Max. 150 sheets Cassette: Max. 150 sheets
Media Size	Rear Tray: A4, B5, A5, Letter, Legal, Envelopes (DL size or Commercial 10), 10 x 15cm, 10 x 18cm, 13 x 18cm, 20 x 25cm, Credit Card (54 x 86mm) Cassette: A4, B5, A5, Letter
Media Weight	Rear Tray: Plain paper: 64 to 105 g/m ² and supported Canon special media up to 300 g/m ² Cassette: Plain paper: 64 to 105 g/m ²
Two Sided Printing	Available by manual operation using plain paper in A4, B5, A5, Letter & 13 x 18cm sizes (Windows only)
Borderless Printing	Yes (A4, 20 x 25cm, 13 x 18cm, 10 x 18cm, 10 x 15cm)
INTERFACE AND SOFTWARE	
Interface Type - PC	Hi-Speed USB (B Port)
Interface Type - Camera	Direct Print Port: Camera direct photo printing from PictBridge compliant digital cameras & camcorders
Interface Type - Mobile Phone / PDA	Photo printing via PictBridge
Supported Operating System	Windows Vista (32bit, 64bit) / Windows XP SP2 / Windows 2000 Professional SP4 Mac OS X v.10.3.9 - v.10.5
Minimum System Requirements	Windows: PC: Windows Vista™, XP, 2000 Professional / Internet Explorer 6.0 / CD-ROM drive / SVGA Display 800 x 600 Mac OS X v.10.3.9, v.10.4, v.10.5 / Safari / CD-ROM drive / XGA Display 1024x768
Driver Features	Photo Optimizer PRO (Windows only), Image Optimizer (Windows only), Photo Noise Reduction, Vivid Photo
Software Included	Windows: Easy-PhotoPrint EX, Mac: Easy-PhotoPrint EX
GENERAL FEATURES	
Power Source	AC 100-240V, 50/60Hz
Power Consumption	Standby: Approx. 1.3W Off: Approx. 0.5W Printing: 16.0W [4]
Temperature Range	Operating environment: 5° - 35° C
Humidity	Operating humidity: 10 - 90%RH (no condensation)
Acoustic Noise Levels	Printing: Approx. 41 dB(A) When printing ISO/JIS-SCID N2 pattern on 10x15cm Photo Paper Plus Glossy II using default settings
Dimensions (W x D x H)	431 x 296 x 153mm
Weight	Approx. 5.6kg

Standard disclaimers

All specifications subject to change without notice.
Borderless 10x15cm photo lab quality print speed based on Standard driver setting using ISO/JIS-SCID N2 on Canon Photo Paper Plus Glossy II media
PPM print speed is based on the highest speed mode setting using Canon standard patterns on plain paper.
Photo print speed is based on the default setting using "ISO/JIS-SCID N2" on 10x15cm Photo Paper Plus Glossy II.
Print speed measured as soon as first page begins to feed into printer and may vary depending upon a number of factors. Print speed does not take into account data processing time on host computer
Ink yield may vary depending on texts/photos printed, applications software used, print mode and type of paper used. For yield information see www.canon-europe.com/ink/yield
All brand and product names are trademarks of their respective companies.
Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.
For more information on ChromaLife100+ please visit www.canon-europe.com/chromalife100

Footnotes

- [1] Ink droplets can be placed with a minimum pitch of 1/9600 inch
[2] Declared yield value in accordance with ISO/IEC 24711. Values obtained by continuous printing.
[3] When printing Canon standard photos continuously on 10x15cm Canon Photo Paper Plus Glossy II with the default settings, using Windows Vista printer driver in borderless printing mode and Windows Vista Home Premium Photo Gallery.
Declared yield value determined based on Canon standard method referring to ISO/IEC 24711.
[4] When printing ISO/JIS-SCID N2 pattern bordered on A4 plain paper with the default settings.