

Dual Tower Dual Fan Twice the Performance



Cooler Master's MA624 Stealth brings to you twice the performance with dual fans and tower in a striking package. Equipped with jet black hardware throughout, its dark veil is nothing to be underestimated. The twin 140mm SickleFlow fan combined with dual tower heatsink configuration delivers a powerful Push-Pull setup, with its 6 pipes and nickel plated base working in sync to draw heat out rapidly. An optional 3rd 120mm fan is included to you for swap out for necessary RAM clearance. The MA624 Stealth is the ultimate secret weapon to blast away heat.

FEATURES

Premium Aluminum Black Top Cover – Black aluminum top cover offers a premium finish

Dual Tower Heat Sink – Dual heatsink combination provides twice the surface area for better cooling

6 Heat Pipes with Nickel Plated Base – 6 heat pipes and nickel plated base provides optimal coverage for exceptional cooling

Dual SickleFlow 140 Fan – Twin fans utilize Push-Pull setup for optimal airflow and pressure

RAM Clearance Option – Optional 3rd SickleFlow 120mm fan included for necessary RAM compatibility and clearance

Easy Mounting System – Exclusive All-In-One mounting design for easy installation

PACKING INFORMATION

4719512111512
884102083822
1.62 kg
2.32 kg
24.8 x 19.1 x 24.3 cm
52 x 40.5 x 27.8 cm
4

Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
20'	1344	28	N/A
40'	2688	28	N/A
40 HQ	3072	32	N/A

SPECIFICATIONS


Product Name		MasterAir MA624 Stealth		
Product Number		MAM-D6PS-314PK-R1		
Exterior Color		Black		
CPU Socket	Intel	LGA 2066/2011-v3 / 2011 /1200/ 1366/ 1156/ 1155/ 1151/ 1150		
	AMD	AM4 / AM3+ / AM3 / AM2+ / AM2 / FM2+ / FM2 / FM1		
Dimensions	144.9 x 153.2 x 160 mm (5.7 x 6 x 6.3 inch)			
Heat Sink Material	6 Heat Pipes/ Aluminum Fins			
		140 mm Fan	120 mm Fan	
Fan	Dimensions (L x W x H)	140 x 140 x 25 mm (5.5 x 5.5 x 1 inch)	120 x 120 x 25 mm (4.7 x 4.7 x 1 inch)	
	Quantity (pcs)	2 PCS	1 PC	
	Speed (RPM)	650 ~ 1400 (PWM) ± 5%	650 ~ 1800 RPM (PWM) ± 5%	
	Airflow (CFM)	67 CFM (Max)	62 CFM (Max)	
	Noise Level (dBA)	10 ~ 27 dBA	8 ~ 27 dBA	
	Pressure (mmH2O)	2.25 mm H ₂ O (Max)	2.5 mm H ₂ O (Max)	
	MTTF	160,000 hours	160,000 hours	
	Power Connector	4-Pin (PWM)	4-Pin (PWM)	
	Rated Voltage (VDC)	12 VDC	12 VDC	
	Rated Current (A)	0.15 A	0.15 A	
	Safety Current	0.4 A	0.37 A	
	Power Consumption	1.8 W	1.8 W	
Warranty		5 years		

FEATURE HIGHLIGHTS



Premium Black Aluminum Top Cover

Black aluminum top cover matches all-black hardware throughout to offer a premium finish



Dual Tower Heatsink

Dual heatsink combination provides twice the surface area for better cooling



6 Heat Pipes with Nickel Plated Base

6 heat pipes and nickel plated base provides optimal coverage for exceptional cooling



Easy Mounting System

Exclusive All-In-One mounting design for easy installation



Dual SickleFlow 140 Fan

Twin fans utilize Push-Pull setup for optimal airflow and pressure



Optional SickleFlow 120

Optional 3rd SickleFlow 120mm fan included for necessary RAM compatibility and clearance