SICKLEFLOW EDGE 360

Introducing the SickleFlow Edge 360 ARGB, the latest addition to the renowned SickleFlow series. This cutting-edge fan boasts all the high-performance design features you expect from the SickleFlow product line, now with extra perks for an even better experience. Enlarged fan blades enhance cooling power, while the hollow frame structure ensures the fan remains lightweight without compromising durability. A single modular cable for both lighting and power streamlines setup, and with only 4 screws required, installation is a breeze. Enjoy customizable addressable RGB lighting, fully controllable via our in-house MasterCTRL software.

FEATURES

MULTI-FAN CONFIGURATION
Designed as a single-frame unit, the SickleFlow Edge 360 ARGB enhances internal airflow, effectively expelling heat and significantly improving cooling efficiency.

QUICK CONNECT
The SickleFlow Edge 360 ARGB uses a single modular cable for both lighting and power, providing a simplified cable management experience and cleaner aesthetics.

EASY INSTALLATION
With just 4 screws needed, it allows for versatile installation in either pull or exhaust configurations, offering a straightforward setup process that minimizes installation time and maximizes your enjoyment of optimal temperatures.

HOLLOW FRAME STRUCTURE
Featuring a hollow design with strategically placed triangular vents, this fan module remains lightweight yet incredibly durable, ensuring efficient airflow and long-lasting performance without adding unnecessary bulk to your build.

LOOP DYNAMIC BEARING
The SickleFlow Edge 360 ARGB features our loop dynamic bearing, our in-house bearings, preventing dust and oil leakage and enhancing operational stability and lifespan.

ADDRESSABLE RGB LIGHTING
Experience vibrant and personalized lighting effects with addressable RGB, fully controllable through our in-house MasterCTRL software for seamless customization.

SPECIFICATIONS

Product Name	SickleFlow Edge 360 ARGB	
Product Number	MFX-B2D-25TP2-R1	
Exterior Color	Black	
Dimension (L x W x H)	361 x 122 x 26.5 mm / 14.21 x 4.8 x 1.02 inch	
Profiles	Addressable 2 RGB	
Fan	Speed	690 – 2500 RPM ± 10%
	Airflow (max.)	322.8 m³/h (190 CFM)
	Pressure (max.)	3.54 mmH2O
	MTTF	> 160,000 hours
	Noise Level (max.)	38.5 dB (A)
	Bearing	Loop Dynamic Bearing
	Power Connector	4-Pin PWM
	Rated Voltage	12 VDC
	Rated Current	0.6 A
	Safety Current	0.8 A
	Power Consumption	6 W
	Weight	460 g (1.01 lbs)
Warranty	5 years	

SHIPPING DETAILS

EAN Code	4719512147870	
UPC Code	884102120190	
Net Weight	0.520	
Gross Weight	0.720	
Packaging dimension (L x W x H)	43.5 x 37 x 28	
Carton Dimension (L x W x H)	42 x 3.5 x 13	
Unit / Pallet	20	
Container 20 feet	With Pallet	6720
	Carton / Pallet	42
	Without Pallet	N/A
Container 40 feet	With Pallet	8400
	Carton / Pallet	42
	Without Pallet	N/A
Container 40 HQ	With Pallet	9600
	Carton / Pallet	48
	Without Pallet	N/A