



Specifications

Copyright © 2015 Dell Inc. All rights reserved. This product is protected by U.S. and international copyright and intellectual property laws. Dell and the Dell logo are trademarks of Dell Inc. in the United States and/or other jurisdictions. All other marks and names mentioned herein may be trademarks of their respective companies.

2015 - 03 Rev. A00

Regulatory model: P51F | Type: P51F001/P51F003 Computer model: Inspiron 15-5558/Inspiron 15-5551

Front

Left



Right



Base



Display



Power and battery-status light/hard-drive 1 activity light

Indicates the power and battery-charge status. Press Fn+H to toggle this light between hard-drive activity light and battery-status light.

Solid white

Power adapter is connected and the battery has more than 5% charge.

Amber

Off

Front

Computer is running on battery and the battery has less than 5% charge.

- Power adapter is connected and the battery is fully charged.
- Computer is running on battery and the battery has more than 5% charge.
- · Computer is in sleep state, hibernation, or turned off.





Left

Front



Left



Right



Base



Display



Power-adapter port

Connect a power adapter to provide power to your computer and charge the battery.

Network port (Inspiron 15-5558 only)

Connect an Ethernet (RJ45) cable from a router or a broadband modem for network or internet access.

HDMI port

Connect a TV or another HDMI-in enabled device. Provides video and audio output.

USB 3.0 port

Connect peripherals such as storage devices, printers, and so on. Provides data transfer speeds up to 5 Gbps.

5 Media-card reader

Reads from and writes to media cards.

Right

Front



Left



Right



Base



Display



Headset port

Connect a headphone, a microphone, or a headphone and microphone combo (headset).

USB 2.0 ports (2)

Connect peripherals such as storage devices, printers, and so on. Provides data transfer speeds up to 480 Mbps.

Optical drive

Reads from and writes to CDs and DVDs.

Security-cable slot

Connect a security cable to prevent unauthorized movement of your computer.



Left



Right



Base



Display

Base



Left-click area

Press to left click.

2 Touch pad

Move your finger on the touch pad to move the mouse pointer. Tap to left click.

Right-click area

Press to right click.

Power button

Press to turn on the computer if it is turned off, in sleep state, or in hibernate state.

Press to put the computer in Sleep state if it is turned on.

Press and hold for 4 seconds to force shut-down the computer.



NOTE: You can customize the power-button behaviour in Power Options. For more information, see Me and My Dell at dell.com/support.

Front



Left



Right



Base



Display

Display



Left microphone (Inspiron 15-5558 only) 1

Provides high-quality digital sound input for audio recording, voice calls, and so on.

Camera

Allows you to video chat, capture photos, and record videos.

Camera-status light

Turns on when the camera is in use.

4 **Right microphone**

Provides high-quality digital sound input for audio recording, voice calls, and so on.



Dimensions and weight

Height:

Touch 24.05 mm (0.95 in)

Non-touch 23.75 mm (0.94 in)

380 mm (14.96 in) Width

260.40 mm (10.25 in) Depth

Weight (maximum):

Touch 2.39 kg (5.27 lb)

2.24 kg (4.94 lb) Non-touch

NOTE: The weight of your laptop varies depending on the configuration ordered

and the manufacturing variability.



Dimensions and weight



information



Memory



Ports and connectors



Communications



Video



Audio



Storage



Media-card reader



Display Keyboard















System information

| Computer model | Inspiron 15-5558 | Inspiron 15-5551 |
|----------------|--|--|
| Processor | Intel Celeron Dual Core Processor Intel Pentium Quad Core Processor 4th generation Intel Core i3 Processor 5th generation Intel Core i3/i5/i7 Processor | Intel Celeron Dual Core Processor Intel Pentium Quad Core Processor |
| Chipset | Integrated in processor | Integrated in processor |



















Audio





















Memory

| | Inspiron 15-5558 | Inspiron 15-5551 |
|--------------------------|---|----------------------|
| Slots | Two SODIMM slots | One SODIMM slot |
| Туре | Dual-channel DDR3L | Single-channel DDR3L |
| Speed | 1600 MHz | 1600 MHz |
| Configurations supported | 2 GB, 4 GB, 6 GB, 8 GB, 12 GB, and 16 GB | 2 GB, 4 GB, and 8 GB |













Battery





Communications



















Ports and connectors

| External | ١ | |
|----------|----|--|
| | ι. | |

Network One RJ45 port (Inspiron 15-5558 only)

• One USB 3.0 port

• Two USB 2.0 ports

Audio/video • One HDMI port

• One headphone and microphone combo (headset) port

Internal:

NGFF slot One NGFF slot for Wi-Fi and Bluetooth combo card



















Audio



reader

Display















Communications

10/100 Mbps Ethernet controller integrated on system board **Ethernet** Wireless • Wi-Fi 802.11ac

- Wi-Fi 802.11b/g/n
- Bluetooth 4.0
- Intel WiDi (Windows only)





































Video

| | Inspiron 15-5558 | Inspiron 15-5551 |
|-------------|---|----------------------|
| Controller: | | |
| Integrated | Intel HD GraphicsIntel HD Graphics 4400Intel HD Graphics 5500 | Intel HD Graphics |
| Discrete | NVIDIA GeForce 920M | N/A |
| Memory: | | |
| Integrated | Shared system memory | Shared system memory |
| Discrete | Up to 4 GB DDR3L | N/A |











Memory



Ports and connectors



Communications



Video



Audio



Storage



Media-card reader



Keyboard















Audio

Controller Realtek Al C3234 with Waves MaxxAudio

Speakers Two

Speaker output:

Average 2 W

Peak 2.2 W

Microphone • Single microphone (Inspiron 15-5551 only)

• Digital array-microphones (Inspiron 15-5558 only)

Volume controls Media-control shortcut keys



Dimensions and weight







Memory



Ports and connectors



Communications



Video



Audio



Storage



Media-card reader



Display



Keyboard



Touch pad











Storage

Interface • SATA 3 Gbps (Inspiron 15-5551 only)

• SATA 6 Gbps (Inspiron 15-5558 only)

Hard drive One 2.5-inch drive (supports Intel Smart Response Technology)

Optical drive One 9.5 mm SATA drive

Drive supported DVD +/- RW







Memory











o | Au



reader

















Media-card reader

One SD card slot Type

Cards supported SD card





































Display

| Туре | 15.6-inch HD Touch 15.6-inch HD Non-touch 15.6-inch FHD Non-touch (Inspiron 15-5558 only) 15.6-inch FHD Touch (Inspiron 15-5558 only) | | | |
|----------------------|--|-------------------------|-------------------------|-------------------------|
| Refresh rate | 60 Hz | | | |
| Operating angle | 0 degrees (closed) to 135 degrees | | | |
| Controls | Brightness can be controlled using shortcut keys. | | | |
| | HD Touch | HD Non-touch | FHD Non-touch | FHD Touch |
| Resolution (maximum) | 1366 x 768 | 1366 x 768 | 1920 x 1080 | 1920 x 1080 |
| Pixel pitch | 0.2265 mm | 0.2265 mm | 0.161 mm | 0.17925 mm |
| Dimensions: | | | | |
| Height | 225.06 mm (8.86 in) | 224.3 mm (8.83 in) | 223.8 mm (8.81 in) | 225.06 mm (8.86 in) |
| Width | 366.63 mm (14.43 in) | 360 mm (14.17 in) | 359.5 mm (14.15 in) | 366.63 mm (14.43 in) |
| Diagonal | 396.24 mm (15.60 in) | 396.24 mm (15.60 in) | 396.24 mm (15.60 in) | 396.24 mm (15.60 in) |



weight

































Keyboard

Type

Standard keyboard

· Backlit keyboard (optional)

Shortcut keys

Some keys on your keyboard have two symbols on them. These keys can be used to type alternate characters or to perform secondary functions. To type the alternate character, press Shift and the desired key. To perform secondary functions, press Fn and the desired key.

NOTE: You can change the behavior of the shortcut keys by pressing Fn+Esc or by changing **Function Key Behavior** in BIOS setup program.

List of shortcut keys.











Memory



Ports and connectors







Video



Audio



Storage







Keyboard













Shortcut keys

| F1 | Mute audio |
|---------|--------------------------------------|
| F2 • | Decrease volume |
| F3 | Increase volume |
| F4 | Play previous track/chapter |
| F5 ► II | Play/Pause |
| F6 ►► | Play next track/chapter |
| F8 | Switch to external display |
| F9 | Search |
| F10 🛎 | Toggle keyboard backlight (optional) |
| F11 🔅 | Decrease brightness |
| F12 | Increase brightness |

| Fn + PrtScr | Turn off/on wireless |
|-------------|---|
| Fn + Insert | Sleep |
| Fn + Esc | Toggle Fn-key lock |
| Fn + H | Toggle between power and battery-status light/hard-drive activity light |
| Fn + Ctrl | Open application menu |
| Fn + B | Pause/Break |
| Fn + R | System request |
| Fn + S | Toggle scroll lock |



Camera

Resolution:

Still image 0.92 megapixel

1280 x 720 (HD) at 30 fps (maximum) Video

Diagonal viewing angle 74 degrees



















Audio





reader

















Touch pad

Resolution:

Horizontal 1211 dpi Vertical 1267 dpi

Dimensions:

Width 105 mm (4.13 in)

Height 80 mm (3.15 in)







































Battery

• 4 cell "smart" lithium ion (40 WHr) Type

• 4 cell "smart" lithium ion (47 WHr)

Dimensions:

Width 270 mm (10.63 in) Depth 37.5 mm (1.48 in)

Height 20 mm (0.79 in)

Weight (maximum) • 40 WHr-0.25 kg (0.55 lb)

• 47 WHr-0.26 kg (0.56 lb)

Voltage 14.8 VDC

Charging time when the 4 hours

computer is off (approximate)

Operating time Varies depending on operating conditions and can significantly reduce under

certain power-intensive conditions.

Life span (approximate) 300 discharge/charge cycles

Temperature range:

Operating 0°C to 35°C (32°F to 95°F)

-40°C to 65°C (-40°F to 149°F) Storage

Coin-cell battery CR-2032



Dimensions and weight



System information



Memory



Ports and connectors



Communications



Video



Audio



Storage



Media-card reader



Display



Keyboard





Touch pad



Battery



Power adapter



Computer environment



Power adapter

Type • 45 W

• 65 W

Input voltage 100 VAC-240 VAC

Input frequency 50 Hz-60 Hz

Input current (maximum):

45 W 1.30 A

65 W 1.60 A/1.70 A

Output current (maximum):

45 W 2.31 A

65 W 3.34 A

19.50 VDC Rated output voltage

Temperature range:

0°C to 40°C (32°F to 104°F) Operating

Storage -40°C to 70°C (-40°F to 158°F)



weight



information



Memory



Ports and connectors



Communications



Video



Audio



Storage



Media-card reader



Display



Camera













Computer environment

| Airborne contaminant level | G1 as defined by ISA-S71.04-1985 | |
|-----------------------------|--|--|
| | Operating | Storage |
| Temperature range | 0°C to 35°C (32°F to 95°F) | -40°C to 65°C (-40°F to 149°F) |
| Relative humidity (maximum) | 10% to 90% (non-condensing) | 0% to 95% (non-condensing) |
| Vibration (maximum)* | 0.66 GRMS | 1.30 GRMS |
| Shock (maximum) | 110 G [†] | 160 G [‡] |
| Altitude (maximum) | –15.2 m to 3048 m (–50 ft to 10,000 ft) | -15.2 m to 10,668 m (-50 ft to 35,000 ft) |

^{*} Measured using a random vibration spectrum that simulates user environment.





















Audio



reader















[†] Measured using a 2 ms half-sine pulse when the hard drive is in use.

[‡] Measured using a 2 ms half-sine pulse when the hard-drive head is in parked position.