

DELL27USB-C MONITOR **S2723HC**



THE WORLD'S # 1 MONITOR COMPANY*

*Source: IDC Worldwide Quarterly PC Monitor Tracker (Q3 2021)

DELL MONITORS-S-series

Simplified for greater space

27" monitor with the USB-C single-cable solution designed to keep your desktop clutter-free. Featuring built-in speakers and In-Plane Switching (IPS) technology.



Stunning, minimalist design

The new micro-texture design compliments every home office with its platinum silver pattern. Designed with 3-sided ultrathin bezel that provides flawless continuity.

Enhanced experience

Get superb clarity on a 27" FHD monitor with 99% sRGB color coverage and In-Plane-Switching (IPS) technology for rich color across a wide viewing angle. Includes dual 3W built-in speakers for an engaging audio experience. Dell's TÜV-certified ComfortView Plus feature



Clutter-free connectivity

The single-cable USB-C solution combines 65W power delivery with video, audio and data transmission in one cable creating more desk space for what's important.



DELL MONITORS-S-series S2723HC

27" FHD monitor with USB-C connectivity

Premium platinum silver finish For a polished look that

complements the home and office

In-Plane-Switching (IPS) Technology Experience superb visuals and rich colors including 99% sRGB color across a wide viewing angle

Enjoy superior sound with built-in 2 x 3W speakers

> Optimize eye comfort with built-in ComfortView Plus that reduces harmful blue light emissions

Smooth gameplay with AMD FreeSync[™] , and up to 75Hz refresh rate.

3-sided Ultrathin

seamless view

bezels design for a

For leisure gaming -

Two USB ports with one quick-access port that supports up to 10W charging are always within your reach.



Environmentally conscious

Monitor is shipped Styrofoam-free, all-in packaging made of at least 75% recycled cardboard.

The Dell Premium Panel Exchange allows a free panel replacement during the Limited Hardware Warranty* period even if only one bright pixel is found.

Click to explore: Dell 27 USB-C Monitor – S2723HC

*For copy of Ltd Hardware Warranty, write to Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 78682 or see //www.dell.com/warranty.

without sacrificing color performance

Adjust to your comfort

Tilt, swivel, pivot, and height adjustable

Easily charge and connect your laptop with USB-C connectivity and 65W of power delivery

DELL MONITORS-S-series S2723HC

Viewable image size (diagonal)68.6 cm (2Active display area (horizontal x vertical)597.89 mr (23.54" x 'Panel technologyIn-Plane SMaximum preset resolutionFull HD (1Aspect ratio16:9Pixel pitch0.3114 mrBrightness (typical)300 cd/m2Color gamut (typical)99% sRGEColor depth16.7 millioContrast ratio (typical)1,000 : 1Typical viewing angles (vertical / horizontal)178° / 178Response time (typical)4ms gray 1BacklightWhite LEDAudio Output2 x 3WAMD FreeSync™Yes, suppTÜV-certifiedYes, comDell Display Manager compatibilityYes, with 1Connectivity1 x USB T up to 65 VVESA mount compatibleYes, (cable Power AC input voltage/frequency/currentPower consumption (Operational)0.3 W (Gf 0.3 W (StarPower consumption (Operational)0.3 W (Gt 2.13 mrDimensions (HxWxD) Panel only363.6 mm	a x 336.31 mm 3.24") witching (IPS); Anti-glare with 3H hardness 20 x 1080) at 75Hz a x 0.3114 mm
Active display area (horizontal x vertical)597.89 mm (23.54" x - (23.54" x - Panel technologyMaximum preset resolutionFull HD (1Aspect ratio16:9Pixel pitch0.3114 mmBrightness (typical)300 cd/m²Color gamut (typical)99% sRGFColor depth16.7 millioContrast ratio (typical)1,000 : 1Typical viewing angles (vertical / horizontal)178° / 178Response time (typical)4ms gray 1BacklightWhite LEEAudio Output2 x 3WAMD FreeSyncTMYes, suppTÜV-certifiedYes, comDell Display Manager compatibilityYes, with 1 Up to 65 V with 10W iddownstreadStand adjustabilityHeight adj Tilt -5° / 2'Stand featuresBuilt-in call Yes (cablePower AC input voltage/frequency/current100 VAC 1Power consumption (Operational)0.3 W (Off 0.3 W (StatDimensions (HxWxD) Panel only363.6 mm 398.95 m	3.24") witching (IPS); Anti-glare with 3H hardness 20 x 1080) at 75Hz a x 0.3114 mm a colors
Maximum preset resolutionFull HD (1)Aspect ratio16:9Pixel pitch0.3114 mmBrightness (typical)300 cd/m²Color gamut (typical)99% sRGEColor depth16.7 millioContrast ratio (typical)1,000 : 1Typical viewing angles (vertical / horizontal)178° / 178Response time (typical)4ms grayBacklightWhite LEEAudio Output2 x 3WAMD FreeSyncTMYes, suppTÜV-certifiedYes, comDell Display Manager compatibilityYes, with 1Connectivity1 x USB TStand adjustabilityHeight adj Titt-5° / 2°Stand featuresBuilt-in callVESA mount compatibleYes, 100 mSecurity lock slotYes (cablePower AC input voltage/frequency/current100 VAC 4Power consumption (Operational)0.3 W (Off 0.3 W (State)Dimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm	220 x 1080) at 75Hz a x 0.3114 mm colors
Aspect ratio16:9Pixel pitch0.3114 mmBrightness (typical)300 cd/m²Color gamut (typical)99% sRGBColor depth16.7 millioContrast ratio (typical)1,000 : 1Typical viewing angles (vertical / horizontal)178° / 178Response time (typical)4ms grayBacklightWhite LEBAudio Output2 x 3WAMD FreeSyncTMYes, suppTÜV-certifiedYes, comDell Display Manager compatibilityYes, with 1Connectivity1 x USB T up to 65 V with 10W downstreadStand adjustabilityYes, 100 mSecurity lock slotYes, 100 mPower AC input voltage/frequency/current100 VAC 10Power consumption (Operational)0.3 W (Off 0.3 W (Stat)Border Width (Edge of Monitor to active area)5.99/6.01/ 21.33 mmDimensions (HXWXD) Panel only363.6 mmStand ed with stand(compressed/extended ht.)398.95 m	o gray in extreme mode
Pixel pitch0.3114 mrBrightness (typical)300 cd/m2Color gamut (typical)99% sRGEColor depth16.7 millioContrast ratio (typical)1,000 : 1Typical viewing angles (vertical / horizontal)178° / 178Response time (typical)4ms grayBacklightWhite LEDAudio Output2 x 3WAMD FreeSync™Yes, suppTÜV-certifiedYes, comDell Display Manager compatibilityYes, with 1Connectivity1 x USB Twith 10Wwith 10WdownstreadStand featuresStand featuresBuilt-in calVESA mount compatibleYes (cablePower AC input voltage/frequency/current100 VAC frequency/currentPower consumption (Operational)0.3 W (Off 0.3 W (State)Dimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm	o gray in extreme mode
Brightness (typical)300 cd/m²Color gamut (typical)99% sRGEColor depth16.7 millioContrast ratio (typical)1,000 : 1Typical viewing angles (vertical / horizontal)178° / 178Response time (typical)4ms gray fillBacklightWhite LEDAudio Output2 x 3WAMD FreeSyncTMYes, suppTÜV-certifiedYes, comDell Display Manager compatibilityYes, with fillConnectivity1 x USB TStand adjustabilityHeight adjTit -5° / 2'Stand featuresBuilt-in callYes (cablePower AC input voltage/frequency/current100 VAC fillPower consumption (Operational)0.3 W (Off 0.3 W (StatBorder Width (Edge of Monitor to active area)5.99/6.01/ 21.33 mmDimensions (HxWxD) Panel only363.6 mm 398.95 m	o gray in extreme mode
Color gamut (typical)99% sRGColor depth16.7 millioContrast ratio (typical)1,000 : 1Typical viewing angles (vertical / horizontal)178° / 178Response time (typical)4ms gray tBacklightWhite LEDAudio Output2 x 3WAMD FreeSync™Yes, suppTÜV-certifiedYes, comDell Display Manager compatibilityYes, with 1Connectivity1 x USB T up to 65 V with 10W idownstreadStand adjustabilityHeight adj Tilt -5° / 2°Stand featuresBuilt-in callVESA mount compatibleYes (cablePower AC input voltage/frequency/current100 VAC featuresPower consumption (Operational)0.3 W (Off 0.3 W (StallBorder Width (Edge of Monitor to active area)5.99/6.01/ 21.33 mmDimensions (HxWxD) Panel only363.6 mm 398.95 m	o gray in extreme mode
Color depth16.7 millioContrast ratio (typical)1,000 : 1Typical viewing angles (vertical / horizontal)178° / 178Response time (typical)4ms gray fillBacklightWhite LEDAudio Output2 x 3WAMD FreeSync TM Yes, suppTÜV-certifiedYes, comDell Display Manager compatibilityYes, with 1Connectivity1 x USB TUp to 65 Vup to 65 VStand adjustabilityHeight adjTilt -5° / 27Stand featuresBuilt-in callVESA mount compatibleYes (cablePower AC input voltage/frequency/current100 VAC fillPower consumption (Operational)0.3 W (Off 0.3 W (StallPower consumption (Operational)0.3 W (Off 0.3 W (StallDimensions (HxWxD) Panel only363.6 mm 398.95 m	o gray in extreme mode
Contrast ratio (typical)1,000 : 1Typical viewing angles (vertical / horizontal)178° / 178Response time (typical)4ms gray itBacklightWhite LEEAudio Output2 x 3WAMD FreeSync™Yes, suppTÜV-certifiedYes, comDell Display Manager compatibilityYes, with 1Connectivity1 x USB Tup to 65 VWith 10W IdownstreadStand adjustabilityStand adjustabilityHeight adjVESA mount compatibleYes (cablePower AC input voltage/frequency/current100 VAC for 0.3 W (Off 0.3 W (StatPower consumption (Operational)0.3 W (Off 0.3 W (StatBorder Width (Edge of Monitor to active area)5.99/6.01/ 21.33 mmDimensions (HxWxD) Panel only363.6 mmPanel only Monitor head with stand(compressed/extended ht.)363.6 mm	o gray in extreme mode
Typical viewing angles (vertical / horizontal)178° / 178Response time (typical)4ms gray itBacklightWhite LEDAudio Output2 x 3WAMD FreeSyncTMYes, suppTÜV-certifiedYes, ComDell Display Manager compatibilityYes, with 10Connectivity1 x USB T up to 65 W with 10W id downstreatStand adjustabilityHeight adj Tilt -5° / 2°Stand featuresBuilt-in call Yes (cableVESA mount compatibleYes (cable Power AC input voltage/frequency/currentPower consumption (Operational)0.3 W (Off 0.3 W (StallPower consumption (Operational)5.99/6.01/ 21.33 mmDimensions (HxWxD) Panel only363.6 mm 398.95 m	o gray in extreme mode
Response time (typical)4ms gray fillBacklightWhite LEEAudio Output2 x 3WAMD FreeSyncTMYes, suppTÜV-certifiedYes, comDell Display Manager compatibilityYes, with 1Connectivity1 x USB T up to 65 W with 10W I downstreatStand adjustabilityHeight adj Tilt -5° / 2*Stand featuresBuilt-in callVESA mount compatibleYes, 100 m Security lock slotPower AC input voltage/frequency/current100 VAC fillPower consumption (Operational)0.3 W (Offill 0.3 W (StatBorder Width (Edge of Monitor to active area)5.99/6.01/ 21.33 mm 363.6 mm 369.95 mtDimensions (HxWxD) Panel only363.6 mm 369.95 mt	o gray in extreme mode
Backlight White LEE Audio Output 2 x 3W AMD FreeSync™ Yes, support TÜV-certified Yes, commonstrain Dell Display Manager compatibility Yes, with 1 Connectivity 1 x USB T up to 65 V with 10W I Stand adjustability Height adj VESA mount compatible Yes, 100 m Security lock slot Yes (cable Power AC input voltage/frequency/current 100 VAC frequency/current Power consumption (Operational) 0.3 W (Off 0.3 W (State) Border Width (Edge of Monitor to active area) 5.99/6.01// 21.33 mm Dimensions (HxWxD) 363.6 mm Panel only 363.6 mm	
Audio Output2 x 3WAMD FreeSyncTMYes, suppTÜV-certifiedYes, ComDell Display Manager compatibilityYes, with 1Connectivity1 x USB TUp to 65 Vwith 10WdownstreatStand adjustabilityStand adjustabilityHeight adjTilt -5° / 2'Stand featuresStand featuresBuilt-in catVESA mount compatibleYes, 100 mSecurity lock slotYes (cablePower AC input voltage/frequency/current100 VAC mPower consumption (Operational)0.3 W (Off 0.3 W (StatBorder Width (Edge of Monitor to active area)5.99/6.01/ 21.33 mmDimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm	edgelight system
AMD FreeSync™Yes, supportTÜV-certifiedYes, CommonDell Display Manager compatibilityYes, with IConnectivity1 x USB Tup to 65 Wup to 65 WStand adjustabilityHeight adjStand featuresBuilt-in callVESA mount compatibleYes, 100 mSecurity lock slotYes (cablePower AC input voltage/frequency/current100 VAC mPower consumption (Operational)0.3 W (Off 0.3 W (StateBorder Width (Edge of Monitor to active area)5.99/6.01/2 21.33 mmDimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm 398.95 m	
TÜV-certifiedYes, ComDell Display Manager compatibilityYes, with IConnectivity1 x USB T up to 65 W with 10W I downstreadStand adjustabilityHeight adj Tilt -5° / 2°Stand featuresBuilt-in callVESA mount compatibleYes, 100 mSecurity lock slotYes (cablePower AC input voltage/frequency/current100 VAC fPower consumption (Operational)0.3 W (Off 0.3 W (StateBorder Width (Edge of Monitor to active area)5.99/6.01/ 21.33 mmDimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm 398.95 m	
Dell Display Manager compatibilityYes, with IConnectivity1 x USB T up to 65 W with 10W I downstreadStand adjustabilityHeight adj Tilt -5° / 2'Stand featuresBuilt-in callVESA mount compatibleYes, 100 m Yes, 100 mSecurity lock slotYes (cable Power AC input voltage/frequency/currentPower consumption (Operational)0.3 W (Off 0.3 W (Stall 21.33 mmBorder Width (Edge of Monitor to active area)5.99/6.01/ 21.33 mm 363.6 mm 398.95 mm	rts AMD FreeSync [™] technology with refresh rate of 75Hz
Connectivity1 x USB T up to 65 W with 10W I downstreadStand adjustabilityHeight adj Tilt -5° / 2*Stand featuresBuilt-in callVESA mount compatibleYes, 100 m Yes, 100 mSecurity lock slotYes (cable Yes (cablePower AC input voltage/frequency/current100 VAC m 100 VAC m 0.3 W (Off 0.3 W (StatPower consumption (Operational)0.3 W (Off 0.3 W (StatBorder Width (Edge of Monitor to active area)5.99/6.01/2 2.1.33 mm 363.6 mm 398.95 mm	ortView Plus ¹ with Flicker-free screen
up to 65 W with 10W downstreadStand adjustabilityHeight adj Tilt -5° / 2'Stand featuresBuilt-in callVESA mount compatibleYes, 100 mVESA mount compatibleYes, 100 mSecurity lock slotYes (cablePower AC input voltage/frequency/current100 VAC fPower consumption (Operational)0.3 W (Off 0.3 W (StatBorder Width (Edge of Monitor to active area)5.99/6.01/2Dimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm 398.95 m	ell EasyArrange
Tilt -5° / 2'Stand featuresBuilt-in calVESA mount compatibleYes, 100 mSecurity lock slotYes (cablePower AC input voltage/frequency/current100 VAC fPower consumption (Operational)0.3 W (Off 0.3 W (StateBorder Width (Edge of Monitor to active area)5.99/6.01/2Dimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm 398.95 mm	vpe-C upstream port (Alternate mode with DisplayPort 1.2, Power Delivery), 1 x Super Speed USB 5 Gbps (USB 3.2 Gen1) Type-A downstream port Power Charging, 1 x SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) Type-A n port, 1 x HDMI port (ver 1.4), HDCP 1.4, 1 x audio line-out port
VESA mount compatibleYes, 100 mSecurity lock slotYes (cablePower AC input voltage/frequency/current100 VAC fPower consumption (Operational)0.3 W (Off 0.3 W (StateBorder Width (Edge of Monitor to active area)5.99/6.01/2Dimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm 398.95 mm	istment up to 110mm °, Swivel -30° / 30°, Pivot -90° / 90°
Security lock slotYes (cablePower AC input voltage/frequency/current100 VAC frPower consumption (Operational)0.3 W (Off 0.3 W (StateBorder Width (Edge of Monitor to active area)5.99/6.01/2 21.33 mmDimensions (HxWxD) 	le management slot
Power AC input voltage/frequency/current 100 VAC ft Power consumption (Operational) 0.3 W (Off 0.3 W (State)) Border Width (Edge of Monitor to active area) 5.99/6.01// 21.33 mm Dimensions (HxWxD) 363.6 mm Panel only 363.6 mm Monitor head with stand(compressed/extended ht.) 398.95 mm	1m x 100 mm
AC input voltage/frequency/current100 VAC tPower consumption (Operational)0.3 W (Off 0.3 W (StateBorder Width (Edge of Monitor to active area)5.99/6.01/2Dimensions (HxWxD) Panel only Monitor head with stand(compressed/extended ht.)363.6 mm 398.95 mm	lock sold separately)
0.3 W (StateBorder Width (Edge of Monitor to active area)5.99/6.01// 21.33 mmDimensions (HxWxD) Panel onlyPanel onlyMonitor head with stand(compressed/extended ht.)398.95 mm	o 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 1.7 A (maximum)
Dimensions (HxWxD) 21.33 mm Panel only 363.6 mm Monitor head with stand(compressed/extended ht.) 398.95 mm	Mode) 17.3 W (On Mode) ndby Mode) 135 W (Max)
Panel only363.6 mmMonitor head with stand(compressed/extended ht.)398.95 mm	.01 mm (Top/Left/Right) (Bottom)
Weight	x 609.9 mm x 54.03 mm (14.32" x 24.01" x 2.13")
Panel only (for VESA)4.65 kg (1Monitor and cables with full packaging8.99 kg (1	i / 508.95 mm x 609.9 mm x 174.7 mm (15.71" / 20.04" x 24.01" x 6.88")
•	0.25 lbs)
	0.25 lbs)
What's Included Monitor pa 3.2 Gen 1 Regulatory ¹ ComfortView Plus feature reduces blue light emission and optimizes eye comfort without co ² Advanced Exchange Service: Replacement part/unit dispatched, if needed, following compl	0.25 lbs) 9.82 lbs) STAR certified, RoHS-compliant, BFR/PVC-reduced monitor (excluding

DELL 27 USB-CMONITOR -

Technical specifications subject to change without prior notice.

Product availability variability varias by country. Please contact your Dell representative for more information. Copyright 2022 Dell Inc. All rights reserved. Other trademarks or trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. Reproduction in any manner whatsoever without express written permission from Dell Inc. is strictly forbidden.