

Eaton 5E550I

Catalog Number: 5E550I

Eaton 5E Gen2 UPS IEC, 550 VA, 300W, Input: C14, Outputs: (4) C13, Tower

General specifications

Product Name	Catalog Number
Eaton 5E Gen2 UPS	5E550I
Product Length/Depth	Product Height
288 mm	148 mm
Product Width	Product Weight
100 mm	3.75 kg
Warranty	Compliances
2 year	CB
	LVD Directive
	EMC Directive
	RoHS Directive
	Packaging Directive
	WEEE Directive
	Batteries Directive



Certifications

IEC/EN 62040-1
IEC/EN 62040-2
CE
EAC
UKCA
Cm
Ukr
IEC/EN 62040-3

Termékjellemzők

Források

Secondary frequency - max

60 Hz

Wattage

300W

Form factor

Tower

Includes network card

No

Input connection

C14

Input voltage - min

140 V

Output voltage - max

257 V

Secondary frequency - min

50 Hz

Battery type

Sealed, lead-acid

Efficiency

95

Special features

Automatic Voltage Regulation (AVR)

Saves space with a compact tower design

Construction type

Free standing model

Output voltage - min

195 V

Color

Black

Extended battery capability

No

Output voltage range

195-257 V

Topology

Line-interactive

Surge protection

Yes

Input nominal voltage

230V default (220/230/240V)

Input frequency range

45-63 Hz

Internal bypass

No

Input voltage - max

300 V

Voltage type

AC

Phase (output)

1

Battery management

Automatic battery test, deep-discharge protection, cold-start capable

Auto shutdown function

No

Number of Outputs C13

4

Operating temperature - min

0 °C

VA rating

550 VA

Potential free switch contact

No

Receptacle

(4) C13

Phase (input)

1

Package contents

(2) IEC-IEC output cables

Quick start

Safety instructions

Feed type

1

Runtime graph

View runtime graph

User interface

LEDs

Battery quantity

1

Operating temperature - max

40 °C

Voltage

230V

Hot swap power

No

Temperature range

0° to 40°C (32° to 104°F)

Ethernet interface

No

Relative humidity

0-90% non-condensing

Output apparent power

550 VA

Rack mounting kit

No

Output frequency

50/60 Hz

Type of interface

None

Primary frequency - min

45 Hz

Battery rating

12 V / 4.5 Ah

Type

UPS

Output nominal voltage

230V

Expansion slots

No

Input voltage range

140-300 V

Nominal frequency

50/60 Hz

Primary frequency - max

63 Hz



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. Minden jogproperty of their respective
fenttartva.

Eaton is a registered trademark.

All other trademarks are
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)