# FUJITSU

# Data Sheet FUJITSU Display B24-8 TS Pro

#### Advanced display: 60.5 cm (23.8-inch) widescreen Best ergonomic and energy saving solutions for office applications

The FUJITSU Display B24-8 TS Pro is made for intensive office work. With visual and mechanical ergonomics this stylish black display enables fatigue-free working for hours in front of the screen. The large 60.5 cm (23.8-inch) screen allows you to keep always track of all open applications. This high-quality display works unfailingly around the clock. Easy connectivity, manageability and usability help you increase your productivity.

Excellent visual performance with wide In-Plane Switching (IPS) technology

Convenient and fatigue-proof longtime-usage with oustanding visual ergonomics for the office

Optimized and relaxed position with ergonomic stand featuring height adjust, swivel, tilt and 90° rotation

Flexible connectivity with HDMI, DVI, Analog and USB

Smart black design with space saving front frame and smart details like discretely integrated speakers and cable guide for a clean desk

Environment-friendly LED technology with unique, highly efficient energy saving solutions like ECO operation mode and ECO standby







CERTIFIE







## Technical details

Special features

Low blue light mode, In-Plane Switching (IPS) technology, 4-in-1 Stand, cable guide, Eco button for Eco mode and 3-coloured Eco status LED, Pivot, DisplayView™ IT Suite, 24/7 usage, Integrated speakers

	3-coloured Eco status LED, Pivot, DisplayView™ IT Suite, 24/7 usage, Integrated speakers
Ergonomic stand	
Stand	4-in-1 Stand
Height adjust range	150 mm
Picture height over desk (min)	40 mm
Rotation to portrait	90°
Tilt angle	-5° / +35°
Swivel angle	340°
Panel and backlit	In-Plane Switching (IPS) technology/LED
Screen Surface Treatment	Anti-glare, 3H hard coating
Contrast - typical	1,000:1
Contrast - advanced	20,000,000:1
Response time gray to gray typical	5 ms (in video mode)
Viewing angle (h/v) - typical	178°/178° CR10:1
Color performance	16.7 million colors (Hi-FRC)
Brightness - typical	250 cd/m2
Size and resolution	
Aspect ratio	16:9
Diagonal Size	60.5 cm (23.8-inch)
Resolution (native)	1,920 x 1,080 pixel
Resolution (interpolated)	1,680 x 1,050 pixel, 1,440 x 900 pixel, 1,366 x 768 pixel, 1,280 x 1,024 pixel, 1,280 x 720 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
Picture size	527 x 296 mm
Pixel Pitch	0.2745 mm
Frequencies	
Horizontal	30 - 82 kHz
Vertical	56 - 76 Hz
Connectivity	
HDMI	1 x HDMI
DVI	1 x DVI-D (HDCP)
VGA/D-SUB	1 x D-SUB
Audio signal output	3.5 mm stereo phone jack for head phone
Audio signal input	3.5 mm stereo phone jack
Audio sound output	2 x 2.0 W
USB downstream	2 x USB 2.0
USB upstream	1 x USB
Ease-of-use menu	
Languages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional
Brightness / Contrast	Brightness, Contrast, Black level, Auto level
Mode	sRGB, Office, Photo, Video, Low Blue Light
Color	sRGB, 5000K, 6500K, 7500K, Native, Custom Color (R,G,B)
Image adjust	Clock, Phase, H-Position, V-Position, Expansion
Audio	Mute, Volume, Input for HDMI and DP interface
Information	Model name, Serial number, Resolution/mode, Signal input
Setup	Input select, Language, DDC/CI, OSD-Timeout, Factory preset
Power consumption (typical, w/o sound)	
Soft switch off	0.16 W
Power save mode	0.17 W

Operating with EPA settings	14.95 W
Operating maximum brightness	23 W
Power supply	integrated
Power notes	Speakers off, without USB
Electrical values	Speakers on, without 05b
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	1
Compliance	
Europe	Energy Efficiency Class: A+, CE certification according to EC Directive 2004/108/EEC, EN 60950, RoHS, WEEE, IT-Eco- Declaration
Model	B24-8 T
Germany	TÜV GS
Russia	EAC
USA/Canada	FCC Class B, cTUVus
Australia/New Zealand	RCM
South Korea	KC
Argentina	TÜV-S
Singapore	S-Mark
Taiwan	BSMI
China	
Saudi Arabia	SASO
Global	TCO Certified Displays 7.0, ENERGY STAR® 7.0, TÜV Low Blue Light Certified, TÜV Flicker Free Certified, EPEAT® Gold (dedicated regions), ISO9241-307 (Pixel fault class I)
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates
Quality and Reliability	
MTBF (demonstrated)	70,000 h
Dimensions / Weight / Environmental	
Dimension without stand $(W \times D \times H)$	553 x 63.5 x 330.2 mm
	21.77 x 2.5 x 13.00 inch
Dimension with stand (W x D x H)	553 x 229.4 x 347 mm
	21.77 x 9.03 x 13.65 inch
Weight (packed)	7.4 kg
	16.20 lbs
Weight (unpacked)	5.6 kg
	12.35 lbs
Weight (Monitor only)	3.5 kg
	7.74 lbs
Operating ambient temperature	5 - 35 °C (41 - 95 °F)
Miscellaneous	
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Color	Black
Package content	
Display delivered accessories	DVI-D Data cable 1.8 m Audio cable 1.8 m USB-cable 1.8 m (USB-A to USB-B) Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Safety notes
Display delivered accessories notes	Data cables and audio cable detachable on display
Order information	· · /
Order Code	S26361-K1577-V160
EAN Code	4054681927121

Order information	
Country specific order code	BDL:K1577V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1577V160-CHN - with China power cable and CEL, mandatory for China BDL:K1577V160-ID - with Import label, mandatory for Indonesia (on demand) BDL:K1577V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed
Accessories information	Further helpful options: Available Privacy Filters: http://globalsp.ts.fujitsu.com/ dmsp/Publications/public/ds-Privacy-Filter.pdf Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/ Publications/public/pos-connectivity.pdf
Warranty	
Warranty period	3 years (depending on country)
Warranty type	Collect & Return Service (depending on country specific requirements)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

### More information

#### Fujitsu OPTIMIZATION Services

In addition to FUJITSU Display B24-8 TS Pro, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

#### **Computing Products**

www.fujitsu.com/global/products/computing/

#### Software

www.fujitsu.com/software/

#### More information

Learn more about FUJITSU Display B24-8 TS Pro, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

http://www.fujitsu.com/fts/displays

#### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www. fujitsu.com/global/about/environment



#### Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/ terms

© 2016 Fujitsu Technology Solutions GmbH

#### Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com/fts 2016-11-01 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms

© 2016 Fujitsu Technology Solutions GmbH