Fujitsu recommends Windows 10 Pro.



Data Sheet FUJITSU Desktop ESPRIMO P557/E85+

Your Flexible and Economic PC

The FUJITSU ESPRIMO P557/E85+ Desktop provides high-quality computing for your daily office tasks. It supports attractive price points and delivers the continuity needed for daily operations. Your valuable business data is protected by the latest TPM controller and the Erasedisk option. To meet your specific hardware needs it can be either individually configured or customized.

High performance and best price/performance ratio

Powerful and cost-effective microtower

■ 7th generation Intel® Core™ processor family

System management

The perfect answer to offload your IT administrators

 DeskView Admin enhances the management of the devices in your IT infrastructure during productive operation – even during remote periods and after hours

Made in Germany

Outstanding quality and stable functions based on German production standards

■ The development, production and functionality tests - all under one roof in Germany

Lifecycle

Hardware continuity for long-lasting project requirements

■ Managed lifecycle of up to 12 months

Meets ENERGY STAR® requirements

Low power consumption and low costs, without any loss in performance

■ 85% energy efficient power supply











Page 1 / 9 www.fujitsu.com/fts/ESPRIMO

Components

Intel® Core™ i7-7700 processor (4 Cores / 8 Threads, 3.60 GHz, up to 4.2 GHz, 8 MB, Intel® HD Graphics 630) * Intel® Core™ i7-6700 processor (4 Cores / 8 Threads, 3.40 GHz, up to 4.0 GHz, 8 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i5-7600 processor (4 Cores / 4 Threads, 3.50 GHz, up to 4.1 GHz, 6 MB, Intel® HD Graphics 630) * Intel® Core™ i5-7500 processor (4 Cores / 4 Threads, 3.40 GHz, up to 3.8 GHz, 6 MB, Intel® HD Graphics 630) * Intel® Core™ i5-7400 processor (4 Cores / 4 Threads, 3.00 GHz, up to 3.5 GHz, 6 MB, Intel® HD Graphics 630) * Intel® Core™ i5-6600 processor (4 Cores / 4 Threads, 3.30 GHz, up to 3.9 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i5-6500 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i3-6400 processor (4 Cores / 4 Threads, 2.70 GHz, up to 3.3 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i3-6100 processor (2 Cores / 4 Threads, 3.90 GHz, 3 MB, Intel® HD Graphics 630) Intel® Core™ i3-6100 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 530) ** Intel® Pentium® processor G4400 (2 Cores / 2 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 510) ** Intel® Pentium® Gold G4560 processor (2 Cores / 4 Threads, 3.50 GHz, 3 MB, Intel® HD Graphics 610)			
Intel® Core™ i5-7600 processor (4 Cores / 4 Threads, 3.50 GHz, up to 4.1 GHz, 6 MB, Intel® HD Graphics 630) * Intel® Core™ i5-7500 processor (4 Cores / 4 Threads, 3.40 GHz, up to 3.8 GHz, 6 MB, Intel® HD Graphics 630) * Intel® Core™ i5-7400 processor (4 Cores / 4 Threads, 3.00 GHz, up to 3.5 GHz, 6 MB, Intel® HD Graphics 630) * Intel® Core™ i5-6600 processor (4 Cores / 4 Threads, 3.30 GHz, up to 3.9 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i5-6500 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i5-6400 processor (4 Cores / 4 Threads, 2.70 GHz, up to 3.3 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i3-7100 processor (2 Cores / 4 Threads, 3.90 GHz, 3 MB, Intel® HD Graphics 630) Intel® Core™ i3-6100 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 530) ** Intel® Pentium® processor G4400 (2 Cores / 2 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 510) **			
Intel® Core™ i5-7500 processor (4 Cores / 4 Threads, 3.40 GHz, up to 3.8 GHz, 6 MB, Intel® HD Graphics 630) * Intel® Core™ i5-7400 processor (4 Cores / 4 Threads, 3.00 GHz, up to 3.5 GHz, 6 MB, Intel® HD Graphics 630) * Intel® Core™ i5-6600 processor (4 Cores / 4 Threads, 3.30 GHz, up to 3.9 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i5-6500 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i5-6400 processor (4 Cores / 4 Threads, 2.70 GHz, up to 3.3 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i3-7100 processor (2 Cores / 4 Threads, 3.90 GHz, 3 MB, Intel® HD Graphics 630) Intel® Core™ i3-6100 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 530) ** Intel® Pentium® processor G4400 (2 Cores / 2 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 510) **			
Intel® Core™ i5-7400 processor (4 Cores / 4 Threads, 3.00 GHz, up to 3.5 GHz, 6 MB, Intel® HD Graphics 630) * Intel® Core™ i5-6600 processor (4 Cores / 4 Threads, 3.30 GHz, up to 3.9 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i5-6500 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i5-6400 processor (4 Cores / 4 Threads, 2.70 GHz, up to 3.3 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i3-7100 processor (2 Cores / 4 Threads, 3.90 GHz, 3 MB, Intel® HD Graphics 630) Intel® Core™ i3-6100 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 530) ** Intel® Pentium® processor G4400 (2 Cores / 2 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 510) **			
Intel® Core™ i5-6600 processor (4 Cores / 4 Threads, 3.30 GHz, up to 3.9 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i5-6500 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i5-6400 processor (4 Cores / 4 Threads, 2.70 GHz, up to 3.3 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i3-7100 processor (2 Cores / 4 Threads, 3.90 GHz, 3 MB, Intel® HD Graphics 630) Intel® Core™ i3-6100 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 530) ** Intel® Pentium® processor G4400 (2 Cores / 2 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 510) **			
Intel® Core™ i5-6500 processor (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i5-6400 processor (4 Cores / 4 Threads, 2.70 GHz, up to 3.3 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i3-7100 processor (2 Cores / 4 Threads, 3.90 GHz, 3 MB, Intel® HD Graphics 630) Intel® Core™ i3-6100 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 530) ** Intel® Pentium® processor G4400 (2 Cores / 2 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 510) **			
Intel® Core™ i5-6400 processor (4 Cores / 4 Threads, 2.70 GHz, up to 3.3 GHz, 6 MB, Intel® HD Graphics 530) *, ** Intel® Core™ i3-7100 processor (2 Cores / 4 Threads, 3.90 GHz, 3 MB, Intel® HD Graphics 630) Intel® Core™ i3-6100 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 530) ** Intel® Pentium® processor G4400 (2 Cores / 2 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 510) **			
Intel® Core™ i3-7100 processor (2 Cores / 4 Threads, 3.90 GHz, 3 MB, Intel® HD Graphics 630) Intel® Core™ i3-6100 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 530) ** Intel® Pentium® processor G4400 (2 Cores / 2 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 510) **			
Intel® Core™ i3-6100 processor (2 Cores / 4 Threads, 3.70 GHz, 3 MB, Intel® HD Graphics 530) ** Intel® Pentium® processor G4400 (2 Cores / 2 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 510) **			
Intel® Pentium® processor G4400 (2 Cores / 2 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 510) **			
Intel® Pentium® Gold G4560 processor (2 Cores / 4 Threads, 3.50 GHz, 3 MB, Intel® HD Graphics 610)			
Intel® Celeron® processor G3930 (2 Cores / 2 Threads, 2.90 GHz, 2 MB, Intel® HD Graphics 610)			
			Intel® Celeron® processor G3900 (2 Cores / 2 Threads, 2.80 GHz, 2 MB, Intel® HD Graphics 510) **
*with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables) **6th generation Intel® processor			
Windows 10 Pro. Fujitsu recommends Windows 10 Pro.			
Windows 10 Home			
Windows 7 Professional 64-bit pre-installed (available through downgrade rights from Windows 10 Pro) (with 6th			
generation Intel® processors)			
Windows 7 Professional 32-bit (available through downgrade rights from Windows 10 Pro) (with 6th generation Intel® processors) openSUSE Linux (with 6th generation Intel® processors)			
Systems with 7th generation Intel® processor receive support from Microsoft with Windows 10 Home / Windows 10 only. For more information, please see Microsoft Support Lifecycle. Downgrade to Microsoft Windows 7 Professional only available with 6th generation Intel® processor Certified for SUSE Enterprise Desktop			
4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,400 MHz, UDIMM			
8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,133 MHz, UDIMM			
8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,400 MHz, UDIMM			
16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,400 MHz, UDIMM			
SSD PCIe, 1024 GB M.2 NVMe module			
SSD PCIe, 512 GB M.2 NVMe module			
SSD PCIe, 256 GB M.2 NVMe module			
SSD PCIe, 128 GB M.2 NVMe module			
SSD SATA III, 512 GB, 2.5-inch			
SSD SATA III, 256 GB, 2.5-inch			
SSD SATA III, 128 GB, 2.5-inch			
SSD SATA III, 512 GB, 2.5-inch, SED			
SSD SATA III, 256 GB, 2.5-inch, SED			
HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical			
HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch			
HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch			
HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch			
HDD SATA II, 5,400 rpm, 500 GB, 2.5-inch			

Page 2 / 9 www.fujitsu.com/fts/ESPRIMO

Hard disk notes	Up to 20 GB of HDD space is reserved for system recovery		
	SSHD (Solid State Hard Disk, Hybrid drive)		
	SSD (Solid State Disk)		
	SED (Self-Encrypting Drive)		
Graphics	VGA Extension Card		
	NVIDIA® Quadro® P400 , 2 GB		
	NVIDIA® NVS™ 315, 1 GB		
	NVIDIA® GeForce® GTX 745 2 GB FH, 2 GB		
	LFH59/ 2x DVI-I adapter cable		
	LFH59/ 2x DP adapter cable		
	DVI-I to VGA Adapter		
	DP to DVI-D (single link) Adapter Cable		
	AMD® Radeon RX 460, 4 GB		
	AMD® Radeon R7 340, 2 GB		
Drives (optional)	BD Triple Writer SATA ultra slim (tray)		
	DVD-ROM		
	DVD Super Multi		
	DVD Super Multi ultra slim (tray)		
	MultiCard Reader 24in1 USB 2.0 3.5"		
Interface add on cards/components (optional)			
	WLAN 802.11ac (2x2) PCIe x1 FH and BT 4.1 (dedicated regions only, up to BT 4.2 depending on OS version)		
	WLAN 802.11ac (2x2) PCIe x1 FH (dedicated regions only)		
	Gigabit Ethernet PCle x1		
	Dual serial card PCIe x1		

Base unit

Base unit	ESPRIMO P557/E85+				
Mainboard					
Mainboard type	D3500				
Formfactor	proprietary				
Chipset	Intel® H110				
Processor socket	LGA 1151				
Processor quantity maximum	1				
Supported capacity RAM (max.)	32 GB				
Memory slots	2 DIMM (DDR4)				
Memory frequency	2,400 MHz				
Memory notes	Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same.				
LAN	10/100/1,000 MBit/s Realtek RTL8111G				
BIOS version	AMI Aptio V UEFI Specification 2.5				
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) CSM (Compatibility Support Module)				
Audio type	On board				
Audio codec	Realtek ALC671				
Audio features	Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound				

3				
3				
<u> </u>				
Serial ATA III (6 Gbit) NCQ AHCI				
1				
1				
 1				
1				
6				
4				
optional via add on card				
2x USB 2.0; 2x USB 3.0; optional: 1x USB 3.1 Type-C (Gen2) via add on card and front adapter bay				
2x USB 2.0; 2x USB 3.0				
2x USB 2.0				
optional: via adapter card				
1				
1 (DVI-D)				
2				
- 1				
1 (optional)				
Anytime USB charge functionality				
Keyboard Mouse KBPC PX ECO Mouse M440 ECO				
5				
2				
5,25" bays: one bay in HH format, one bay for slim optical disc drive only				
1 x on mainboard for SSD NVMe (PCIe 2.0 x2; up to 10Gbit/s)				
1 x (240 mm / 9.45 inch) Full height				
2 x (174mm / 210 mm / 6.85 inch / 8.27 inch) Full height				
<u>-</u>				
Intel® HD Graphics 510, Intel® HD Graphics 530, Intel® HD Graphics 610, Intel® HD Graphics 630				
up to 1,782 MB				
1,024 x 768 pixel 1,280 x 1,024 pixel 1,360 x 768 pixel 1,440 x 900 pixel 1,600 x 900 pixel 1,600 x 1,200 pixel 1,680 x 1,050 pixel 1,920 x 1,080 pixel				

Page 4 / 9 www.fujitsu.com/fts/ESPRIMO

Graphics on board	
TFT resolution (DVI)	1,280 x 1,024 pixel
(1,360 x 768 pixel
	1,440 x 900 pixel
	1,600 x 900 pixel
	1,680 x 1,050 pixel 1,920 x 1,080 pixel
	1,920 x 1,200 pixel
TFT resolution (DisplayPort)	1,280 x 1,024 pixel
	1,360 x 768 pixel
	1,440 x 900 pixel
	1,600 x 900 pixel 1,680 x 1,050 pixel
	1,920 x 1,080 pixel
	1,920 x 1,200 pixel
	2,560 x 1,440 pixel
	2,560 x 1,600 pixel 3,440 x 1,440 pixel
	3,840 x 2,160 pixel
	4,096 x 2,304 pixel
Graphics features	Dual display support
	DirectX® 12
	HDCP support OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors)
	OpenGL® 4.4
	One DisplayPort connector can be converted to DVI-D or HDMI with an optional external adapter
	For multi monitoring mode, graphics card and integrated graphics run in parallel
	DisplayPort interface supports Ver. 1.2 incl. Multi-Stream DVI-D interface supports audio output for HDMI monitors
Graphics notes	up to 1 GB dedicated video memory (main memory owned and locked for graphics use)
diapilics flotes	Tested resolutions, depending on display type additional resolutions and frequencies possible
	Shared memory depending on main memory size and operating system
	Resolution (color depth up to 32 Bit/pixel)
	For TFT we recommend using 60Hz
Electrical values	
Power efficiency note	power supply efficiency (at 230V; 10% / 20% / 50% / 100% load) : 75% / 83% / 85% / 84%
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	280 W
Power factor correction/active power Monitor outlet	active No
	NO .
Power consumption	
Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=54214aad-322e-4b14-a447-8d82e2a569c9
Heat dissipation	
Heat dissipation notes	See white paper Energy Consumption
Noise emission	
Related Processors for noise	Intel® Core™ i7 7700
Standard noise emission	2x4 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))
Standard noise operation mode: CPU 50% load	3.6 B / 22 dB(A) Bystander; 25 dB(A) Operator position
	3.6 B / 23 dB(A) Bystander; 26 dB(A) Operator position

Page 5 / 9 www.fujitsu.com/fts/ESPRIMO

Noise emission					
Standard noise operation mode: Idle mode	3.5 B / 21 dB(A) Bystander; 24 dB(A) Operator position				
Standard noise operation mode: ODD load	4.6 B / 31 dB(A) Bystander; 37 dB(A) Operator position				
Standard noise operation mode: Office applications 2.0	3.5 B / 21 dB(A) Bystander; 24 dB(A) Operator position				
Blue angel noise emission according certification	According to ISO 7779:2010, ECMA-74 for max. possible configuration				
Blue angel noise notes / description	A-weighted sound power level Lwad (in B); 1B = 10dB				
Blue angel noise operation mode: HDD load	3.8 B = 38 dB (A)				
Blue angel noise operation mode: Idle mode	3.5 B = 35 dB (A)				
Blue angel noise operation mode: ODD load	4.6 B = 46 dB (A)				
Dimensions / Weight / Environmental					
Dimensions (W x D x H)	180 x 304 x 375 mm				
	7.09 x 11.97 x 14.76 inch				
Operating position	Vertical				
Weight	7 kg				
Weight (lbs)	15.50 lbs				
Weight notes	Actual weight may vary depending on configuration				
Operating ambient temperature	10 - 35 °C (50 - 95 °F)				
Operating relative humidity	5 - 85 % (relative humidity)				
Compliance					
Product	ESPRIMO P557/E85+				
Model	MI6W				
Germany	TÜV GS				
Europe	CE				
USA/Canada	FCC Class B cCSAus				
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 6.1 (dedicated regions) EPEAT® Gold (dedicated regions)				
China	CCC (planned) TPM 2.0 for China (optional)				
Compliance link	https://sp.ts.fujitsu.com/sites/certificates				
Additional Software					
Additional software (preinstalled)	Adobe® Reader® (pdf reader) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Microsoft Office (buy license to activate the pre-installed Microsoft Office)				
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL				

Page 6 / 9 www.fujitsu.com/fts/ESPRIMO

Manageability	
Manageability technology	DeskUpdate Driver management
manageability technology	PXE 2.1 Boot code
	Wake up from S5 (off mode)
	Intrusion switch (optional) WoL (Wake on LAN)
Manageability software	DeskView Client
manageability software	DeskView Instant BIOS Management
DeskView components	BIOS Management incl. Security
	Inventory Management Driver Management
	Alarm Management
Supported standards	DMI (Desktop Management Interface)
	SMBIOS (System Management BIOS) PXE (Preboot Execution Environment)
	WMI (Windows Management Instrumentation)
	WBEM (Web Based Enterprise Management)
	CIM (Common Information Model)
Security	
Physical Security	Kensington Lock support Eye for padlock
	Integrated cabinet lock (optional)
	Cable Cover (optional; covers and secures the ports and cables on rear side)
System and BIOS Security	Embedded security (TPM 2.0)
	EraseDisk (optional) Credential Guard Ready and Device Guard Capable (Windows 10, v. 1511)
	Boot sector virus protection
	Write protect option for the Flash EPROM
	Control of all USB interfaces External USB ports can be disabled separately
	Control of external interfaces
User Security	User and supervisor BIOS password
	Hard disk password
	Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional)
	Workplace Protect (secure authentication solution)
Workplace Embedded Tools	Auto BIOS Update via Fujitsu Server
	Auto BIOS Update via customer server (optional) Easy PC Protection (optional)
	Lasy PC Protection (optional)
Miscellaneous	Keyboard on (Special Fujitsu keyboard required)
	Thermal management
Serviceability	
Serviceability	EasyFix
	EasyChange for single 3.5" HDD (optional)
	EasyChange for optical drives
Packaging information	
Packaging dimension (mm)	439 x 296 x 499 mm
Packaging dimension (inch)	17.28 x 11.65 x 19.65 inch
Max. quantity / pallet	24
Material - Weight (g) Carton	1040 g
Material - Weight (lbs) Carton	2.29 lbs
Material - Weight (g) EPS / PS	165 g 0.36 lbs
Material - Weight (lbs) EPS / PS Material - Weight (g) PE	0.36 lbs 60 g
Material - Weight (lbs) PE	0.13 lbs
material Weight (103) FL	U. I J IUJ

Page 7 / 9 www.fujitsu.com/fts/ESPRIMO

Packaging information			
Packaging notes	If cable cover is inlcuded in packaging: 1.) packaging dimension is increasing to: $505 \times 298 \times 537$ mm / (19.88: 11.73 x 21.14 inch); 2.) material weight of carton will increase to 1400g; 3.) max. quantity/pallet = 18; printed documentation is bleached in chlorine free process		
Warranty			
Warranty period	1 year (for countries in EMEIA)		
Warranty type	Bring-In / Onsite Service (for countries within region EMEIA, for all other countries depending on local regulations)		
Warranty Terms & Conditions Product Related Services - the perfo			
Recommended Service	- 9x5, Onsite Response Time: Next Business Day		
Spare Parts availability	5 years after end of product life		
Service Weblink	http://www.fujitsu.com/fts/services/support		

Recommended Accessories

Recommended Accessories			
Display B24-9 TS	Safes and Safes	The FUJITSU Display B24-9 TS is a widescreen display with 1920 x 1080 Full HD resolution with a ultra-thin bezel housing. The monitor has a wide viewing angle that delivers consistent picture quality and DisplayView™ Click manageability software for further enhancing monitor features with a range of connectivity options ideal for medium- and large-sized businesses.	Order Code: S26361-K1643-V160
Display P24-8 WE Neo	The state of the s	The FUJITSU Display P24-8 WE Neo is a 16:10 IPS panel monitor that has DisplayView™ IT Suite that helps you activate features such Presence Sensor, Workplace Lighting Guide that promote the overall ergomomics and security of your workplace. The monitor has a 178°/178° wide viewing angle delivering a consistent picture quality and is ideal for CAD and Document Management applications.	Order Code: S26361-K1647-V140
Wireless Mouse Touch WI910		The Fujitsu Wireless Mouse Touch WI910 has a special touch sensitive surface that recognizes when your hand touches the mouse even before you move it. This provides nearly instantaneous wake-up from the intelligent energy saving sleep mode. Unbeatable responsiveness combines with features like switchable resolution, and three programmable buttons for a unique user experience.	Order Code: S26381-K465-L100
Wireless Keyboard Set LX901		The Wireless Keyboard LX901 is a top of the line desktop solution for	S26381-K565-L4** (**:



lifestyle orientated customers, who want only the best for their desk. This superb keyboard set offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption.

Country specific variation)

Page 8 / 9 www.fujitsu.com/fts/ESPRIMO

More information

Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO P557/ E85+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO P557/E85+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/qlobal/about/environment



Copyrights

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/ terms

© 2017 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com/fts 2018-09-03 EM-EN All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

© 2017 Fujitsu Technology Solutions GmbH