Fujitsu recommends Windows 10 Pro.

Data Sheet FUJITSU Notebook LIFEBOOK U728

Ultra-Mobile Meets Ultra Secure

The FUJITSU Notebook LIFEBOOK U728, based on the 8th generation Intel[®] Core[™] processor is a slim, light and stylish ultra-mobile notebook for business professionals who are always on the move. With its 31.8 cm (12.5-inch) and light weight of only 1.11 kg (2.44 lbs.) it provides excellent mobility. Ergonomic viewing is guaranteed with the anti-glare HD, FHD or optional FHD touch display options and the embedded palm vein or finger print sensor provide outstanding security. Smart design combines legacy interfaces like full-size VGA and easy upgradeability with a thin and durable housing. The common port replicator of the LIFEBOOK U family facilitates workplace sharing within today's modern workstyle.

Convenient upgradeability

Direct access to key components reduces upgrade time and costs

Battery, memory and internal storage can be changed easily

Family concept

Reduce your acquisition cost as well as the complexity of your IT equipment

Shared components such as the same classic or USB Type-C port replicator, AC Adapter, keyboard layout, BIOS and bit image across the ultra-mobile LIFEBOOK U family

Elegant design and mobility

Manage your workday with premium notebooks providing ultimate convenience to maximize your productivity

A remarkably slim 19 mm ultra-mobile notebook starting from 1.11 kg, HD or FHD display, antiglare, FHD touch panel option, aluminum/magnesium housing and optional backlit keyboard

Excellent security for your business

Enhance your security with outstanding features to best protect your notebook and company data from unauthorized access

Embedded palm vein or finger print sensor, Trusted Platform Module 2.0, integrated SmartCard reader

Premium connectivity

Stay flexible and productive within a modern workplace environment

- Full set of interfaces with, full-size LAN connector, full-size VGA port and USB Type-C
- Embedded 4G/LTE, WLAN and Bluetooth







Components

8 GB (1 module (s) 8 GB) DDR4, 2,400 MHz, S0 DIMM 16 GB (1 module (s) 16 GB) DDR4, 2,400 MHz, S0 DIMM Hard disk drives (internal) SSD SATA III, 1024 GB M.2 module, OPAL capable SSD SATA III, 52 GB M.2 module, OPAL capable SSD SATA III, 52 GB M.2 module, OPAL capable SSD SATA III, 52 GB M.2 module, OPAL capable SSD SATA III, 52 GB M.2 module, SED PCIe-SSD, 1024 GB M.2 NVMe module, SED PCIe-SSD, 512 GB M.2 NVMe module, SED PCIe-SSD, 512 GB M.2 NVMe module, SED PCIe-SSD, 526 GB M.2 NVMe module, SED PCIe-SSD, 512 GB M.2 NVMe module, SED PCIe-SSD, 512 GB M.2 NVMe module, SED PCIe-SSD, 516 GB M.2 NVMe module, SED PCIe-SSD, 516 GB M.2 NVMe module, SED SG/4 (optional) Up to 20 GB of HDD space is reserved for system recovery Internal storage interface: S-ATA III or PCIe Interface add on cards/components (optional) LTE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) UTE Sierra Wireless EM7305 (Cat. 3) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) LTE Sierra Wireless AC8265 11ac with integrated Bluetooth 4.2 Display 31.8 cm (12.5-inch), LED backlight, (HU), Anti-glare display, magnesium, 1,366 x 768 pixel,500: 1,220 cd/m ² 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS touchscreen, magnesium, 1,920 x 1,0	Base unit	LIFEBOOK U728
Processor Intel® Core® 17.8550U processor (1.9 GHz, up to 3.9 GHz, 8 MB) Intel® Core® 17.8550U processor (1.9 GHz, up to 3.7 GHz, 8 MB) Intel® Core® 15.8350U processor (1.6 GHz, up to 3.4 GHz, 6 MB) * Intel® Core® 15.8350U processor (1.6 GHz, up to 3.4 GHz, 6 MB) Intel® Core® 15.8350U processor (1.6 GHz, up to 3.4 GHz, 6 MB) * Intel® Core® 15.7300U processor (2.6 GHz, up to 3.4 GHz, 6 MB) * Intel® Core® 15.7300U processor (2.6 GHz, up to 3.4 GHz, 6 MB) * Memory modules 4 GB (1 module(s) 4 GB) DR4, 2,400 MHz, S0 DIMM 8 GB (1 module(s) 16 GB) DR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DR4, 2,400 MHz, S0 DIMM 16 GB (1 module(Operating systems	
Intel® Core [™] 17-85500 processor (1.8 GHz, up to 3.7 GHz, 8 MB) * Intel® Core [™] 15-83500 processor (1.7 GHz, up to 3.6 GHz, 6 MB) Intel® Core [™] 15-83500 processor (1.6 GHz, up to 3.6 GHz, 6 MB) * Intel® Core [™] 15-72000 processor (1.6 GHz, up to 3.6 GHz, 6 MB) * Intel® Core [™] 15-72000 processor (2.5 GHz, up to 3.1 GHz, 3 MB) *	Operating system pre-installed	
Intel® Core™ I5-8350U processor (1.7 GHz, up to 3.6 GHz, 6 MB) Intel® Core™ I5-8250U processor (2.6 GHz, up to 3.6 GHz, 6 MB) Intel® Core™ I5-7300U processor (2.6 GHz, up to 3.6 GHz, 3 MB) Intel® Core™ I5-7300U processor (2.6 GHz, up to 3.6 GHz, 3 MB) *Processor only for retail, SMB, education and government Memory modules 4 GB (1 module(s) 4 GB) DDR4, 2,400 MHz, S0 DIMM 8 GB (1 module(s) 6 GB) DDR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, S0 DIMM 16 GB (1 DDX Capable SDS SATA III, 25G GB M.2 module, OPAL capable SDS SATA III, 25G GB M.2 module, SED PCIe-SSD, 1024 GB M.2 NVMe module, SED PCIe-SSD, 25G GB M.2 NVMe module, SED <td rowspan="4">Processor</td> <td>Intel® Core™ i7-8650U processor (1.9 GHz, up to 3.9 GHz, 8 MB)</td>	Processor	Intel® Core™ i7-8650U processor (1.9 GHz, up to 3.9 GHz, 8 MB)
Intel® Core™ I5-8250U processor (1.6 GHz, up to 3.4 GHz, 6 M8) * Intel® Core™ I5-7300U processor (2.6 GHz, up to 3.1 GHz, 3 M8) **Processor only for retail, SM8, education and government Memory modules 4 GB (1 module(s) 4 GB) DDR4, 2,400 MHz, SO DIMM 8 G B (1 module(s) 8 GB) DDR4, 2,400 MHz, SO DIMM 16 GB (1 module(s) 8 GB) DDR4, 2,400 MHz, SO DIMM 16 GB (1 module(s) 8 GB) DDR4, 2,400 MHz, SO DIMM 16 GB (1 module(s) 8 GB) DDR4, 2,400 MHz, SO DIMM 16 GB (1 module(s) 8 GB) DDR4, 2,400 MHz, SO DIMM Hard disk drives (internal) SSD SATA III, 512 GB M.2 module, OPAL capable SSD SATA III, 526 GB M.2 module, OPAL capable SSD SATA III, 526 GB M.2 module, OPAL capable SSD SATA III, 526 GB M.2 module, SED PCIe-SSD, 1024 GB M.2 NVMe module, SED PCIe-SSD, 512 GB M.2 NVMe module, SED PCIe-SSD, 526 GB M.2 NVMe module, SED PCIe-SSD, 526 GB M.2 NVMe module, SED PCIe-SSD, 1024 GB M-12NVMe module, SED Interface add on cards/components (optional) ITE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) IITE sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) WLAN (optional) Inte! Dual Band Wireless-AC8265 11ac with integrated Bluetooth 4		Intel® Core™ i7-8550U processor (1.8 GHz, up to 3.7 GHz, 8 MB) *
Intel® Core® 15-7300U processor (2.6 GHz, up to 3.5 GHz, 3 MB) Intel® Core® 15-7200U processor (2.5 GHz, up to 3.1 GHz, 3 MB) * *Processor only for retail, SMB, education and government Memory modules 4 GB (1 module(s) 4 GB) DDR4, 2,400 MHz, SO DIMM 8 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, SO DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, SO DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, SO DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, SO DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, SO DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, SO DIMM 16 GB (1 module(s) 12 GB M.2 module, OPAL capable SSD SATA III, 1024 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 NVMe module, SED PCIe-SSD, 122 GB M.2 NVMe module, SED PCIe-SSD, 122 GB M.2 NVMe module, SED PCIe-SSD, 256 GB M.2 NVMe module, SED PCIe-SSD, 256 GB M.2 NVMe module, SED PCIe-SSD, 126 GB M.2 NVME MEDIA SED SATA III, 0 PCIE Interface add on cards/components (optional) IITE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) IITE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) IITE Sierra Wireless EM7455 (Cat. 6) (Downlink		Intel® Core™ i5-8350U processor (1.7 GHz, up to 3.6 GHz, 6 MB)
Intel® Core™ IS-7200U processor (2.5 GHz, up to 3.1 GHz, 3 MB) * *Processor only for retail, SMB, education and government Memory modules 4 GB (1 module(s) 4 GB) DDR4, 2,400 MHz, SO DIMM 8 GB (1 module(s) 4 GB) DDR4, 2,400 MHz, SO DIMM 16 GB (1 module(s) 6 GB) DDR4, 2,400 MHz, SO DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, SO DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, SO DIMM SSD SATA III, 1024 GB M.2 module, OPAL capable SSD SATA III, 512 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, SED PCIe-SSD, 1024 GB M.2 NVMe module, SED PCIe-SSD, 256 GB M.2 NVME ME modulE, SED PCIE-SSD, 256 GB M.2 NVME ME modulE, SED PCIE-SSD, 256 GB M.2 NVME ME modulE, SED PCIE-SSD, 256 GB M.2 NVME M.2 NO ME MADE MITHERS MAREMENTE (ptional) Intel® Dual Band Wireles-ACREMENTE INTERS MERCIENTERS MAREMENTE SUBARY MAINTERS AND		Intel® Core™ i5-8250U processor (1.6 GHz, up to 3.4 GHz, 6 MB) *
*Processor only for retail, SMB, education and government Memory modules 4 GB (1 module(s) 4 GB) DDR4, 2,400 MHz, S0 DIMM B GB (1 module(s) 16 GB) DDR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, S0 DIMM Hard disk drives (internal) SSD SATA III, 1024 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable POLe-SSD, 1024 GB M.2 NVMe module, SED POLe-SSD, 512 GB M.2 NVMe module, SED POLe-SSD, 526 GB M.2 NVMe module, SED POLe SSD, 526 GB M.2 NVMe module, SED POLe SSD, 526 GB M.2 NVMe module, SED POLe SSD, 512 GB M.2 NVMe module, SED POLe SSD, 512 GB M.2 NVMe module, SED POLe SSD, 526 GB M.2 NVMe module, SED Interface add on cards/components (optional) LTE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) LTE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) LTE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) LTE Si		Intel® Core™ i5-7300U processor (2.6 GHz, up to 3.5 GHz, 3 MB)
Memory modules 4 GB (1 module(s) 4 GB) DDR4, 2,400 MHz, SO DIMM 8 GB (1 module(s) 8 GB) DDR4, 2,400 MHz, SO DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, SO DIMM Hard disk drives (internal) SSD SATA III, 1024 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, SED PCIe-SSD, 512 GB M.2 NVMe module, SED PCIe-SSD, 526 GB M.2 NVMe module, SED PCIe-SSD, 526 GB M.2 NVMe module, SED Interface add on cards/components (optional) ITE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) ITE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) ITE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) ITE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) ITE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbi		Intel® Core™ i5-7200U processor (2.5 GHz, up to 3.1 GHz, 3 MB) *
8 GB (1 module(s) 8 GB) DDR4, 2,400 MHz, S0 DIMM 16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, S0 DIMM Hard disk drives (internal) SSD SATA III, 1024 GB M.2 module, OPAL capable SSD SATA III, 25G GB M.2 module, OPAL capable SSD SATA III, 25G GB M.2 module, OPAL capable SSD SATA III, 25G GB M.2 module, OPAL capable SSD SATA III, 25G GB M.2 module, SED PCIe-SSD, 1024 GB M.2 NVMe module, SED PCIe-SSD, 512 GB M.2 NVMe module, SED PCIe-SSD, 512 GB M.2 NVMe module, SED PCIe-SSD, 256 GB M.2 NVMe module, SED PCIe-SSD, 512 GB M.2 NVMe module, SED SG/4 (optional) Up to 20 GB of HDD space is reserved for system recovery Internal storage interface: S-ATA III or PCIe Interface add on cards/components (optional) UTE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) SG/4G (optional) ITE Sierra Wireless AC8265 11ac with integrated Bluetooth 4.2 Display 31.8 cm (12.5-inch).LED backlight,		*Processor only for retail, SMB, education and government
16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, S0 DIMM Hard disk drives (internal) SSD SATA III, 1024 GB M.2 module, OPAL capable SSD SATA III, 512 GB M.2 module, OPAL capable SSD SATA III, 512 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, SED PCIe-SSD, 1024 GB M.2 NVMe module, SED PCIe-SSD, 256 GB M.2 NVMe module, SED PCIe-SSD, 256 GB M.2 NVMe module, SED PCIe-SSD, 266 GB M.2 NVMe module, SED Interface add on cards/components (optional) LTE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) Interface add on cards/components (optional) LTE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) ILTE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) ILTE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) WLAN (optional) Intel® Dual Band Wireless-AC8265 11ac with integrated Bluetooth 4.2 Display 31.8 cm (12.5-inch), LED backlight, (HD), Anti-glare IPS touchscreen, magnesium, 1,920 x 1,080 pixel,700: 1,260 cd/m² 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS display, ma	Memory modules	4 GB (1 module(s) 4 GB) DDR4, 2,400 MHz, SO DIMM
Hard disk drives (internal) SSD SATA III, 1024 GB M.2 module, OPAL capable SSD SATA III, 512 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, SED PCIe-SSD, 1024 GB M.2 NVMe module, SED PCIe-SSD, 512 GB M.2 NVMe module, SED PCIe-SSD, 512 GB M.2 NVMe module, SED PCIe-SSD, 256 GB M.2 NVMe module, SED PCIe-SSD, 256 GB M.2 NVMe module, SED Hard disk notes One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software. Up to 20 GB of HDD space is reserved for system recovery Internal storage interface: S-ATA III or PCIe Interface add on cards/components (optional) LTE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) UTE Sierra Wireless EM7305 (Cat. 3) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) ITE Sierra Wireless FAR305 (Cat. 3) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) WLAN (optional) Intel® Dual Band Wireless-AC8265 11ac with integrated Bluetooth 4.2 Display 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare display, magnesium, 1,366 x 768 pixel,500:1,220 cd/m ² 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS touchscreen, magnesium, 1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-i		8 GB (1 module(s) 8 GB) DDR4, 2,400 MHz, SO DIMM
SSD SATA III, 512 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module, OPAL capable PCIe-SSD, 1024 GB M.2 NVMe module, SED PCIe-SSD, 512 GB M.2 NVMe module, SED PCIe-SSD, 256 GB M.2 NVMe module, SED PCIe-SSD, 256 GB M.2 NVMe module, SED Hard disk notes One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software. Up to 20 GB of HDD space is reserved for system recovery Internal storage interface: S-ATA III or PCIe Interface add on cards/components (optional) LTE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) LTE Sierra Wireless EM7305 (Cat. 3) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) TE Sierra Wireless -AC8265 11ac with integrated Bluetooth 4.2 Display 31.8 cm (12.5-inch), LED backlight, (HD), Anti-glare IPS display, magnesium, 1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS display, magnesium, 1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS display, magnesium, 1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS display, magnesium, 1,920 x 1,080 pixel,700:1,260 cd/m ²		16 GB (1 module(s) 16 GB) DDR4, 2,400 MHz, SO DIMM
SSD SATA III, 256 GB M.2 module, OPAL capable SSD SATA III, 256 GB M.2 module PCIe-SSD, 1024 GB M.2 NVMe module, SED PCIe-SSD, 512 GB M.2 NVMe module, SED PCIe-SSD, 256 GB M.2 NVMe module, SED Hard disk notes One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software. Up to 20 GB of HDD space is reserved for system recovery Internal storage interface: S-ATA III or PCIe Interface add on cards/components (optional) ITE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) ITE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) ITE Sierra Wireless EM7455 (Cat. 3) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) WLAN (optional) Intel® Dual Band Wireless-AC8265 11ac with integrated Bluetooth 4.2 Display 31.8 cm (12.5-inch), LED backlight, (HD), Anti-glare display, magnesium, 1,366 x 768 pixel,500: 1,220 cd/m ² 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS display, magnesium, 1,920 x 1,080 pixel,700: 1,260 cd/m ² 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS display, magnesium, 1,920 x 1,080 pixel,700: 1,260 cd/m ² 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS display, magnesium, 1,920 x 1,080 pixel,700: 1,260 cd/m ² 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS display, magnesium, 1,920 x 1,080 pixel,700: 1,260 cd/m ² 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS display, magnesium, 1,920 x 1,080 pixel,700: 1,260 cd/m ² 31.8 cm (12.5-inch), LED	Hard disk drives (internal)	SSD SATA III, 1024 GB M.2 module, OPAL capable
SSD SATA III, 256 GB M.2 module PCIe-SSD, 1024 GB M.2 NVMe module, SED PCIe-SSD, 512 GB M.2 NVMe module, SED PCIe-SSD, 256 GB M.2 NVMe module, SED Hard disk notes One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software. Up to 20 GB of HDD space is reserved for system recovery Internal storage interface: S-ATA III or PCIe Interface add on cards/components (optional) LTE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) ITE Sierra Wireless EM7305 (Cat. 3) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) ITE Sierra Wireless EM7305 (Cat. 3) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) WLAN (optional) Intel® Dual Band Wireless-AC8265 11ac with integrated Bluetooth 4.2 Display 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS touchscreen, magnesium, 1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS display, magnesium, 1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS display, magnesium, 1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS display, magnesium, 1,920 x 1,080 pixel,700:1,260 cd/m ²		SSD SATA III, 512 GB M.2 module, OPAL capable
PCIe-SSD, 1024 GB M.2 NVMe module, SED PCIe-SSD, 512 GB M.2 NVMe module, SED PCIe-SSD, 256 GB M.2 NVMe module, SED Hard disk notes One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software. Up to 20 GB of HDD space is reserved for system recovery Internal storage interface: S-ATA III or PCIe Interface add on cards/components (optional) LTE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) LTE Sierra Wireless EM7305 (Cat. 3) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) WLAN (optional) Intel® Dual Band Wireless-AC8265 11ac with integrated Bluetooth 4.2 Display 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS touchscreen, magnesium, 1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS display, magnesium, 1,920 x 1,080 pixel,700:1,260 cd/m ² Multimedia Multimedia		SSD SATA III, 256 GB M.2 module, OPAL capable
PCIe-SSD, 512 GB M.2 NVMe module, SED PCIe-SSD, 256 GB M.2 NVMe module, SED Hard disk notes One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software. Up to 20 GB of HDD space is reserved for system recovery Internal storage interface: S-ATA III or PCIe Interface add on cards/components (optional) LTE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) LTE Sierra Wireless EM7305 (Cat. 3) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) WLAN (optional) Intel® Dual Band Wireless-AC8265 11ac with integrated Bluetooth 4.2 Display 31.8 cm (12.5-inch),LED backlight, (HUI HD),Anti-glare IPS touchscreen,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-inch),LED backlight, (Full HD),Anti-glare IPS display,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² Multimedia Multimedia		SSD SATA III, 256 GB M.2 module
PCIe-SSD, 256 GB M.2 NVMe module, SED Hard disk notes One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software. Up to 20 GB of HDD space is reserved for system recovery Internal storage interface: S-ATA III or PCIe Interface add on cards/components (optional) ITE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) ITE Sierra Wireless EM7305 (Cat. 3) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) WLAN (optional) Intel® Dual Band Wireless-AC8265 11ac with integrated Bluetooth 4.2 Display 31.8 cm (12.5-inch), LED backlight, (HD), Anti-glare display, magnesium, 1,366 x 768 pixel,500: 1,220 cd/m ² 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS touchscreen, magnesium, 1,920 x 1,080 pixel,700: 1,260 cd/m ² 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS display, magnesium, 1,920 x 1,080 pixel,700: 1,260 cd/m ² Multimedia Multimedia		PCIe-SSD, 1024 GB M.2 NVMe module, SED
Hard disk notes One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software. Up to 20 GB of HDD space is reserved for system recovery Internal storage interface: S-ATA III or PCle Interface add on cards/components (optional) ITE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) 3G/4G (optional) ITE Sierra Wireless EM7455 (Cat. 3) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) WLAN (optional) Intel® Dual Band Wireless-AC8265 11ac with integrated Bluetooth 4.2 Display 31.8 cm (12.5-inch),LED backlight,(HD),Anti-glare display,magnesium,1,366 x 768 pixel,500:1,220 cd/m ² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS touchscreen,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS display,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS display,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS display,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS display,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS display,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ²		PCIe-SSD, 512 GB M.2 NVMe module, SED
Accessible capacity may vary, also depending on used software. Up to 20 GB of HDD space is reserved for system recovery Internal storage interface: S-ATA III or PCIe Interface add on cards/components (optional) ITE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) ITE Sierra Wireless EM7305 (Cat. 3) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) WLAN (optional) Intel® Dual Band Wireless-AC8265 11ac with integrated Bluetooth 4.2 Display 31.8 cm (12.5-inch),LED backlight, (HD),Anti-glare display,magnesium,1,366 x 768 pixel,500:1,220 cd/m² 31.8 cm (12.5-inch),LED backlight, (Full HD),Anti-glare IPS touchscreen,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m² 31.8 cm (12.5-inch),LED backlight, (Full HD),Anti-glare IPS display,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m² Multimedia Multimedia		PCIe-SSD, 256 GB M.2 NVMe module, SED
Up to 20 GB of HDD space is reserved for system recovery Internal storage interface: S-ATA III or PCIe Interface add on cards/components (optional) 3G/4G (optional) ITE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) ITE Sierra Wireless EM7305 (Cat. 3) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) WLAN (optional) Intel® Dual Band Wireless-AC8265 11ac with integrated Bluetooth 4.2 Display 31.8 cm (12.5-inch),LED backlight,(HD),Anti-glare display,magnesium,1,366 x 768 pixel,500:1,220 cd/m ² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS touchscreen,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS display,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² Multimedia Multimedia	Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.
Internal storage interface: S-ATA III or PCle Interface add on cards/components (optional) 3G/4G (optional) ITE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) ITE Sierra Wireless EM7305 (Cat. 3) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) WLAN (optional) Intel® Dual Band Wireless-AC8265 11ac with integrated Bluetooth 4.2 Display 31.8 cm (12.5-inch),LED backlight,(HD),Anti-glare display,magnesium,1,366 x 768 pixel,500:1,220 cd/m ² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS touchscreen,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² Multimedia		
Interface add on cards/components (optional) ITE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) ITE Sierra Wireless EM7305 (Cat. 3) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) WLAN (optional) Intel® Dual Band Wireless-AC8265 11ac with integrated Bluetooth 4.2 Display 31.8 cm (12.5-inch),LED backlight,(HD),Anti-glare display,magnesium,1,366 x 768 pixel,500:1,220 cd/m ² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS touchscreen,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS display,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² Multimedia Xultimedia		
(optional) LTE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) 3G/4G (optional) LTE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) WLAN (optional) Intel® Dual Band Wireless-AC8265 11ac with integrated Bluetooth 4.2 Display 31.8 cm (12.5-inch),LED backlight,(HD),Anti-glare display,magnesium,1,366 x 768 pixel,500:1,220 cd/m ² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS touchscreen,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS display,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² Multimedia		
3G/4G (optional) LTE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s) LTE Sierra Wireless EM7305 (Cat. 3) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s) WLAN (optional) Intel® Dual Band Wireless-AC8265 11ac with integrated Bluetooth 4.2 Display 31.8 cm (12.5-inch),LED backlight,(HD),Anti-glare display,magnesium,1,366 x 768 pixel,500:1,220 cd/m ² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS touchscreen,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS display,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² Multimedia		
WLAN (optional) Intel® Dual Band Wireless-AC8265 11ac with integrated Bluetooth 4.2 Display 31.8 cm (12.5-inch),LED backlight,(HD),Anti-glare display,magnesium,1,366 x 768 pixel,500:1,220 cd/m² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS touchscreen,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS display,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m² Multimedia	3G/4G (optional)	LTE Sierra Wireless EM7455 (Cat. 6) (Downlink speed up to 300 Mbit/s, Uplink speed up to 50 Mbit/s)
Display 31.8 cm (12.5-inch),LED backlight,(HD),Anti-glare display,magnesium,1,366 x 768 pixel,500:1,220 cd/m ² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS touchscreen,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS display,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS display,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² Multimedia		LTE Sierra Wireless EM7305 (Cat. 3) (Downlink speed up to 100 Mbit/s, Uplink speed up to 50 Mbit/s)
31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS touchscreen, magnesium, 1,920 x 1,080 pixel, 700:1,260 cd/m ² 31.8 cm (12.5-inch), LED backlight, (Full HD), Anti-glare IPS display, magnesium, 1,920 x 1,080 pixel, 700:1,260 cd/m ² Multimedia	WLAN (optional)	Intel [®] Dual Band Wireless-AC8265 11ac with integrated Bluetooth 4.2
m ² 31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS display,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ² Multimedia	Display	31.8 cm (12.5-inch),LED backlight,(HD),Anti-glare display,magnesium,1,366 x 768 pixel,500:1,220 cd/m ²
Multimedia		
		31.8 cm (12.5-inch),LED backlight,(Full HD),Anti-glare IPS display,magnesium,1,920 x 1,080 pixel,700:1,260 cd/m ²
Camera Optional: Built-in webcam, HD (Microsoft® Lync™)	Multimedia	
	Camera	Optional: Built-in webcam, HD (Microsoft® Lync™)

Base unit

Base unit

LIFEBOOK U728

General system information	
Processor	Intel® Core™ processor
10(2350)	
	()
Chipset	Integrated
Supported capacity RAM (max.)	32 GB
Memory slots	2 SO DIMM (DDR4, 2400 MHz)
LAN	10/100/1,000 MBit/s Intel® I219LM
BIOS version	UEFI Specification 2.5
BIOS features	InsydeH20 Bios
Audio type	On board
Audio codec	Realtek ALC255 with MaxxAudio
Audio features	Stereo speakers
MIL-STD tested	Yes, selected MIL-STD-810G tests passed. MIL-STD-810G test results are not a guarantee of future performance under identified test conditions. Accidental damage is not covered under standard international limited warranty.
Display	
Display notes	ISO 9241-307 - Pixel class II HD - Viewing angle: Left/Right 45°, Top 20°, Bottom 40°; Color Gammut: 45% FHD - Viewing angle: Left/Right 80°, Top 80°, Bottom 80°; Color Gammut: 50%
Graphics	
Base unit	LIFEBOOK U728
TFT resolution (DisplayPort)	up to 4,096 × 2,160
TFT resolution (VGA)	up to 1,920 x 1,200
TFT resolution (DVI on Port Replicator)	up to 1,920 x 1,200
Graphics brand name	Intel® HD Graphics 620
Graphics features	3 Display Support
Graphics notes	Shared memory depending on main memory size and operating system
Interfaces	
DC-in	1
Audio: line-out / headphone	1 (combo port with Audio line-in)
Audio: line-in / microphone	1 (combo port with Audio line-out)
Internal microphones	2x digital array microphones (optional)
USB 3.1 Gen1 (USB 3.0) total	2x Type-A (1 with Anytime USB charge functionality) 1x Type-C (with Power Delivery functionality)
USB Туре-С	1
VGA	1
DisplayPort	1
Ethernet (RJ-45)	1 (with status LED)
Memory card slots	1 microSD up to 2GB, microSDHC up to 32GB, microSDXC up to 128GB Speed Class: up to UHS-I
SmartCard slot	1 (optional)
SIM card slot	1 (only for models with integrated 4G/LTE module)
Port Replicator interfaces (optional)	
DC-in	1 (19V)
Power on switch	1
Audio: headphone	1
Audio: microphone	1
USB 3.1 Gen1 (USB 3.0) total	4х Туре-А 2х Туре-С
DisplayPort	2
VGA	1

Port Replicator interfaces (optional)	
DVI	1
Ethernet (RJ-45)	1 (10/100/1000)
Kensington Lock support	1 (Portrep only, Portrep option with key lock to secure Portrep & System)
Keyboard and pointing devices	
	Keyboard w/o touchstick (spill-resistant)#Keyboard w/ touchstick#Backlight keyboard w/o touchstick (spill-resistant
	Number of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 1.7 mm
	Multi gesture touchpad with two mouse buttons Status LED
	Power Button
Wireless technologies	
Antennas	2 Dual band WLAN antennas, 2 LTE antennas optional
Bluetooth	v4.2
WLAN encryption	WEP, WPA, WPA2
WLAN notes	Import and usage according to country-specific regulations.
GPS	Embedded in 3G/4G module if configured with WWAN
Power supply	-
AC Adapter	19 V / 65 W (3.42 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) slim and light AC-Adapter
ne Adapter	19 V / 80 W (4.22 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) 0-Watt AC Adapter technology
	19 V / 90 W (4.72 A), 100 V - 240 V, 50 Hz - 60 Hz, 3-pin (grounded) AC-Adapter
Notes	65W/80W AC Adapter for usage with system/ 90W AC Adapter for usage with Port Replicator
lst battery options	Li-Ion battery 3-cell, 45 Wh
lst battery	Lithium Polymer battery 3-cell
Battery features	Quick Charge: 80% in 1 h
Runtime 1st battery	up to 13h 10min.
Battery notes	Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime.
Noise emission	
Noise emission	Please refer to the Eco Declaration
Dimensions / Weight / Environmental	
Dimensions (W x D x H)	302 x 209 x 19.0 (non-touch and touch) mm
	11.89 x 8.23 x 0.75 (non-touch and touch) inch
Weight	From 1.11 kg (non touch), 1.21kg (touch)
Weight (lbs)	From 2.44 lbs (non touch), 2.67 (touch) lbs
Weight notes	Weight may vary depending on actual configuration
Operating ambient temperature	5 - 35 °C (41 - 95 °F)
Operating relative humidity	20 - 80 %
Product	
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Additional Software	
Additional software (preinstalled)	McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Waves MaxxAudio (audio enhancer) Fujitsu Plugfree Network (network management utility) Fujitsu Anytime USB Charge Utility Fujitsu Battery Utility Fujitsu Function Manager

Additional Software	
Additional software (optional)	Microsoft Office (buy license to activate the pre-installed Microsoft Office) CyberLink YouCam (webcam software) Drivers & Utilities DVD (DUDVD) Recovery DVD for Windows®
Manageability	
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN) Intel® vPro™ technology iAMT 11.6 (depending on processor)
Manageability software	DeskView Client DeskView Instant BIOS Management
DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management
Supported standards	WMI (Windows Management Instrumentation) PXE (Preboot Execution Environment) DMI (Desktop Management Interface) SMBIOS (System Management BIOS) CIM (Common Information Model) BootP (made4you)
Manageability link	http://www.fujitsu.com/fts/manageability
Security	
System and BIOS Security	Optional: Trusted Platform Module (TPM 2.0) EraseDisk (optional)
User Security	Integrated palm vein sensor (optional) Embedded fingerprint sensor (optional) Access protection via internal SmartCard reader (optional) Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)

Warranty	
Warranty Terms & Conditions http://support.ts.fujitsu.com/warranty Product Related Services - the perfect extension	
Recommended Service	X - 9x5, Onsite Response Time: Next Business Day
Service Weblink	htttp://ts.fujitsu.com/Supportservice

Recommended Accessories

More information

Fujitsu products, solutions & services

In addition to FUJITSU Notebook LIFEBOOK U728, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Notebook LIFEBOOK U728, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/fts/mobile

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www. fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www. fujitsu.com/fts/resources/navigation/terms-ofuse.html

Copyright 2018 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

CONTACT

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com/fts 2018-03-05 EM-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/fts/resources/ navigation/terms-of-use.html

Copyright 2018 Fujitsu Technology Solutions GmbH