

Data Sheet FUJITSU Display E24-8 TS Pro

Best-in-class wide screen office monitor that combines performance with energy savings

The FUJITSU Display E24-8 TS Pro combines robust business performance with cost savings. It has Integrated speakers, In-Plane Switching (IPS) technology with Full HD for supreme audio visual experience required by business professionals. The E24-8 TS Pro comes with the DisplayPort, DVI (HDCP), VGA interfaces and is an extremely energy efficient monitor for demanding business environments.

In-Plane Switching (IPS) technology with FHD resolution that delivers accurate and sharp picture quality

Ergonomic design in a matt black slender housing that helps you save on desk space and have a clean working area

Direct access keys on the monitor housing for brightness, mode, input, audio, menu and ECO savings

Five lighting modes that help users switch from sRGB, Office applications, Photo, Video and Low Blue Light for varied lighting conditions

Anti-glare and flicker-free backlight feature for working without straining your eyes







CERTIFIED







Technical details

Special features

In-Plane Switching (IPS) technology, LED backlight panel, Keep aspect ratio option, headset connector, Eco control button, Integrated speakers

| | button, Integrated speakers |
|--------------------------------------|--|
| Ergonomic stand | |
| Stand | removable |
| Picture height over desk (min) | 63 mm |
| Tilt angle | -5° / +22° |
| Picture performance | |
| Panel and backlit | In-Plane Switching (IPS) technology/LED |
| Screen Surface Treatment | Anti-glare, 3H hard coating |
| Contrast - typical | 1,000:1 |
| Contrast - advanced | 20,000,000:1 |
| Response time gray to gray typical | 5 ms (in video mode) |
| Viewing angle (h/v) - typical | 178°/178° |
| Color performance | 16.7 million colors (Hi-FRC) |
| Brightness - typical | 250 cd/m2 |
| Size and resolution | |
| Aspect ratio | 16:9 |
| Diagonal Size | 60.5 cm (23.8-inch) |
| Resolution (native) | 1,920 x 1,080 pixel |
| Resolution (interpolated) | 1,680 x 1,050 pixel, 1,440 x 900 pixel, 1,280 x 1,024 pixel, 1,280 x 720 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel |
| Picture size | 527 x 296 mm |
| Pixel Pitch | 0.2745 mm |
| Frequencies | |
| Horizontal | 30 - 82 kHz |
| Vertical | 56 - 76 Hz |
| Connectivity | |
| DisplayPort | 1 x DisplayPort |
| DVI | 1 x DVI-D (HDCP) |
| VGA/D-SUB | 1 x D-SUB |
| Audio signal output | 3.5 mm stereo phone jack |
| Audio signal input | 3.5 mm stereo phone jack |
| Audio sound output | 2 x 2.0 W |
| Ease-of-use menu | |
| Direct Access Keys | Brightness, ECO, Input, Mode, Audio, Menu |
| Languages | Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese simply, Chinese traditional |
| Brightness / Contrast | Brightness, Contrast, Black level, Auto level |
| Mode | sRGB, Office, Photo, Video, Low Blue Light |
| Color | sRGB, 5000K, 6500K, 7500K, Native, Custom Color (R,G,B) |
| lmage adjust | Clock, Phase, H-Position, V-Position, Expansion |
| Audio | Mute, Volume, Input for DP interface |
| Information | Model name, Serial number, Signal input, Resolution/mode, Display mode , Color Temperature, ACR Status |
| Advanced settings | Overdrive, DDC/CI, Factory Recall |
| Power consumption (typical, w/o soun | |
| Soft switch off | 0.1 W |
| Power save mode | 0.2 W |
| Operating with EPA settings | 14.95 W |

| Electrical values | |
|---|--|
| Rated voltage range | 100 V - 240 V |
| Rated frequency range | 50 Hz - 60 Hz |
| Protection class | 1 |
| Compliance | |
| Europe | Energy Efficiency Class: A+, CE certification according to EC Directive 2004/108/EEC, EN 60950, RoHS, WEEE, IT-Eco- Declaration |
| Model | B24-8T |
| Germany | TÜV GS |
| Russia | EAC |
| USA/Canada | FCC Class B, cTUVus |
| Australia/New Zealand | (on customer request) |
| South Korea | KC#E-Standby |
| Singapore | S-Mark |
| Taiwan | BSMI |
| China | (((|
| Saudi Arabia | SASO |
| Global | ENERGY STAR® 7.0, TCO Certified Displays 7.0, EPEAT® Gold (dedicated regions), Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TÜV Low Blue Light Certified, TÜV Flicker Free Certified |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates |
| Quality and Reliability | |
| Dimensions / Weight / Environmental | |
| Dimension without stand $(W \times D \times H)$ | 553 x 63.5 x 330.2 mm |
| | 21.77 x 2.5 x 13.00 inch |
| Dimension with stand $(W \times D \times H)$ | 553 x 209 x 372 mm |
| · _ / | 21.77 inch x 8.24 x 14.65 inch |
| Weight (packed) | 4.84 kg |
| | 10.67 lbs |
| Weight (unpacked) | 3.6 kg |
| | 7.94 lbs |
| Weight (Monitor only) | 3.3 kg |
| | 7.28 lbs |
| Operating ambient temperature | 5 - 35 °C (41 - 95 °F) |
| Operating relative humidity | 10 - 85 % (non condensing) |
| Miscellaneous | |
| Miscellaneous | VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared |
| Color | Black |
| Package content | |
| Display delivered accessories | DVI-D Data cable 1.8 m Audio cable 1.8 m Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Safety notes |
| Display delivered accessories notes | Data cables and audio cable detachable on display Please note: cable length may vary by +/- 5 cm. |
| Order information | |
| Order Code | S26361-K1598-V160 |
| EAN Code | 4057185668828 |

| Order information | |
|-----------------------------|---|
| Country specific order code | BDL:K1573V160-UK - with UK power cable, mandatory for Arabian countries BDL:K1573V160-CHN - with China power cable and CEL, mandatory for China BDL:K1573V160-INT - W/o power cable, mandatory for countries where import with EU cable is not allowed |
| Accessories information | Further helpful options: Available Privacy Filters: http://globalsp.ts.fujitsu.com/ dmsp/Publications/public/ds-Privacy-Filter.pdf Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/ Publications/public/pos-connectivity.pdf |
| Warranty | |
| Warranty period | 3 years (depending on country) |
| Warranty type | Collect & Return Service (depending on country specific requirements) |
| Warranty Terms & Conditions | http://support.ts.fujitsu.com/warranty |
| Spare Parts availability | 5 years after end of product life |
| Service Weblink | http://www.fujitsu.com/fts/services/support |
| | |

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Display E24-8 TS Pro, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Display E24-8 TS Pro, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

http://www.fujitsu.com/fts/displays

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www. fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/ terms

© 2017 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com/fts 2017-05-01 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms

© 2017 Fujitsu Technology Solutions GmbH