FUJITSU

Data Sheet FUJITSU Tablet STYLISTIC R727

Unlimited Usability and Productivity with 2 in 1

The FUJITSU Tablet STYLISTIC R727 with a 31.8 cm (12.5-inch) anti-glare display transforms into a full performance and full productivity notebook by simply attaching the strong yet slim magnetic keyboard. Its magnesium-aluminum housing delivers durability for business pros on the move, presenting in tablet mode or working in notebook mode anywhere you like. With the sensitive display you can naturally use a digital pen for notes or signatures on the tablet. Enterprise-grade connectivity like 4G/LTE, manageability and security features like encrypted drives and NFC-based authentication allow you to do your job wherever you want; all in confidence that your data is secure.

Powerful and responsive 2 in 1

- Business tablet, business notebook, one device
- Transform a tablet into a full-fledged notebook by simply attaching the magnetic keyboard and unfolding the integrated tablet stand

Mobility first

- Smart features for dynamic work styles
- Anti-glare display, durable yet thin & light magnesium-aluminum housing, flexible input options, UC&C capabilities, long runtime of up to 10 hours

Go-anywhere connectivity

- Smart features let you do your job wherever you want
- Optional embedded 4G/LTE and NFC

Enterprise-grade manageability and security

Future-proof security features and remote management capabilities keep data safe

Embedded NFC for contactless SmartCard authentication, encrypted drives, TPM and remote BIOS manageability

Best-in-class office comfort

Switch to a full desktop-like experience in no time Cradle to attach peripherals in the office













Components

Operating systems				
Operating system pre-installed	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home	Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home
Operating system notes	MS OS support information: Systems with 7th generation Intel processor receive support from Microsoft with Windows 10 Home / Windows 10 Pro only. For more information, please see MS Support Lifecycle. *Processor only for retail, SM	MS OS support information: Systems with 7th generation Intel processor receive support from Microsoft with Windows 10 Home / Windows 10 Pro only. For more information, please see MS Support Lifecycle. B, education and government	Intel processor receive support from Microsoft with Windows 10 Home / Windows 10 Pro only. For more information, please see MS Support Lifecycle.	MS OS support information: Systems with 7th generation Intel processor receive support from Microsoft with Windows 10 Home / Windows 10 Pro only. For more information, please see MS Support Lifecycle.
Hard disk drives (internal)	SSD SATA III, 512 GB, M.2 mo SSD SATA III, 256 GB, M.2 mo SSD SATA III, 128 GB, M.2 mo	dule, OPAL capable		
Hard disk notes	One Gigabyte equals one bill	ion bytes, when referring to h , also depending on used soft reserved for system recovery		
Interface add on cards/components (optional)				
Multimedia				
Camera	Front camera 2 megapixel, re	ear camera 5 megapixel with a	autofocus	

Base unit

General system information				
Processor	Intel® Core™ i3-7100U processor	Intel® Core™ i5-7200U processor	Intel® Core™ i5-7300U processor	Intel® Core™ i7-7600U processor
	(2 Cores / 4 Threads, up to 2.3 GHz)	(2 Cores / 4 Threads, up to 2.8 GHz)	(2 Cores / 4 Threads, up to 3.0 GHz)	(2 Cores / 4 Threads, up to 3.4 GHz)
Chipset	Integrated in CPU	Integrated in CPU	Integrated in CPU	Integrated in CPU
Supported capacity RAM	4 GB	8 GB	8 GB	16 GB
Memory slots	LPDDR3 (1600 MHz)	LPDDR3 (1600 MHz)	LPDDR3 (1600 MHz)	LPDDR3 (1600 MHz)
LAN	Built-in 10/100/1,000 MBit/s Intel® I219V	Built-in 10/100/1,000 MBit/s Intel® I219V	Built-in 10/100/1,000 MBit/s Intel® I219LM	Built-in 10/100/1,000 MBit/s Intel® I219LM
LAN notes	LAN connector via optional cradle or optional USB adapter cable	LAN connector via optional cradle or optional USB adapter cable	LAN connector via optional cradle or optional USB adapter cable	LAN connector via optional cradle or optional USB adapter cable
Integrated WLAN	Intel Dual Band Wireless- AC8265	Intel Dual Band Wireless- AC8265	Intel Dual Band Wireless- AC8265	Intel Dual Band Wireless- AC8265
BIOS features	InsydeH20 Bios	InsydeH20 Bios	InsydeH20 Bios	InsydeH20 Bios
Audio type	On board	On board	On board	On board
Audio codec	Realtek ALC255	Realtek ALC255	Realtek ALC255	Realtek ALC255

General system information Audio features	2x digital array	2x digital array	2x digital array	2x digital array
	microphones, 2x built-in	microphones, 2x built-in	microphones, 2x built-in	microphones, 2x built-in
	speakers (stereo)	speakers (stereo)	speakers (stereo)	speakers (stereo)
Display				
Display	31.8 cm (12.5-inch),PLS	31.8 cm (12.5-inch),PLS	31.8 cm (12.5-inch),PLS	31.8 cm (12.5-inch),PLS
	(Plane to Line Switching),(Full HD),Anti-	(Plane to Line	(Plane to Line	(Plane to Line
	glare display, 1,920 x 1,080	Switching),(Full HD),Anti- glare display,1,920 x 1,080	Switching),(Full HD),Anti- glare display,1,920 x 1,080	Switching), (Full HD), Anti- glare display, 1,920 x 1,080
	pixel,700:1,400 cd	pixel,700:1,400 cd	pixel,700:1,400 cd	pixel,700:1,400 cd
Display notes	ISO 9241-307 - Pixel class II	ISO 9241-307 - Pixel class II	ISO 9241-307 - Pixel class II	ISO 9241-307 - Pixel class II
	Viewing angle: Left/Right	Viewing angle: Left/Right	Viewing angle: Left/Right	Viewing angle: Left/Right
	89°, Top 89°, Bottom 89°; 30ms response time;	89°, Top 89°, Bottom 89°; 30ms response time;	89°, Top 89°, Bottom 89°; 30ms response time;	89°, Top 89°, Bottom 89°; 30ms response time;
	Integrated ambient light	Integrated ambient light	Integrated ambient light	Integrated ambient light
	sensor for automatic	sensor for automatic	sensor for automatic	sensor for automatic
	backlight adjustment to the	backlight adjustment to the	backlight adjustment to the	backlight adjustment to the
	working environment.	working environment.	working environment.	working environment.
Sensors	3-axis Accelerometer	3-axis Accelerometer	3-axis Accelerometer	3-axis Accelerometer
	Gyroscope Ambient Light Sensor	Gyroscope Ambient Light Sensor	Gyroscope Ambient Light Sensor	Gyroscope Ambient Light Sensor
	Magnetic Field Sensor	Magnetic Field Sensor	Magnetic Field Sensor	Magnetic Field Sensor
	Compass	Compass	Compass	Compass
Aspect ratio	16:9	16:9	16:9	16:9
Brightness - typical	400 cd	400 cd	400 cd	400 cd
Contrast - typical	700:1	700:1	700:1	700:1
Digitizer / Touch Technology	TPK Touch Panel for active	TPK Touch Panel for active	TPK Touch Panel for active	TPK Touch Panel for active
	pen input plus capacitive 10-finger multi-touch screen	pen input plus capacitive	pen input plus capacitive 10-finger multi-touch screen	pen input plus capacitive 10-finger multi-touch scree
Ambient light sensor	Integrated	Integrated	Integrated	Integrated
Ambient light sensor notes		While enabled, the ambient	,	2
5	light sensor automatically	light sensor automatically	light sensor automatically	light sensor automatically
	· · · · · · · · · · · · · · · · · · ·	adjusts the display backlight	· · · · · ·	
Viewing angle (h/v) - typical	178°/178°	178°/178°	178°/178°	178°/178°
Graphics				
TFT resolution (HDMI)	up to 4,096 × 2,160		up to 4,096 × 2,160	
TFT resolution (VGA)	1,920 x 1,080 pixel		1,920 x 1,200 pixel	
Max. resolution external display	4,096 x 2,304 pixel		4,096 x 2,304 pixel	
Max. resolution display port	4,096 x 2,304 pixel		4,096 x 2,304 pixel	
Graphics brand name	Intel [®] HD Graphics 620		Intel [®] HD Graphics 620	
Graphics features	3 Display Support (2 external		3 Display Support (2 externa	
Graphics notes	Shared memory depending c operating system	on main memory size and	Shared memory depending of operating system	on main memory size and
Interfaces				
DC-in	1			
Audio: line-out / headphone	1 (combo port with Audio lin	•		
Audio: line-in / microphone	1 (combo port with Audio lin	e-out)		
Internal microphones	2 (digital)			
USB 3.1 Gen1 (USB 3.0) total	1 (Anytime USB-charge)			
VGA	1 (via optional cradle or optional cradle o	onal conversion cable)		
mini DisplayPort	1			
HDMI	1 (via optional cradle or optional cradle o			
Ethernet (RJ-45)	1 (via optional cradle or optional cradle or option	onal conversion cable)		
Memory card slots	1 microSD up to 2GB			
	microSDHC up to 32GB			
	microSDXC up to 128GB			

Interfaces	
SIM card slot	1 (MicroSIM - only for models with integrated 4G/LTE)
nterface Module notes	VGA and HDMI via conversion cables (mini DP to VGA and mini DP to HDMI), Ethernet via conversion cable (USB to RJ-45)
Wireless technologies	
Intennas	2x dual band for WLAN, 2x for 4G/LTE, Bluetooth shared with WLAN, 1 x NFC
Bluetooth	Bluetooth 4.2 LE
ntegrated WLAN	Intel Dual Band Wireless-AC8265
VLAN encryption	WEP, WPA, WPA2
VLAN notes	Import and usage according to country-specific regulations.
ntegrated LTE or UMTS	LTE Sierra Wireless EM7305 (Cat. 3) (optional)
TE/UMTS/GPS notes	Including GPS functionality Import and usage according to country-specific regulations.
NFC	optional
i PS	Embedded in 3G/4G module if configured with WWAN
Power supply	
AC adapter	19 V / 65 W (3.42 A)
Rated voltage range	100 V - 240 V (AC Input)
Rated frequency range	50 Hz - 60 Hz
st battery	Lithium polymer battery 4-cell, 34 Wh
Runtime 1st battery	up to 10h slate only and 9h incl. keyboard (Productivity Workload MobileMark [®] 2014)
, Battery charging time	~ 3h
Battery notes	Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity) Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime.
Dimensions / Weight / Environmental	
Dimensions (W x D x H)	319 x 9.5 x 201 mm
	12.55 x 0.37 x 7.91 inch
Veight	from 830 g slate only / 1170g incl. keyboard
Veight (lbs)	slate only from1,83 lbs / incl. keyboard 2,58 lbs
Veight notes	Weight may vary depending on actual configuration (including battery pack)
Dperating ambient temperature	Running: 5 - 35 °C; Packed -15 - 60 °C
perating relative humidity	Running: 20 - 85%; Packed 8 - 85% (relative humidity, non-condensing)
Product	STYLISTIC R727
Germany	GS (planned)
urope	CE! EN 60950
Jobal	ENERGY STAR® 6.1 EPEAT® Gold (dedicated regions) (planned) RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) IT-Eco-Declaration Microsoft Operating Systems (HCT / HCL entry / WHQL)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates

Additional Software				
Additional software (preinstalled)	Fujitsu Plugfree Network (ne Fujitsu Anytime USB Charge Fujitsu Battery Utility Fujitsu Function Manager Fujitsu DeskUpdate (driver a Microsoft Office (buy license	ager (if configured with 4G/LTf twork management utility) Utility	Nicrosoft Office)	
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUD CyberLink PowerDVD BD (pla CyberLink PowerDVD DVD (p CyberLink YouCam (webcam Nero (backup and burning s	VD) optional ayback software for Blu-ray Dis layback software for DVD) software)	SC™)	
Manageability				
Manageability technology	PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN)			
Supported standards	WMI PXE BootP (made4you)			
Manageability link	http://www.fujitsu.com/fts/m	nanageability		
Security				
System and BIOS Security	Optional: Trusted Platform Module (TPM 2.0) EraseDisk (optional)	Optional: Trusted Platform Module (TPM 2.0) EraseDisk (optional)	Optional: Trusted Platform Module (TPM 2.0) EraseDisk (optional)	Optional: Trusted Platform Module (TPM 2.0) EraseDisk (optional)
User Security	Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)	Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)	Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)	Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)

Warranty	
Warranty period	2 years (for countries within EMEIA)
Warranty type	Collect & Return Service / Bring-in Service (depending on country)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Product Support Services - the perfe	ect extension
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://ts.fujitsu.com/Supportservice

Recommended Accessories

Cradle STYLISTIC R series



The cradle for STYLISTIC R series allows you switch from mobile to desktop productivity mode in one click. Enjoy a complete desktop experience with a FUJITSU display, wireless mouse and keyboard or magnetic keyboard and work comfortably on spreadsheets or presentations. Available ports: HDMI, DisplayPort, VGA, 2x USB 3.0, LAN, Audio (1x in / 1x out), DC-In, Kensington lock support.

Order Code: S26391-F2167-L100

	Order Code: S26391-F6097-L36
Sneaker Sleeve 14	The Sneaker Sleeve 14 protects notebooks with up to 14-inch screens. The Order Code: front half of the bag has dedicated compartments for your notebook, power S26391-F1194-L40 cord, office supplies and personal items. The back half of the bag has an expanding, divided compartment for your files.
Active Pen for STYLISTIC R726	Annotate and fill in forms on your tablet with the premium, real size Order Code: FUJITSU Active Pen. Navigate, erase and right-click with the function button. S26391-F2169-L10 Includes a battery and a pen holder to attach to the keyboard or tablet.
/GA Conversion Adapter (Mini Display Port to VGA)	Connect and present on demand from your STYLISTIC Tablet with the Order Code: FUJITSU VGA Conversion Cable. From the mini Display Port on your Tablet to S26391-F2169-L20 the VGA port on the projector or display. (Picture similar to product)
HDMI Conversion Adapter (mini DP to HDMI)	The FUJITSU HDMI Conversion Cable lets you connect your STYLISTIC tablet to Order Code: projectors and screens that have a modern HDMI interface. (Picture similar S26391-F2169-L30 to product)
LAN Conversion Cable (USB to LAN)	The FUJITSU LAN Conversion Cable allows you to connect your STYLISTIC Order Code: tablet to a wired network connection. (Picture similar to product) S26391-F2169-L40

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Tablet STYLISTIC R727, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Tablet STYLISTIC R727, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/fts/tabletpc

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www. fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/ terms

© 2017 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

CONTACT

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com/fts 2017-05-18 CE-EN All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms © 2017 Fujitsu Technology Solutions GmbH