

# DATASHEET

## FUJITSU ESPRIMO P5730

### DESKTOP PC

YOUR EXPANDABLE WORKHORSE

#### ESPRIMO P5730

The ESPRIMO P5730 combines high scaling with state-of-the-art Intel® technology and meets the daily challenges of your business applications. Almost inaudible thanks to its innovative fan concept. The optimized design makes installing and removing components child's play. Downtimes are reduced to a minimum. The use of environmentally conscious material means that the ESPRIMO P5730 today already meets the environmental standards of tomorrow. It is a good investment for you and the environment.

#### MICROTOWER

Maximum performance and optimal extendability

- Top-quality, high-value microtower, 6 drive bays, 4 PCI/PCI express interfaces

#### ENVIRONMENTALLY COMPATIBLE PRODUCT

Your contribution to environmental protection for the continued existence of our planet

- Halogen-free mainboard, sophisticated product concept for the entire lifecycle

#### SILENT OPERATION

Pleasant working environment due to an extremely quiet system

- Innovative hardware design, optimized cooling concept

#### SERVICEABILITY



Simple extendability and optimal user-friendliness without any additional tools

- Easy access to all replaceable and expandable components

#### RELIABILITY

Reliable top-quality products designed and engineered in Germany

- High product standards thanks to top-quality components and comprehensive testing in certified in-house laboratories



# COMPONENTS

## PROCESSOR

Intel® Core™2 Quad processor Q9650 (4C/4T, 3.0 GHz, 12 MB, 1333 MHz)  
Intel® Core™2 Quad processor Q9550 (4C/4T, 2.83 GHz, 12 MB, 1333 MHz)  
Intel® Core™2 Quad processor Q9505 (4C/4T, 2.83 GHz, 6 MB, 1333 MHz)  
Intel® Core™2 Quad processor Q9400 (4C/4T, 2.66 GHz, 6 MB, 1333 MHz)  
Intel® Core™2 Quad processor Q8300 (4C/4T, 2.5 GHz, 4 MB, 1333 MHz)  
Intel® Core™2 Duo processor E8600 (2C/2T, 3.33 GHz, 6 MB, 1333 MHz)  
Intel® Core™2 Duo processor E8500 (2C/2T, 3.16 GHz, 6 MB, 1333 MHz)  
Intel® Core™2 Duo processor E8400 (2C/2T, 3.0 GHz, 6 MB, 1333 MHz)  
Intel® Core™2 Duo processor E7600 (2C/2T, 3.06 GHz, 3 MB, 1066 MHz)  
Intel® Core™2 Duo processor E7500 (2C/2T, 2.93 GHz, 3 MB, 1066 MHz)  
Intel® Pentium® processor E6300 (2C/2T, 2.8 GHz, 2 MB, 1066 MHz)  
Intel® Pentium® processor E5400 (2C/2T, 2.7 GHz, 2 MB, 800 MHz)  
Intel® Pentium® processor E5200 (2C/2T, 2.5 GHz, 2 MB, 800 MHz)  
Intel® Celeron® processor E3200 (2C/2T, 2.4 GHz, 1 MB, 800 MHz)  
Intel® Celeron® processor 450 (1C/1T, 2.2 GHz, 512 KB, 800 MHz)

## MEMORY MODULES

1 GB (1 module(s) 1 GB) DDR2, 800 MHz, PC2-6400, DIMM  
2 GB (1 module(s) 2 GB) DDR2, 800 MHz, PC2-6400, DIMM  
4 GB (1 module(s) 4 GB) DDR2, 800 MHz, PC2-6400, DIMM

## HARD DISK DRIVES (INTERNAL)

SSD SATA, 128 GB, 2.5-inch  
SATA II, 7200 rpm, 1000 GB, 3.5-inch, S.M.A.R.T.  
SATA II, 7200 rpm, 500 GB, 3.5-inch, S.M.A.R.T.  
SATA II, 7200 rpm, 320 GB, 3.5-inch, S.M.A.R.T.  
SATA II, 7200 rpm, 250 GB, 3.5-inch, S.M.A.R.T.  
SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T.  
SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T.

## Hard disk notes

Supporting NCQ and 3 GBit

## GRAPHICS ADD ON CARDS (OPTIONAL)

ATI Radeon® HD 3450, 256 MB  
Dual DVI Adapter  
DVI Adapter  
NVIDIA® GeForce® 9300GE, 256 MB  
NVIDIA® GeForce® 9300GE, 512 MB  
NVIDIA® GeForce® 9300GE display port low profile, 512 MB  
NVIDIA® GeForce® 9500GS, 512 MB  
NVIDIA® Quadro NVS 290, 256 MB

## MODULAR BAY OPTIONS

1.44 MB Floppy  
Blu-ray Disc Triple Writer, SATA I  
DVD-ROM, SATA I  
DVD Super Multi, SATA I  
MultiCard Reader 20in1, 3,5-Inch, USB 2.0

## INTERFACE ADD ON CARDS/COMPONENTS (OPTIONAL)

WLAN III, 802.11g/Draft-n (Windows only)  
WLAN II, 802.11g, 54Mbps (Windows only)  
Parallel Interface  
Modem adapter kit (EU)  
Modem 56k incl. RJ11 modem cable  
Gigabit Ethernet PCIe x1  
FireWire PCI-Card IEEE1394  
eSATA Interface  
Dual serial card, PCI, EX-43092

<b>Base unit</b>	ESPRIMO P5730
<b>MAINBOARD</b>	
<b>Mainboard type</b>	D2811
<b>Formfactor</b>	µBTX
<b>Chipset</b>	Intel® Q43
<b>Processor socket</b>	LGA 775
<b>Processor quantity maximum</b>	1
<b>System bus (FSB / HT / QPI)</b>	up to 1333 MHz
<b>Memory slots</b>	4 DIMM (DDR2)
<b>Supported capacity RAM (max.)</b>	16 GB
<b>Memory frequency</b>	800 MHz
<b>Memory notes</b>	Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules).
<b>LAN</b>	10/100/1000 MBit/s Intel® 82567 LF
<b>BIOS version</b>	Phoenix 6.0
<b>BIOS features</b>	BIOS Flash EPROM update by software Recovery BIOS
<b>Audio codec</b>	Realtek ALC663
<b>Audio features</b>	Internal speaker supports audio playback, High Definition audio, 5.1 surround sound
<b>I/O CONTROLLER ON BOARD</b>	
<b>Serial ATA total</b>	4
<b>thereof eSATA</b>	2 (optional)
<b>Controller functions</b>	Serial ATA II NCQ and 3 GBit AHCI
<b>INTERFACES</b>	
<b>Audio: line-in</b>	1
<b>Audio: line-in / microphone</b>	1
<b>Audio: line-out</b>	1
<b>USB 2.0 total</b>	12
<b>USB front</b>	2
<b>USB rear</b>	6
<b>USB internal</b>	4, thereof 2 optional rear
<b>VGA</b>	1
<b>DVI</b>	optional
<b>Serial (RS-232)</b>	1 (9pi, 16 byte FIFO, 16550 compatible)
<b>Mouse / Keyboard (PS/2)</b>	2
<b>Ethernet (RJ-45)</b>	1
<b>Parallel</b>	optional (25pin with EPP and ECP)
<b>INPUT DEVICE / COMPONENTS</b>	
	Optical USB tilt wheel mouse Optional: Optical USB/PS2 tilt wheel mouse
<b>DRIVE BAYS</b>	
<b>Drive bays total</b>	6
<b>3.5-inch internal bays</b>	2
<b>3.5-inch external bays</b>	2
<b>5.25-inch external bays</b>	2
<b>SLOTS</b>	
<b>PCI-Express 2.0 x16</b>	1 x (230 mm) FlexySlot
<b>PCI-Express x4 (mech. x8)</b>	1 x (230 mm) full height
<b>PCI (32-bit / 33 MHz)</b>	2 x (170 / 315 mm) full height
<b>GRAPHICS ON BOARD</b>	
<b>Graphics brand name</b>	Intel® GMA 4500

## GRAPHICS ON BOARD

Shared video memory	up to 256 MB
Refresh rate 1024 x 768 (recommended / max.)	85 Hz / -
Refresh rate 1280 x 1024 (recommended / max.)	85 Hz / -
Refresh rate 1600 x 1200 (recommended / max.)	85 Hz / -
TFT resolution (VGA)	1360 x 768 pixel 1440 x 900 pixel 1680 x 1050 pixel 1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel 1440 x 900 pixel 1680 x 1050 pixel 1920 x 1200 pixel
Graphics features	DirectX 10
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

## ELECTRICAL VALUES

Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 71% / 77% / 76%
Rated voltage range	100 - 127 V / 200 - 240 V
Rated frequency range	50 - 60 Hz
Operating voltage range	90 - 137 V / 180 - 264 V
Operating line frequency range	47 - 63 Hz
Max. output of power supply	260 W
Power factor correction/active power	passive
Monitor outlet	Switched

## POWER CONSUMPTION

Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=838373c8-dd75-4b46-81d9-e6d35e7f1abb">http://docs.ts.fujitsu.com/dl.aspx?id=838373c8-dd75-4b46-81d9-e6d35e7f1abb</a>

## HEAT DISSIPATION

Heat dissipation notes	See white paper Energy Consumption
------------------------	------------------------------------

## NOISE FOR STANDARD CONFIGURATION (HDD, ODD, FDD)

Noise emission	According to ISO9296
Related Processors for noise	Intel® Core™2 Duo E8600
Noise Operation mode 1: ODD load (Blue angel requirement)	4.9 B / 34 dB(A)
Noise Operation mode 2: HDD load (Blue angel requirement)	3.7 B / 21 dB(A)
Noise Operation mode 3: CPU 90% load (Blue angel requirement)	3.8 B / 23 dB(A)
Noise Operation mode 4: High load	3.8 B / 23 dB(A)
Noise Operation mode 5: Office applications	3.9 B / 23 dB(A)
Idle mode (Blue Angel requirement)	3.7 B / 21 dB(A)
Noise notes / description	A weighted sound power level L <sub>wad</sub> (in B) / workplace related A-weighted sound pressure level L <sub>pAm</sub> (in dB(A)), Bystander position

## DIMENSIONS / WEIGHT / ENVIRONMENTAL

Dimensions (W x D x H)	203 x 390 x 392 mm
Operating position	Vertical
Weight	approx. 12 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	15 - 35°C

## COMPLIANCE

<b>Product</b>	ESPRIMO P5730
<b>Model</b>	MI3W-D2811
<b>Germany</b>	GS optional
<b>Europe</b>	CE Nordic Swan
<b>USA/Canada</b>	FCC Class B cCSAus
<b>Global</b>	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL)
<b>Compliance link</b>	<a href="https://sp.ts.fujitsu.com/sites/certificates/default.aspx">https://sp.ts.fujitsu.com/sites/certificates/default.aspx</a>

## OPERATING SYSTEM

<b>Operating system optional preinstalled</b>	Microsoft® Windows® 7 Home Premium Microsoft® Windows® 7 Professional Microsoft® Windows Vista® Home Basic Microsoft® Windows Vista® Home Premium Microsoft® Windows Vista® Business 32-bit Microsoft® Windows Vista® Business 64-bit TwinLoad Microsoft® Windows® XP Professional (DVD)
<b>Operating system compatible</b>	Linux
<b>Operating system notes</b>	Windows Vista® Premium Logo: min. 1 GB RAM necessary. All Windows Vista® and Windows® 7 versions are Office 2007 ready.

## ADDITIONAL SOFTWARE

<b>Additional software (preinstalled)</b>	Nero Essentials S (burning software)
<b>Additional software (optional)</b>	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink Power2Go BD (playback software for Blu-ray Disc™, only with Blu-ray Disc™ drive)

## COMPATIBILITY (REFERENCES)

DMI 2.0  
PC 2001  
WMI 1.5  
USB 2.0

## MANAGEABILITY

<b>Manageability features</b>	ASF 2.0 (Alert Standard Format) DeskUpdate Driver management DeskView Migrate (optional) DeskView Control (optional) PXE 2.1 Boot code BootP Boot Code including Bootmanage Administrator Software (tested) Wake up from S5 (off mode) Intrusion switch (optional) Intel® Standard Manageability
<b>Manageability type</b>	DeskView 10.x client management including:
<b>DeskView features</b>	On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Advanced alerts (ASF implementation) Security Remote Control DeskView Helpdesk Integration WoL (Wake on LAN)
<b>Manageability link</b>	<a href="http://ts.fujitsu.com/manageability">http://ts.fujitsu.com/manageability</a> <a href="http://www.altiris.com/fujitsu">http://www.altiris.com/fujitsu</a>

## SECURITY

<b>Physical security</b>	Kensington Lock support Eye for padlock Optional: Integrated cabinet lock
--------------------------	---------------------------------------------------------------------------------

---

## SECURITY

<b>System security</b>	Boot sector virus protection Write protect option for the Flash EPROM Embedded security (TPM 1.2) Control of all USB interfaces External USB ports can be disabled separately Boot protection for floppy disk / CD drive and write protection for floppy disk drive Control of external interfaces
<b>User security</b>	User and supervisor BIOS password SystemLock 2 BIOS SmartCard Security Hard disk password Optional: Access protection via external SmartCard reader Optional: Access protection via internal SmartCard reader

---

## SERVICEABILITY

FlexySlot  
EasyFix  
EasyChange for HDD  
EasyChange for optical drives

---

## PACKAGING INFORMATION

<b>Packaging dimension</b>	500x290x540 mm
<b>Max. quantity / pallet</b>	24
<b>Material - Weight (g) Carton</b>	1270 g
<b>Material - Weight (g) EPS / PS</b>	210 g
<b>Material - Weight (g) PE</b>	appr. 60 g
<b>Packaging notes</b>	printed user documentation is bleached in chlorine free process

---

## WARRANTY

### MAINTENANCE AND SUPPORT SERVICES - THE PERFECT EXTENSION

<b>Recommended Service</b>	5x9, Response Time: Next Business Day
<b>Spare Parts availability</b>	5 years
<b>Service Weblink</b>	<a href="http://ts.fujitsu.com/Supportservice">http://ts.fujitsu.com/Supportservice</a>



#### FUJITSU PLATFORM SOLUTIONS

In addition to Fujitsu ESPRIMO P5730, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

#### Computing Products

[www.fujitsu.com/global/services/computing/](http://www.fujitsu.com/global/services/computing/)

#### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

#### MORE INFORMATION

Learn more about Fujitsu ESPRIMO P5730, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. <http://ts.fujitsu.com/ESPRIMO>

#### FUJITSU GREEN POLICY INNOVATION

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



#### COPYRIGHTS

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see [http://ts.fujitsu.com/terms\\_of\\_use.html](http://ts.fujitsu.com/terms_of_use.html)

Copyright © Fujitsu Technology Solutions

#### DISCLAIMER

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

---

#### CONTACT

FUJITSU Technology Solutions  
Website: <http://ts.fujitsu.com>  
2010-02-01 CE-EN

---