

Fujitsu recommends Windows 10 Pro for business.

Datasheet

FUJITSU Desktop ESPRIMO D7011

New small form factor PC in a more compact and space-saving design

The FUJITSU ESPRIMO D7011 desktop is a high performance, secure small form factor PC with ultimate expandability, along with best-in-class connectivity. Faster operations and a new housing help in space saving to create the perfect working desk. The USB Type-C™, flexible graphics options, offers great connectivity. The 80Plus GOLD and 80Plus PLATINUM power supply helps to reduce environmental impact and energy bills.

Intel® chipset technology and higher memory speed

High performance ensures faster operations and lower system response time

- Intel® B560 chipset with higher memory frequency of up to 3,200 MT/s

New housing and ultimate expandability

Space saving design for your future computing needs

- 2x low profile (LP) or 1x LP/ 1x full height (Riser) via BTO
- Space saving in width and depth with new 8.3 litres volume

Best-in-class connectivity

Be flexible and stay productive in a hyper-connected world

- Support of new USB Type-C™ in front
- Flexible graphics options (VGA, DVI-D, HDMI®, USB Type-C™, DisplayPort™)
- USB Type-C™ support of 60 W (optional to power a display)
- Legacy Serial port connectors as option

High security with integrated options

Designed to protect data and hardware components against manipulation and theft

- Smartcard reader, Erasedisk software
- Hole for pad lock and Kensington as standard for security

Low power consumption, easy serviceability and usability

Reduced environmental impact and reduced energy bills and features designed for easy access, control and use of the system

- 80Plus GOLD and 80Plus PLATINUM power supply efficiency with monitor outlet
- Tool-less access to components, easy change and screw-less add on cards



Fujitsu recommends Windows 10 Pro for business.

Specification

	ESPRIMO D7011	ESPRIMO D7011 ESTARx
Processor	Intel® Core™ i7-10700 processor (8 Cores / 16 Threads, 2.90 GHz, 16 MB, Intel® UHD Graphics 630) ** Intel® Core™ i5-10600 processor (6 Cores / 12 Threads, 3.30 GHz, 12 MB, Intel® UHD Graphics 630) * Intel® Core™ i5-10505 processor (6 Cores / 12 Threads, 3.20 GHz, 12 MB, Intel® UHD Graphics 630) * Intel® Core™ i5-10400 processor (6 Cores / 12 Threads, 2.90 GHz, 12 MB, Intel® UHD Graphics 630) * Intel® Core™ i3-10105 processor (4 Cores / 8 Threads, 3.70 GHz, 6 MB, Intel® UHD Graphics 630) * *with Intel® Turbo Boost Technology 2.0 (clock speed and performance will vary depending on workload and other variables) **with Intel® Turbo Boost Max Technology 3.0 (clock speed and performance will vary depending on workload and other variables)	
Operating systems		
Operating system pre-installed (optional)	Windows 10 Pro. Fujitsu recommends Windows 10 Pro for business. Windows 10 Home	Windows 10 Pro. Fujitsu recommends Windows 10 Pro for business. Windows 10 Home
Memory modules	32 GB (1 module(s) 32 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, UDIMM 16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, UDIMM 8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, UDIMM 4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, UDIMM	32 GB (1 module(s) 32 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, UDIMM 16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, UDIMM 8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, UDIMM 4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, UDIMM
Graphics	Entry 3D: NVIDIA® T400 LP, 2 GB, PCIe x16, 3 x miniDP# Entry 3D: NVIDIA® T600 LP, 2 GB, PCIe x16, 3 x miniDP#	Entry 3D: NVIDIA® T400 LP, 2 GB, PCIe x16, 3 x miniDP# Entry 3D: NVIDIA® T600 LP, 2 GB, PCIe x16, 3 x miniDP#
Mass storage 3.5 inch size	HDD SATA III, 7,200 rpm, 3,000 GB, 3.5 inch HDD SATA III, 7,200 rpm, 2,000 GB, 3.5 inch HDD SATA III, 7,200 rpm, 1,000 GB, 3.5 inch	Not available for ESTARx
Mass storage M.2 technology	SSD PCIe, 1,024 GB M.2 NVMe module (Gen 4), SED SSD PCIe, 512 GB M.2 NVMe module (Gen 4), SED SSD PCIe, 512 GB M.2 NVMe module (Value) SSD PCIe, 256 GB M.2 NVMe module (Gen 4), SED SSD PCIe, 256 GB M.2 NVMe module (Value) SSD PCIe, 128 GB M.2 NVMe module (Value)	SSD PCIe, 1,024 GB M.2 NVMe module (Gen 4), SED SSD PCIe, 512 GB M.2 NVMe module (Gen 4), SED SSD PCIe, 512 GB M.2 NVMe module (Value) SSD PCIe, 256 GB M.2 NVMe module (Gen 4), SED SSD PCIe, 256 GB M.2 NVMe module (Value) SSD PCIe, 128 GB M.2 NVMe module (Value)
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. SSD (Solid State Disk) SED (Self-Encrypting Drive)	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. SSD (Solid State Disk) SED (Self-Encrypting Drive)
Optical drive	DVD Super Multi ultra slim (tray), SATA SD Card reader, USB 3.0	DVD Super Multi ultra slim (tray), SATA SD Card reader, USB 3.0
Interfaces add on cards / Components	WLAN 802.11ax (2x2) PCIe x1 LP and Bluetooth 5.2, SRD 5.8 GHz (dedicated regions only) Gigabit Ethernet PCIe x1 Dual serial card PCIe x1 LP	Not available for ESTARx
Component notes	The listed product components and optional functions are not available in all region/countries	The listed product components and optional functions are not available in all region/countries; Energy Star certification requires Windows operating system installed "ESPRIMO D7011 ESTARx" will be shown in device label as model name

Fujitsu recommends Windows 10 Pro for business.

Base unit

	ESPRIMO D7011	ESPRIMO D7011 ESTARx
Mainboard		
Mainboard type	D3923-A2	D3923-A2
Formfactor	Proprietary	Proprietary
Chipset	Intel® B560	Intel® B560
Processor socket	LGA 1200	LGA 1200
Processor quantity maximum	1	1
Supported capacity RAM (max.)	128 GB	128 GB
Memory slots	4 DIMM (DDR4)	4 DIMM (DDR4)
Memory frequency	3,200 MT/s	3,200 MT/s
Memory notes	Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 3,200 MHz may be clocked down to 2,400 MHz depending on processor, memory configuration, and memory type.	Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 3,200 MHz may be clocked down to 2,400 MHz depending on processor, memory configuration, and memory type.
LAN	10/100/1,000 MBit/s Realtek RTL8111H	10/100/1,000 MBit/s Realtek RTL8111H
BIOS version	AMI Aptio V UEFI Specification 2.6	AMI Aptio V UEFI Specification 2.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio type	On board	On board
Audio codec	Realtek ALC897	Realtek ALC897
Audio features	Internal speaker supports audio playback, High-Definition audio, 5.1 surround sound	Internal speaker supports audio playback, High-Definition audio, 5.1 surround sound
I/O controller on board		
Serial ATA total	4	4
Thereof SATA III	4	4
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI	Serial ATA III (6 Gbit) NCQ AHCI
Interfaces		
Audio: line-in	1	1
Audio: line-out	1	1
Front audio: headset	1	1
USB 2.0 total	7 (1 internal)	7 (1 internal)
USB 3.2 Gen 1x1 (5 Gbps) total	4 (1 internal)	4 (1 internal)
USB 3.2 Gen 2x1 (10 Gbps) total	1 and 1 (optional)	1 and 1 (optional)
USB 3.2 Gen 2x2 (20 Gbps) total	1	1
USB front	3x USB 2.0 1x USB 3.2 Gen 2x1 1x USB 3.2 Gen 2x2 Type-C (supports up to 15 W)	3x USB 2.0 1x USB 3.2 Gen 2x1 1x USB 3.2 Gen 2x2 Type-C (supports up to 15 W)
USB rear	4x USB 2.0 2x USB 3.2 Gen 1x1 optional: additional 1x USB 3.2 Gen 2x1 Type-C (supports DisplayPort 1.4 and power delivery (PD) up to 15 W or 60 W (occupies PCIe x16 slot)	4x USB 2.0 2x USB 3.2 Gen 1x1 optional: additional 1x USB 3.2 Gen 2x1 Type-C (supports DisplayPort 1.4 and power delivery (PD) up to 15 W or 60 W (occupies PCIe x16 slot)
USB internal	1x USB 2.0 or 1x USB 3.2 Gen1x1 Type A	1x USB 2.0 or 1x USB 3.2 Gen1x1 Type A
VGA	Optional	Optional
DisplayPort	2	2
DVI	DVI-D (optional)	DVI-D (optional)
Serial (RS-232)	1 (optional serial port (9 pin, 16 byte FIFO, 16550 compatible))	1 (optional serial port (9 pin, 16 byte FIFO, 16550 compatible))
Ethernet (RJ-45)	1	1
Interface module notes	Anytime USB charge functionality	Anytime USB charge functionality
Kensington Lock support	1	1

Fujitsu recommends Windows 10 Pro for business.

Input device / Components		
Input devices (optional)	Keyboard Mouse	Keyboard Mouse
Drive bays		
Drive bays total	3	3
2.5 inch internal bays	1	1
5.25 inch external bays	1	1
Drive bay notes	1x internal 3.5 inch bay (screwless) can be used via adapter for 1x or 2x 2.5 inch drives (screwless) (optional); 5.25 inch bay: for slim optical disc drive only	1x internal 3.5 inch bay (screwless) can be used via adapter for 1x or 2x 2.5 inch drives (screwless) (optional); 5.25 inch bay: for slim optical disc drive only
M.2-2280	1x on mainboard for SSD NVMe: 1x PCIe 3.0 x4; up to 32 Gbit/s	1x on mainboard for SSD NVMe: 1x PCIe 3.0 x4; up to 32 Gbit/s
Slots		
PCI-Express 3.0 x4 (mech. x16)	1 x (150 mm / 5.91 inch)	1 x (150 mm / 5.91 inch)
PCI-Express 4.0 x16	1 x (210 mm / 8.27 inch) low profile or full height (via Riser card) (optional)	1 x (210 mm / 8.27 inch) low profile or full height (via Riser card) (optional)
Graphics on board		
Graphics brand name	Intel® UHD Graphics 630	Intel® UHD Graphics 630
Shared video memory	Shared memory depending on main memory and operating system	Shared memory depending on main memory and operating system
TFT resolution (VGA)	Up to 1,920 x 1,080 pixel	Up to 1,920 x 1,080 pixel
TFT resolution (DVI)	Up to 1,920 x 1,200 pixel	Up to 1,920 x 1,200 pixel
TFT resolution (DisplayPort)	Up to 4,096 x 2,304 pixel	Up to 4,096 x 2,304 pixel
TFT resolution (HDMI)	Up to 4,096 x 2,160 pixel (30 Hz)	Up to 4,096 x 2,160 pixel (30 Hz)
Graphics features	Support for up to three independent displays DirectX® 12 HDCP support OpenCL™ 2.1 OpenGL® 4.5 For multi monitoring mode, graphics card and integrated graphics run in parallel DisplayPort interface supports Ver. 1.4 incl. Multi-Stream Digital audio formats are supported, including Dolby Digital Plus (7.1 channels) DVI-D interface supports audio output if connected to the HDMI interface of a display via suitable adapter cables (not included) System provides one connector to be used for LAN or graphics Optional graphics connectors: <ul style="list-style-type: none"> ▪ HDMI® 2.0b ▪ DVI-D ▪ VGA ▪ USB Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 15 W) ▪ USB Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 60 W. Occupies PCIe x16 slot) 	Support for up to three independent displays DirectX® 12 HDCP support OpenCL™ 2.1 OpenGL® 4.5 For multi monitoring mode, graphics card and integrated graphics run in parallel DisplayPort interface supports Ver. 1.4 incl. Multi-Stream Digital audio formats are supported, including Dolby Digital Plus (7.1 channels) DVI-D interface supports audio output if connected to the HDMI interface of a display via suitable adapter cables (not included) System provides one connector to be used for LAN or graphics Optional graphics connectors: <ul style="list-style-type: none"> ▪ HDMI® 2.0b ▪ DVI-D ▪ VGA ▪ USB Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 15 W) ▪ USB Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 60 W. Occupies PCIe x16 slot)
Graphics notes	Up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (colour depth up to 32 Bit/ pixel) For TFT we recommend using 60 Hz	Up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (colour depth up to 32 Bit/ pixel) For TFT we recommend using 60 Hz
Electrical values		
Power efficiency note	Power supply efficiency in % at 10% / 20% / 50% / 100% load 80Plus GOLD: For 230 V ; 87 / 90 / 92 / 91 For 115 V ; 86 / 89 / 91 / 88 80Plus PLATINUM: For 230 V ; 88 / 92 / 94 / 93 For 115 V ; 87 / 91 / 92 / 91	Power supply efficiency in % at 10% / 20% / 50% / 100% load 80Plus GOLD: For 230 V ; 87 / 90 / 92 / 91 For 115 V ; 86 / 89 / 91 / 88 80Plus PLATINUM: For 230 V ; 88 / 92 / 94 / 93 For 115 V ; 87 / 91 / 92 / 91

Fujitsu recommends Windows 10 Pro for business.

Rated voltage range	100 V – 240 V	100 V – 240 V
Rated frequency range	50 Hz – 60 Hz	50 Hz – 60 Hz
Operating voltage range	90 V – 264 V	90 V – 264 V
Operating line frequency range	47 Hz – 63 Hz	47 Hz – 63 Hz
Max. output of single power supply	GOLD: 280 W; PLATINUM: 300 W	GOLD: 280 W; PLATINUM: 300 W
Power factor correction/active power	Active	Active
Monitor outlet	Switched for PLATINUM power supply	Switched for PLATINUM power supply
Power consumption		
Power consumption note	See white paper Energy Consumption	See white paper Energy Consumption
Link to Energy White Paper	https://docs.ts.fujitsu.com/dl.aspx?id=972acf94-29e6-49ca90fd-c198b6e0cacf	
Noise emission		
Standard noise emission	According to ISO 7779:2010, ECMA-74	According to ISO 7779:2010, ECMA-74
Standard noise operation mode: CPU 50% load	For PLATINUM PSU: 3.1 B / 18 dB(A) Bystander; 18 dB(A) Operator position (SSD M.2)	For PLATINUM PSU: 3.1 B / 18 dB(A) Bystander; 18 dB(A) Operator position (SSD M.2)
	For GOLD PSU: 3.3 B / 20 dB(A) Bystander; 20 dB(A) Operator position (3.5 inch HDD)	For GOLD PSU: 3.3 B / 20 dB(A) Bystander;
Standard noise operation mode: HDD load	For PLATINUM PSU: 3.1 B / 18 dB(A) Bystander; 18 dB(A) Operator position (SSD M.2)	For PLATINUM PSU: 3.1 B / 18 dB(A) Bystander; 18 dB(A) Operator position (SSD M.2)
	For GOLD PSU: 3.4 B / 21 dB(A) Bystander; 22 dB(A) Operator position (3.5 inch HDD)	For GOLD PSU: 3.4 B / 21 dB(A) Bystander
Standard noise operation mode: Idle mode	For PLATINUM PSU: 3.1 B / 18 dB(A) Bystander; 18 dB(A) Operator position (SSD M.2)	For PLATINUM PSU: 3.1 B / 18 dB(A) Bystander; 18 dB(A) Operator position (SSD M.2)
	For GOLD PSU: 3.4 B / 20 dB(A) Bystander; 21 dB(A) Operator position (3.5 inch HDD)	For GOLD PSU: 3.4 B / 20 dB(A) Bystander;
Standard noise operation mode: ODD load	For PLATINUM PSU: 4.5 B / 31 dB(A) Bystander; 35 dB(A) Operator position (SSD M.2)	For PLATINUM PSU: 4.5 B / 31 dB(A) Bystander; 35 dB(A) Operator position (SSD M.2)
	For GOLD PSU: 3.4 B / 30 dB(A) Bystander; 35 dB(A) Operator position (3.5 inch HDD)	For GOLD PSU: 3.4 B / 30 dB(A) Bystander;
Standard noise operation mode: Office applications 2.0	For PLATINUM PSU: 3.1 B / 18 dB(A) Bystander; 19 dB(A) Operator position (SSD M.2)	For PLATINUM PSU: 3.1 B / 18 dB(A) Bystander; 19 dB(A) Operator position (SSD M.2)
	For GOLD PSU: 3.4 B / 19 dB(A) Bystander; 20 dB(A) Operator position (3.5 inch HDD)	For GOLD PSU: 3.4 B / 19 dB(A) Bystander;
Dimensions / Weight / Environmental		
Dimensions (W x D x H)	314 x 296 x 89 mm 12.36 x 11.65 x 3.51 inch	314 x 296 x 89 mm 12.36 x 11.65 x 3.51 inch
Operating position	Horizontal / vertical (optional, feet needed)	Horizontal / vertical (optional, feet needed)
Weight	Approx. 8 kg	Approx. 8 kg
Weight (lbs)	Approx. 17.64 lbs	Approx. 17.64 lbs
Weight notes	Actual weight may vary depending on configuration	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)	5 - 85 % (relative humidity)
Compliance		
Product	ESPRIMO D7011	ESPRIMO D7011 ESTARx
Model	DTG	
Global	RoHS (Restriction of hazardous substances) Microsoft Operating Systems (HCT / HCL entry / WHQL)	RoHS (Restriction of hazardous substances) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 8.0
Compliance link	https://sp.ts.fujitsu.com/sites/certificates	
Additional software		
Additional software (pre-installed)	Adobe® Reader® (pdf reader) McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed) Microsoft® Office 30 days trial	Adobe® Reader® (pdf reader) McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed) Microsoft® Office 30 days trial
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD DVD (playback software for DVD)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD DVD (playback software for DVD)

Fujitsu recommends Windows 10 Pro for business.

	Nero Essentials XL Microsoft® Office Professional 2019 Microsoft® Office Home and Business 2019 (A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the region in which it was acquired.)	Nero Essentials XL Microsoft® Office Professional 2019 Microsoft® Office Home and Business 2019 (A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the region in which it was acquired.)
Security		
Physical security	Kensington Lock support Eye for padlock	Kensington Lock support Eye for padlock
System and BIOS security	Embedded security (TPM 2.0) EraseDisk Credential Guard Ready and Device Guard Capable (requires 8 GB or more system RAM and SSD PCIe NVMe) Modern Standby ready (for configurations with NVMe SSD and w/o PCIe cards) Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces	Embedded security (TPM 2.0) EraseDisk Credential Guard Ready and Device Guard Capable (requires 8 GB or more system RAM and SSD PCIe NVMe) Modern Standby ready (for configurations with NVMe SSD and w/o PCIe cards) Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
User security	User and supervisor BIOS password Hard disk password Access protection via external Smartcard reader (optional) Access protection via internal Smartcard reader (optional) AuthConductor™ Client Basic (secure authentication solution)	User and supervisor BIOS password Hard disk password Access protection via external Smartcard reader (optional) Access protection via internal Smartcard reader (optional) AuthConductor™ Client Basic (secure authentication solution)
Manageability		
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (with FH config) WoL (Wake on LAN)	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (with FH config) WoL (Wake on LAN)
Manageability software	DeskView Client DeskView Instant BIOS Management	DeskView Client DeskView Instant BIOS Management
DeskView components	BIOS Management incl. Security Inventory Management Driver Management Alarm Management	BIOS Management incl. Security Inventory Management Driver Management Alarm Management
Supported standards	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)	DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model)
Miscellaneous		
	Keyboard on with any key (USB) Thermal management Internal dust filter (optional)	Keyboard on with any key (USB) Thermal management Internal dust filter (optional)
Packaging information		
Packaging dimension (mm)	504 x 310 x 440 mm	504 x 310 x 440 mm
Packaging dimension (inch)	19.84 x 12.2 x 17.32 inch	19.84 x 12.2 x 17.32 inch
Max. quantity / pallet	24	24
Material - weight (g) carton	1,144 g	1,144 g
Material - weight (lbs) carton	2.52 lbs	2.52 lbs
Packaging notes	Bulk packaging for projects (optional)	Bulk packaging for projects (optional)
Warranty		
Warranty terms & conditions	www.fujitsu.com/hk/microsite/warranty/	

Fujitsu recommends Windows 10 Pro for business.

More information

Fujitsu OPTIMIZATION solutions

In addition to Fujitsu Desktop ESPRIMO D7011, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

hk.fujitsu.com/pc

Software

www.fujitsu.com/software/

More information

To learn more about Fujitsu Desktop ESPRIMO D7011, please contact your Fujitsu sales representative, Fujitsu Business partner, or visit our website.

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment/>



Copyrights

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see <http://www.fujitsu.com/global/about/resources/terms/>
© 2021 Fujitsu Business Technologies Asia Pacific Limited

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact Us

HONG KONG

Fujitsu Business Technologies Asia Pacific Ltd.
Tel: (852) 3910-8228
Email: fpca.hksales@hk.fujitsu.com
hk.fujitsu.com/pc

INDONESIA

PT Fujitsu Indonesia
Tel: (62) 21-570-9330
Email: marketing@id.fujitsu.com
id.fujitsu.com/pc

TAIWAN

Fujitsu Taiwan Ltd.
Tel: (886) 2-2311-2255
Email: ftl.lifebook@fujitsu.com
tw.fujitsu.com/pc

SINGAPORE

Fujitsu Asia Pte Ltd.
Tel: (65) 6512-7555
Email: faapl.info@fujitsu.com
sg.fujitsu.com/pc

PHILIPPINES

Fujitsu Philippines, Inc.
Tel: (63) 2-8841-8488
Email: info.fpi@fujitsu.com
ph.fujitsu.com/pc

THAILAND

Fujitsu (Thailand) Co., Ltd.
Tel: (66) 0-2302-1500
Email: info.th@fujitsu.com
th.fujitsu.com/pc

CHINA

Fujitsu (China) Holdings Co., Ltd. – PC China Division
Tel: 86 (21) 58871000-8721
Email: fpcacn.support@cn.fujitsu.com cn.fujitsu.com/pc

MALAYSIA

Fujitsu (Malaysia) Sdn. Bhd
Tel: (60) 3-8230-4188
Email: askfujitsu.my@fujitsu.com
my.fujitsu.com/pc

VIETNAM

Fujitsu Vietnam Limited
Tel: (84-24) 2220-3113
Email: sales-vn@fujitsu.com
vn.fujitsu.com/pc

Note: For countries not listed above, please contact Hong Kong office.

Specification disclaimers

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. 2. GB = 1 billion bytes. TB = 1 trillion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software. Up to 20 GB of HDD space is reserved for system recovery. 3. Shared memory depending on main memory size and operating system.

* The availability of Graphis and Physical Security module subject to countries/ regions. For more detail, please contact Fujitsu sales specialist.

FUJITSU shall not be liable for technical or editorial errors or omissions contained herein. Ultrabook, Celeron, Celeron Inside, Core Inside, Intel, Intel Logo, Intel Atom, Intel Atom Inside, Intel Core, Intel Inside, Intel Inside Logo, Intel vPro, Intel Evo, Itanium, Itanium Inside, Pentium, Pentium Inside, vPro Inside, Xeon, Xeon Phi, Xeon Inside, Intel Agilex, Arria, Cyclone, Movidius, eASIC, Enpirion, Iris, MAX, Intel RealSense, Stratix, and Intel Optane are trademarks of Intel Corporation or its subsidiaries. USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum. All other trademarks are the property of their respective owners.

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/global/about/resources/terms/.

© 2021 Fujitsu Business Technologies Asia Pacific Limited

Last Update: 7th October 2021