

## Data Sheet Fujitsu Display B22W-6 LED Displays

Advanced display: 55.9 cm (22-inch) widescreen Best ergonomic and energy saving solutions for office applications

The B22W-6 LED offers best ergonomics and usability for intensive office use with a 4-in-1 stand.

Environment-friendly LED technology with unique, high efficient energy saving solutions like ECO operation mode and ECO standby

Convenient and fatigue-proof longtime-usage with excellent visual ergonomics for the office

Optimized and relaxed position - with ergonomic stand featuring height adjust, swivel, tilt and  $90^\circ$  rotation

Flexible connectivity with 4x USB, DisplayPort, DVI and Analog

Ready for remote inventory and administration tasks due to the DisplayView Manageability tools

Representative design with space saving front frame and smart details like discretely integrated speakers

































## Technical details

Special features	
special leacules	DisplayView™ IT Suite, 4-in-1 Stand, ECO button, ECO Status LED: 3 colors for 3 modes, Pivot
Ergonomic stand	
Stand	4-in-1 Stand
leight adjust range	110 🗉
Picture height over desk (min)	55 mm
otation to portrait	90°
ilt angle	-5° / +35°
wivel angle	340°
icture performance	
anel and backlit	TN/LED
ontrast - typical	1000:1
ontrast - advanced	2,000,000:1
esponse time typical	5 ms
iewing angle (h/v) - typical	170°/170° CR5:1
olor performance	16.7 million colors (Hi-FRC)
rightness - typical	250 cd/m2
ize and resolution	
spect ratio	16:10
iagonal Size	55.9 cm (22-inch)
esolution (native)	1680 x 1050 pixel (recommended)
esolution (interpolated)	1440 x 900 pixel, 1280 x 1024 pixel, 1024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
icture size	474 x 296 mm
ixel Pitch	0.282 II
	U.202 III
requencies Iorizontal	30 - 82 kHz
ertical	56 - 76 Hz
onnectivity	1 0:   0 .
isplayPort	1 x DisplayPort
VI	1 x DVI (HDCP)
GA/D-SUB	1 x D-SUB
udio signal input	3.5 mm stereo phone jack
udio sound output	2 x 1.5 W
SB downstream	4 x USB 2.0
SB upstream	1 x USB
ase-of-use menu	
anguages	Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese
rightness / Contrast	Brightness, Contrast, Black level, Auto level
olor	sRGB, 6500K, 7500K, 9300K, Native, Custom Color (R,G,B)
nage adjust	Clock, Phase, H-Position, V-Position, Expansion
udio	Mute, Volume
nformation	Model name, S/N, Resolution/mode, Signal input
etup	Input select, Language, DDC-CI, OSD-Timeout, Factory recall
ower consumption (typical, w/o sou	ind)
oft switch off	0.3 W
ower save mode	0.3 W
Operating with EPA settings	22 W
Operating maximum brightness	28 W
Power supply display	integrated

Page 2 / 4

Power notes	(measured w/o sound and w/o USB device)
Electrical values	
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	
Compliance	
Europe	CE certification according to EC Directive 2004/108/EEC, EN 60950, Nordic Swan, RoHS, WEEE, IT-Eco-Declaration
Model	B22W-6
Germany	TÜV GS
Russia	GOST
USA/Canada	FCC Class B, cUL
Japan	VCCI
South Korea	KC
Argentina	TÜV-S
China	CCC
Saudi Arabia	SASO
Mexico	NOM
Global	TCO Displays 5.1, ENERGY STAR® 5.0, EPEAT® Gold (dedicated regions), ISO9241-307 (Pixel fault class I)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/
Quality and Reliability	
MTBF (demonstrated)	70000 h
Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	508 x 60 x 343 mm
Dimension with stand $(W \times D \times H)$	508 x 180 x 370 mm
Weight (packed)	8.0 kg
Weight (unpacked)	5.9 kg
Weight (Monitor only)	3.6 kg
Operating ambient temperature	5 - 35℃
Miscellaneous	
Miscellaneous	VESA DDC/ CI, Standardized mounting interface VESA FP MP MI 100 mm, Kensington lock prepared
Color	Marble grey
Package content	
Display delivered accessories	DVI-D Data cable 1.8 m, D-SUB Data cable 1.8 m, Audio cable 1.8 m, USB-cable 1.8 m (USB-A to USB-B), Power cable
	for wall socket (Euro-Schuko-Type CEE7) 1.8 m, Quickstart flyer, Utility CD, Warranty booklet, Safety booklet
Display delivered accessories notes	Data cables and audio cable detachable on display
Order information	
Order Code	S26361-K1375-V140
EAN-No.	4049699310652
Warranty	
Standard Warranty	3 years
Service level	Collect & Return Service (depending on country)
Spare Parts availability	5 years
Service Weblink	http://ts.fujitsu.com/Supportservice



# red dot design award winner 2011

Design of Fujitsu Displays P, B and E Line, International - March 15, 2011

### More information

#### Fujitsu platform solutions

In addition to Fujitsu Display B22W-6 LED, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### **Dynamic Infrastructures**

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

#### **Computing Products**

www.fujitsu.com/global/services/computing/

#### Software

www.fujitsu.com/software/

#### More information

Learn more about Fujitsu Display B22W-6 LED, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

http://ts.fujitsu.com/displays

#### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT.

Please find further information at http://www.fujitsu.com/global/about/environment/



#### Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms\_of\_use.html Copyright © Fujitsu Technology Solutions

#### Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

#### Contact

FUJITSU Technology Solutions Website: http://ts.fujitsu.com 2012-03-02 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms\_of\_use.html Copyright © Fujitsu Technology Solutions