DATA SHEET

ESPRIMO MOBILE M9410

Your mobile hotspot

Issue: August 2009

ESPRIMO Mobile M9410

You are frequently "on the road"? You don't accept any compromises? Business people like yourself know that the use of mobile hardware is an important work prerequisite. The lightweight 35.8 cm (14.1-inch) mainstream notebook ESPRIMO Mobile M9410 with its state-of-the-art Intel[®] Centrino[®] dual processor technology meets the increasing requirements for unlimited connectivity. It helps you to be productive at work, wherever you may be. With its new clear-line design the ESPRIMO Mobile M fits perfectly into your office environment.

No compromises when "on the road"

High-level productivity even with demanding applications thanks to state-of-the-art technology and powerful components.

■ Intel[®] Centrino[®] dual processor technology, 35.8 cm (14.1-inch) display

Ultimate connectivity

Available anytime, anywhere thanks to unrestricted connectivity, even if there is no hot spot nearby.

Optional integrated 3G/UMTS, WLAN and Bluetooth

Maximum security

Protect your company data against unauthorized third-party access.

Integrated SmartCard reader, optional TPM module and SmartCase Logon+

Great flexibility

The family concept offers standardized accessory components for the ESPRIMO Mobile U, M, D, X Series.

 Common port replicator, AC adapter and modular bay for optical drive, second battery or second hard disk

Extreme reliability

- Stable housing and innovative functions, built to meet the highest requirements.
- ShockSensor, spill-proof keyboard, robust magnesium cover and housing






















Components	
Processor	Intel [®] Core ™2 Duo T9600 (2.8 GHz, 6 MB , 1066 MHz)
	Intel [®] Core ™2 Duo T9550 (2.66 GHz, 6 MB , 1066 MHz)
	Intel [®] Core ™2 Duo P8800 (2.66 GHz, 3 MB , 1066 MHz)
	Intel [®] Core ™2 Duo P8700 (2.53 GHz, 3 MB , 1066 MHz)
	Intel [®] Core ™2 Duo P8600 (2.4 GHz, 3 MB , 1066 MHz)
	Intel [®] Celeron [®] 585 (2.16 GHz, 1 MB , 667 MHz)
Memory modules	2 GB (1 module(s) with 2 GB) DDR3, 1066 MHz, PC3-8500, SODIMM
	1 GB (1 module(s) with 1 GB) DDR3, 1066 MHz, PC3-8500, SODIMM
Hard disk drives (internal)	320 GB, 5400 rpm, SATA, 2.5-inch S.M.A.R.T.
	160 GB, 7200 rpm, SATA, 2.5-inch S.M.A.R.T.
	160 GB, 5400 rpm, SATA, 2.5-inch S.M.A.R.T.
	160 GB, 5400 rpm, FDE-3, 2.5-inch S.M.A.R.T.
Hard disk notes	ShockSensor for HDD shock protection
	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.
	Accessible capacity may vary, also depending on used software
Display	35.8 cm (14.1-inch) TFT 1440 x 900 pixel (WXGA+) non-glare display
Diopidy	35.8 cm (14.1-inch) TFT 1280 x 800 pixel (WXGA+) non-glare display
WLAN (optional)	Atheros Minicard b/g 802.11 b/g
	Intel [®] Wireless WiFi Link 5300 AGN 11/13ch
UMTS/HSUPA (optional)	Option GTM 382 (downlink 7.2 MBit/s, uplink 2.0 MBit/s)
Bluetooth (optional)	Bluetooth 2.1
,	
Modular bay options	2nd battery
	2nd hard disk drive
	DVD Super Multi
	Weight saver
Base unit	ESPRIMO Mobile M9410
General system information	
Chipset	Intel [®] GM45, ICH 9-M
BIOS features	BIOS based on Phoenix TrustedCore Notebook
Memory slots	2 DIMM (DDR3)
•	Optional 4 GB
Turbo memory	•
Supported capacity RAM (max.)	4 GB
Memory notes	8 GB - with future memory modules.
Interfaces	
Memory card slots	1 (SD/MMC/MS/MSPro/XD)
ExpressCard slots	1
SIM card slot	1
Modem (RJ-11)	Optional
USB 2.0 total	3 (2x USB 2.0, 1x eSATA & USB port)
VGA	1
Ethernet (RJ-45)	1
DC-in	1
Audio: line-in / microphone	1
Audio: line-out / headphone	1
Internal microphones	2
Docking connector for Port	1
Replicator	•
•	1
-	1
Kensington Lock support	1 Optional: 56 K V.92 modem MDC1.5

Wireless technologies	
Antennas	3 Dual band WLAN antennas, 2 UMTS antennas
WLAN notes	Import and usage according to country-specific regulations.
UMTS	Optional
Keyboard and pointing devices	i
	Spill-proof keyboard
	Number of keyboard keys: 86, Keyboard pitch: 19 mm, Keyboard stroke: 2.7 mm
	TouchPad with two mouse buttons Second set of mouse buttons Application buttons
Input devices (optional)	Optional: TouchStick
Multimedia	
Audio type	On board
Audio codec	Realtek ALC262
Audio features	Stereo speakers, Internal microphone (array)
Camera	Optional: Built-in ConfCam, 1.3 megapixel, VGA camera
Graphics	
Max. resolution external display	1920 x 1200 / true color / 60 Hz
Graphics brand name	Mobile Intel [®] GMA 4500M HD
Graphic features	DualView (Windows XP & Windows Vista)
Power supply	
AC adapter	20 V / 90 W (4.5 A)
Rated voltage range	100 - 240 V (AC Input)
Rated frequency range	50 - 60 Hz
1st battery	Li-Ion battery 6-cell, 5200 mAh, 57 Wh
2nd battery (optional)	Li-Ion 6 cell, 3800 mAh, 40 Wh
Battery features	Dynamic charge supported (rapid charge)
Runtime 1st battery	up to 5:45 h
Runtime 1st + 2nd battery	up to 9:45 h
Battery notes	Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Battery recharge time depends on usage.
Power consumption	
Power consumption note	see white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=7ee7f44c-de35-421c-8b00-3bdfa160b317
Dimensions / Weight / Environn	nental
Dimension (W x D x H)	335 x 245 x 37.9 mm
Weight	2.3 kg
Weight notes	Weight may vary depending on actual configuration
Operating ambient temperature	5 - 35°C
Operating relative humidity	20 - 85 % (running)
Operating system	
Operating system optional preinstalled	Microsoft [®] Windows Vista [®] Home Basic Microsoft [®] Windows Vista [®] Business 32bit TwinLoad Microsoft [®] Windows [®] XP Professional (DVD)
Operating system compatible	Microsoft® Windows® XP Professional
Operating system notes	Driver support for Microsoft Windows XP

Additional Software	
Additional software (preinstalled)	Adobe Acrobat Reader
	Camera
	EasyGuide online user documentation
	Nero Essentials (burning software)
	Norton Internet Security (incl. Firewall) on Drivers & Utilities DVD for Microsoft Windows XP
	Drivers & Utilities DVD (DUDVD)
	Toshiba Bluetooth Stack
	Mobile Software Suite:
	Application Button Utility Wireless Selector Utility
	ShockSensor Utility
	Fan Control Utility
	Power Saving Utility
Additional software (optional)	Windows Vista [®] recovery media
	Drivers & Utilities DVD (DUDVD)
	UMTS connection manager (optional with UMTS)
	DVD playback software
Manageability	
Manageability features	DeskUpdate Driver management
	DeskView Migrate (optional)
Managaability type	DeskView Control (optional)
Manageability type DeskView features	DeskView 10.x client management including: On/Offline remote client management
Deskview leatures	Detailed system inventory management and reports
	BIOS Management
	Remote power management
	System notifications
	Security Remote Control
	DeskView Helpdesk Integration
	WoL (Wake on LAN)
Supported standards	PXE DestD (meda (vou)
	BootP (made4you) WMI
Manageability link	http://ts.fujitsu.com/solutions/it_infrastructure_solutions/manageability/featurefinder.html
Security	
Physical security	Kensington Lock support
System security	Optional: Trusted plattform module (TPM 1.2)
Cystom Southy	Symantec Norton Internet Security (90 day test version)
User security	Hard disk password
	User and supervisor BIOS password
	Separate SmartCard slot
	SystemLock 2 BIOS SmartCard Security
Compliance	
Germany	GS
Europe	CE CE!
USA/Canada	
UUrvUallaud	CUL
Global	RoHS (Restriction of hazardous substances)
	WEEE (Waste electrical and electronical equipment)
	ENERGY STAR [®] 4.0
	Microsoft Operating Systems (HCT / HCL entry / WHQL)
Compliance link	WiFi certified https://sp.ts.fujitsu.com/sites/certificates/default.aspx
Deutocalization interations of the	
Portreplicator interfaces (option	
DC-in	1
Power on switch	1
Headphones	1
Audio: microphone in	1

USB 2.0 total

4

Portreplicator interfaces (optional)	
VGA	1
DVI	1, DVI-D single link, maximal resolution 1920 x 1200 pixel (WUXGA)
Serial (RS-232)	1
Mouse / Keyboard (PS/2)	1
Ethernet (RJ-45)	1
Parallel	1
Kensington Lock support	2
eSATA	1

Warranty	
Standard Warranty	1 year
Service level Maintenance and Support S	Collect & Return Service / Bring-In Service (depending on country) Services - the perfect extension
Recommended Service	3 years, On-site Service
Spare Parts availability	5 years
Service Weblink	htttp://ts.fujitsu.com/Supportservice

Information about environmental care, policies, programs and our Environmental Guideline FSC 03230: http://ts.fujitsu.com/aboutus Take back and Recycling information: http://ts.fujitsu.com/recycling

All rights reserved, including intellectual property rights. Changes to technical data reserved. Published by Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html Copyright © Fujitsu Technology Solutions August 2009