

850 VA "Basic 850" UPS, Shuko output sockets, black

EG-UPS-B850

ULTIMATE DEFENCE

- Provides backup power prevents data loss
- Protects your sensitive and valuable equipment
- Compact and reliable ideal for home and small office use



Features

- Uninterruptable 850 VA power supply for PC's
- Automatic output voltage regulation (AVR)
- LED status indication
- Short circuit protection
- Overload, surge, spike and lightning protection
- Audible and visual alarms
- Overcharge and overdischarge protection

Specifications

UPS type: line interactive
 Input: AC 220V \pm 25%, 50Hz/60Hz \pm 10%
 Output: AC 220V \pm 10%, 50Hz/60Hz \pm 0.5% (on battery)
 Switching time: 4-8ms
 Backup time: up to 20 mins (depends on the load)
 Battery: 151 x 65 x 95 mm, sealed lead-acid 12V/8Ah x 1 pc
 Charge time: up to 12 hours
 Sockets: 2 x Schuko output (CEE 7/4)
 Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing
 Power: 850 VA (510 W)
 Dimensions: 280 x 140 x 100 mm
 Product weight: 5.5 kg
 "Cold-start" function

Packaging

Q'ty in crtn, pcs	4
Crtn volume, CUM	0.045356
Crtn weight, kgs	21.4
Individual package size LxWxH:	338x147x210 mm
Carton size LxWxH:	580x340x230 mm
Country of origin	CN
Barcode	8716309087070
Customs code	8504408590

Package contents

UPS
User manual

Certificates



System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.