# **HANN**spree

### Experts in **Display**

#### HC 342 PFB

86,4 cm / 34" Diagonal LED Backlight – Format 21:9

- 34" 21:9 LED Backlight Monitor
- 3440 x 1440 UWQHD Resolution
- 178°/178° Ultra Wide Viewing Angle
- Digital Inputs: DP + HDMI x 2
- Built-In Stereo Speakers
- Frameless Design and Thin Bezel
- Multi-Functional Height Adjustable Stand
- Tilt and Wall-Mountable (VESA)
- Low Power Consumption
- External Power Adaptor
- Low Blue Light Mode, Flicker Free
- PIP: Picture In Picture
- PBP: Picture By Picture





86,4 cm / 34"

Part. No.: HC 342 PFB

### SIZE, RESOLUTION

**34.0"** 21:9

### 34"

21:9 Aspect Ratio



UltraWide QHD 3440 x 1440

## CONNECTIVITY, AUDIO



HDMI x 2 Display Port



Built-In Stereo Speakers

#### VIEWING ANGLE, HZ



178°/178° Wide Viewing Angle



75Hz Refresh Rate

#### **ERGONOMIC FEATURES**



Height Adjust. Stand



VESA



Tilt



Swivel


# **HANN**spree


### Experts in **Display**

Display Size	86,4 cm / 34" Diagonal
Panel Type	LED Backlight - ADS Panel*
Aspect Ratio	21:9
Resolution (H x V)	3440 x 1440 Ultra-Wide QHD
Brightness	300cd/m² (Typical)
Contrast (Typ.)	1.000:1 (Typical)
Contrast (Active)	10.000.000:1 (Active)
Viewing Angle L/R; U/D	178° H – 178° V (CR >10)
Response Time	5 msec (with OD)
Pixel Pitch	0,2325 (H) x 0,2325 (V) mm
Panel Surface	Anti-Glare, Haze level 25%; Hard Coating 3H
Display Colors	16.7 M
Horizontal Frequency	30 ~ 113 kHz
Vertical Frequency	56 ~ 75 Hz
Max Display Frequency	3440 x 1440 @ 75Hz
Input 1	HDMI 2.0 x 1
Input 2	HDMI 1.4 x 1
Input 3	DP 1.2 x 1
Buil-in Speakers	Yes, 2W x 2, Earphone jack
Power Consumption	On: 26W; Standby: 0,5W; Off: 0,3W
AC Power Range	External PSU DC: 12V – 5A Input: AC 100 ~ 240 Volt; 50 ~ 60 Hz
Product Dimensions	816,2 x 228,94 x 435~555 mm with stand (W x D x H) 816,2 x 69,13 x 360,2 mm without stand (W x D x H)
Packing Dimensions	1035 x 165 x 480 mm (W x D x H)
Net / Gross Weight	5,85 Kg / 8,2 Kg

- 1					
ĺ	Monitor Stand	Height Adjustable Stand (Lift 120 mr	m ± 5 mm)		
I	Tilt / Kensington Lock	-8°~15°(±2°) / Yes			
	Pivot / Swivel	- / Left: 45° - Right: 45°			
	Controls	Menu (Enter) / < (Vol) / > (Bri) / Exit	(Input) / Power		
	Color	Warm / Normal / Cool / User Modes			
	Preset Mode	PC, ECO, Movie, Game Modes			
	On Screen Display	7 OSD Languages			
	Accessory	Power Adaptor; Power Cable (1,5m); DP-DP Cable (1,5m); Quick Start Guide; Warranty Card			
	Other Features	PIP: Picture In Picture / PBP: Picture E Low Blue Light Mode / Flicker Free	: Picture In Picture / PBP: Picture By Picture v Blue Light Mode / Flicker Free		
	ENERG† Sur	oplier's Name	HANNspree		

Yes, 100 x 100 mm





**VESA Mounting** 

Supplier's Name	HANNspree
Model Name	HC342PFB
Energy efficiency class for standard Dynamic Range (SDR)	Е
Annual Energy Power Consumption (kWh/1000h)	26 kWh/1000h
On mode power demand for Standard Dynamic Range (SDR)	26 W
Off mode power demand (W)	0,3 W
Standby mode power demand (W)	0,5 W
Screen Diagonal (cm / inches)	86,4cm / 34"
Resolution	3440 x 1440

PART. NO.: HC 342 PFB



© 2021 HANNSpree Europe Holdings B.V. Specifications and design as well as accessories are subject to change without notice. Screen shots are simulated. Actual products may differ slightly from those illustrated on this promotion material. Please refer to actual samples for final selection. The products displayed on this promotion material may not be available for purchase in your particular country or locality. Please check with your local HANNspree authorized representatives for the availability of specific products in your area. All brand, product, Service names and logos are trademarks and/or registered trademarks of their respective manufactures and Companies.

\* "ADS" word mark / trademark and related patents on technologies belong to their respective owners.

**Display** Solutions