HP DesignJet T500 Printer series



The world's smallest plotters ¹ – easy printing for growing needs



The perfect fit – for your office and budget

- Save space by placing the world's smallest plotters¹ wherever they fit best, using the built-in stand.
- Save time by connecting and printing right away with Wi-Fi capabilities.
- Save money by printing in-house with HP's most affordable plotters.²

Radically simple – from setup to printout

- Speed up your PDF printing process with free HP Click software.
- · Easily access your files from cloud folders and print them using your smartphone with the HP Smart app.
- Impress your clients with beautifully designed posters using the free and intuitive HP Poster Web app.

DesignJet quality – from the most trusted brand³

- Meet client expectations with high-quality, highspeed A1/D-size printing, as fast as 27 seconds.⁴
- Get perfectly matched color on both small- and large-format prints thanks to the built-in A3/A4 tray.
- Achieve precise details with up to 2400 dpi and original HP/GL-2 capability.
- Convey your ideas with bold images, sharp lines on plain paper for any application with HP Bright Office Inks

For more information, please visit http://www.hp.com/go/designjett500

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: http://www.hp.com/go/learnaboutsupplies

Most compact footprint based on competitive alternatives with comparable size and features as of February 2019.

 ² Compared to other HD DesignJet T-series plotters, as of February 2019.
³ Compared to other HD DesignJet T-series plotters, as of February 2019.
⁴ The HP DesignJet T530 36-in Printer, available from authorised HP resellers, delivers A1/D prints in 27 seconds. The HP DesignJet T530 24-in Printer delivers A1/D prints in 30 seconds. The HP DesignJet T525 Printer series delivers A1/D prints in 35 seconds.

Technical specifications

Print	
Print speed	T525: 35 sec/page on A1, 70 A1 prints per hour T530 24-in: 30 sec/page on A1, 76 A1 prints per hour T530 36-in: 27 sec/page on A1, 79 A1 prints per hour ¹
Print resolution	Up to 2400 x 1200 optimised dpi
Technology	HP Thermal Inkjet
Margins	Roll: 5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in) Sheet: 5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in)
Ink types	Dye-based (C, M, Y); pigment-based (K)
Ink drop	5.5 pl (C, M, Y); 12 pl (K)
Printheads	1 (cyan, magenta, yellow, black)
Printhead nozzles	1376
Line accuracy	±0.1% ²
Minimum line width	0.02 mm (0.0008 in) (HP-GL/2 addressable);
Max optical density	8 L* min/2.10 D ³
Media	
Handling	Sheet feed, roll feed, input tray, automatic horizontal cutter
Sheet size	24-in: Input ray: 210 x 279 to 330 x 482 mm (8.3 x 11 to 13 x 19 in) Manual feed: 330 x 482 to 610 x 1897 mm (13 x 19 to 24 x 74.7 in) 36-in: Input ray: 210 x 279 to 330 x 482 mm (8.3 x 11 to 13 x 19 in) Manual feed: 330 x 482 to 914 x 1897 mm (13 x 19 to 36 x 74.7 in)
Roll size	24 in: 279 to 610 mm (11 to 24 in) rolls
Standard sheets	36 in: 279 to 914 mm (11 to 36 in) 24-in: Input tray: A4, A3 Manual Feet: A2, A1 36-in: Input tray: A4, A3 Manual Feet: A2, A1, A0
Grammage	60 to 280 g/m² (roll/manual feed); 60 to 220 g/m² (input tray)
Thickness	Up to 0.3 mm (Up to 11.8 mil)
Applications	Line drawings; Presentations; Renderings
Memory	1 GB;
Hard disk	None
Connectivity	
Interfaces	Fast Ethernet (100Base-T), Hi-Speed USB 2.0, Wi-Fi
Print languages (standard	i) HP-GL/2, HP-RTL, JPEG, CALS G4
Printing paths	Windows printer drivers, HP Print Service Plugin for Android, HP Print for Chrome for Chrome OS
Drivers	Raster driver for Windows
Dimensions (w x d x h)	
Printer	24-in: 987 x 530 x 932 mm (38.9 x 20.9 x 36.7 in) 36-in: 1292 x 530 x 932 mm (50.9 x 20.9 x 36.7 in)
Shipping	24-in: 1090 x 570 x 480 mm (42.9 x 22.4 x 18.9 in) 36-in: 1395 x 570 x 480 mm (54.9 x 22.4 x 18.9 in)
Weight	
Printer	24-in: 26 kg (57.3 lb) 36-in: 30.5 kg (67.2 lb)
Shipping	24-in: 48.5 kg (106.9 lb) 36-in: 58 kg (127.9 lb)
What's in the box	HP DesignJet TSOD series printer, printer stand, printhead, introductory ink cartridges, quick reference guide, setup poster, power cord
HP Software and solutions	HP Click, HP DesignJet Utility for Windows, HP Smart app, HP Poster Web app
Environmental ranges	
Operating temperature	5 to 40°C (41 to 104°F)
Operating humidity	20 to 80% RH
Storage temperature	-25 to 55°C (-13 to 131°F)
Acoustics	
Sound pressure	45 dB(A) (operating); < 16 dB(A) (idle);
Sound power	6.2 B(A) (operating); < 3.4 B(A) (idle);
Power	
Consumption	< 35 W (printing), < 6 W (ready), < 4.5 W (sleep), < 0.3 W (standby)
Requirements	Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1200 mA max
Certification	
Safety	EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC)
Electromagnetic	Compliant with Class B requirements, including: EU (EMC/R&TTE Directives)
Environmental	ENERGY STAR; WEEE; EU ROHS; REACH; EUP; EPEAT
Warranty	T525: One-year limited hardware warranty; T530: Two-year limited hardware warranty

Ordering information

Product

Accessories		
5ZY62A	HP DesignJet T530 36-in Printer	
5ZY61A	HP DesignJet T525 36-in Printer	
5ZY60A	HP DesignJet T530 24-in Printer	
5ZY59A	HP DesignJet T525 24-in Printer	

110005501105	
B3Q36A B3Q37A	HP DesignJet T120/T520 24-in Spindle HP DesignJet 36-in Spindle

Original HP printing supplies

C1Q10A	HP 711 DesignJet Printhead Replacement Kit	
P2V31A	HP 711 2-pack 80-ml Black DesignJet Ink Cartridges	
P2V32A	HP 711 3-pack 29-ml Cyan/Magenta/Yellow Ink Cartridges	
Use Original HP inks and printheads, and HP large format printing materials, to experience consistent high quality and reliable performance that enable less		

downtime. These tritical components are designed and engineered together as an optimized printing system, and Original HP inks are designed to maximize the life of HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, visit hp.com/go/OriginalHPinks.

Original HP large format printing materials

Q1396A HP Universal Bond Paper (FSC® certified)⁴ (recyclable)⁵ 610 mm x 45.7 m (24 in x 150 ft)

Constant and the Costed Paper (FSC® certified)⁴ (recyclable)⁵ 610 mm x 45.7 m (24 in x 150 ft) Cost29C HP Heavyweight Coated Paper (FSC® certified)⁴ (recyclable)⁵ 610 mm x 30.5 m (24 in x 100 ft)

COF18A HP Everyday Adhesive Matte Polypropylene, 2 Pack (recyclable)⁵ 610 mm x 22.9 m (24 in x 75 ft)

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

UC288E (24 in)/UC2T1E (36 in) HP 2y Nbd Onsite HP Design.let T525 HWS UC289E (24 in)/UC2T1E (36 in) HP 3y Nbd Onsite HP Design.let T525 HWS UC250E (24 in)/UC2T1E (36 in) HP 4y Nbd Onsite HP Design.let T525 HWS UC251E (24 in)/UC2T2E (36 in) HP 4y Nbd Onsite HP Design.let T525 HWS UC2528F (24 in)/UC2T5PE (36 in) HP 2y Nbd Design.let T525 HWS UC2528F (24 in)/UC2T5PE (36 in) HP 2y Nbd Design.let T525 HWS UC255E (24 in)/UC2T5PE (36 in) HP 2y Nbd Dosite HP Design.let T530 HWS UC255E (24 in)/UC2T2FE (36 in) HP 2y Nbd Onsite HP Design.let T530 HWS UC255E (24 in)/UC2T2FE (36 in) HP 2y Nbd Onsite HP Design.let T530 HWS UC25SFE (24 in)/UC2T0FE (36 in) HP 3y Nbd Onsite HP Design.let T530 HWS UC25SFE (24 in)/UC2T0FE (36 in) HP 3y Nbd Dosite HP Design.let T530 HWS UC25SFE (24 in)/UC2U0FE (36 in) HP 3y Nbd Design.let T530 HWS UC25SFE (24 in)/UC2U0FE (36 in) HP 3y Nbd Design.let T530 HWS UC25SFE (24 in)/UC2U0FE (36 in) HP 3y Nbd Design.let T530 HWS UC25SFE (24 in)/UC2U0FE (36 in) HP 3y Nbd Design.let T530 HWS

HP DesignJet Support Services offer installation, maintenance, and extended support services (e.g. 2,3, 4 and 5 years). For more information, please visit hp.com/go/cpc ECO highlights

ENERGY STAR® certified¹ and EPEAT® Bronze registered²

Free, convenient HP ink cartridge recycling³ FSC®-certified papers⁴ and a range of recyclable HP media with a take-back • program⁵

Please recycle large-format printing hardware and printing supplies. Find out how at our website: http://www.hp.com/ecosolutions

¹ ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the

¹ ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency.
² EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country.
³ Program availability varies. Please check http://www.hp.com/recycle for details.
⁴ BMG trademark license code FSC®-C115319, see http://www.fsc.org. HP trademark license code FSC®-C01763, see http://www.fsc.org. Not all FSC®-certified products are available in all regions.
⁵ Many HP printing materials are recyclable through commonly available recycling programs. For information about HP large format printing materials, please visit http://www.HPLFMedia.com.

Mechanical printing time. Printed in Fast mode, using HP Bright White Inkjet Paper (bond) and Original HP inks.
±0.1% of the specified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E printing material in Best or Normal mode with HP Heavyweight Coated roll feed and Original HP inks.
With HP Premium Instant Dry Photo Gloss media with Original HP inks.



© Copyright 2019 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. 4AA7-5523 eu-en August 2019

