HP E27m G4 QHD USB-C Conferencing Monitor



Connect with Confidence. Conference with Ease.

Conference and connect with ease with the Zoom Certified HP E27m G4 USB-C Conferencing Monitor that has an integrated 5MP, tilt-adjustable webcam, front-firing speakers, and dual mics. Work effortlessly and simplify your set up with one USB-C® cable¹ that delivers data, video, and up to 65W of laptop charging.



*Product image may differ from actual product

Present Your Best Self.

• Say goodbye to blurry images or muffled sound on video calls. Get sharp picture with an integrated 5 mega-pixel webcam with 25 degrees of tilt adjustability for perfect angles, pop-up action for privacy, improved color sensor and Windows Hello™ support. Built-in speakers and echo-cancelling dual mics produce rich, clear sound.

Zoom Certified.

 HP's partnership with Zoom culminated in weeks of lab testing for webcams, mics, and speakers against over 200 of Zoom's rigorous audio and video quality benchmarks². Because HP met or exceeded all requirements, you can be sure our hardware works seamlessly with Zoom's software to deliver an unmatched conferencing experience every time.

Simplify your set up.

• Keep your set up simple and seamless with a display that has everything built in. Connect a keyboard and mouse to the ports on the back of this monitor and only one USB-C® cable¹ to your notebook for data, video, and up to 65W of charging.

Your Webcam and Audio Your Way.

Customize your webcam and audio settings to your needs within a simple and intuitive dashboard in the newly updated HP Display
Center³. Use the preview window to zoom into the perfect frame and adjust brightness or exposure. Select from music, video, and
voice EQ modes to curate your sound experience.

Featuring

- Work effortlessly with 4-way ergonomics and comfortably view your work on a 27-inch diagonal QHD screen that reduces blue light with HP Eve Ease.
- Push the webcam down for worry-free privacy.
- Speakers that deliver crystal-clear audio straight to you.
- Daisy chain or run two monitors via DisplayPort™.⁴
- This monitor's plastics consist 90% recycled materials and its recyclable packaging is 100% sustainably sourced.^{5,6}
- HP Eye Ease keeps you comfortable by reducing blue light.
- Packed with ports including HDMI, DisplayPort[™], USB-C[®] plus four USB ports.¹
- Personalize settings and dim the screen upon unauthorized disconnection.³
- Manage deployment, asset tracking and monitor settings remotely.
- RJ-45 port for stable internet connection and remote IT manageability.⁷
- Get peace of mind with a 3-year warranty.

HP E27m G4 QHD USB-C Conferencing Monitor Specifications Table







*Product i	mage may	differ from	actual	product

*Product image may differ from actual product	
Display type	IPS
Panel Active Area	23.49 x 13.22 in 59.67 x 33.57 cm
Display size (diagonal)	77"
Brightness	300 nits ¹
Contrast ratio	100c1 ¹
Response Ratio	Today Sms (IG (with overdrive) 1
Product colour	Black head, silver stand
Aspect ratio	16.91
Native resolution	QHD (2560×1440) ^{1,8}
Resolutions supported	$640 \times 480; 720 \times 400; 800 \times 600; 1024 \times 768; 1280 \times 720; 1280 \times 800; 1280 \times 1024; 1440 \times 900; 1600 \times 900; 1600 \times 1200; 1680 \times 1050; 1920 \times 1080; 1920 \times 1200; 2560 \times 1400; 2560 \times 1440 \times 1000; 1600 \times 1000; 1600 \times 1200; 1600 \times 1200; 1600 \times 1000; 1600 \times $
Display features	On-screen controls; Anti-glare; Height Adjust/Tilt/Swivel/Pivot; Integrated speakers; Webcam; HP Eye Ease
User controls	Exit; Information; Management; Power control; Input control; Menu control; Brightness*; Image; Color
Horizontal viewing angle	178*
Vertical viewing angle	178°
Display colors	Up to 16.7 million colors supported
Height adjustment range	150 mm
Pixel pitch	0.2331 mm x 0.2331 mm
Horizontal Display Scan Frequency	30-115 kHz
Vertical Display Scan Frequency	50-75 Hz
Tilt	-5 to +23*
VESA mounting	100 mm x 100 mm
Pivot	±90
Low blue light modes	Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified)
Panel bit depth	8 bit
Integrated privacy filter	No
Touch-enabled	Not touch-enabled
Hardness	3H
Swivel	±45°
Maximum resolution	QHD (2560 x 1440 @ 75 Hz)
Pixels Per Inch	109 ppi
Bezel	3-sided micro-edge
Screen treatment	Anti-glare
Screen treatment Curvature	Anti-glare Flat
Screen treatment Curvature Display Color Gamut	Anti-glare Flat 99% sRGB
Screen treatment Curvature Display Color Gamut Flicker-free	Anti-glare Flat 99% sRGB Yes
Screen treatment Curvature Display Color Gamut Flicker-free Dynamic Display Contrast Ratio	Anti-glare Flat 99% sRGB
Screen treatment Curvature Display Color Gamut Flicker-free	Anti-glare Flat 99% sRGB Yes
Screen treatment Curvature Display Color Gamut Flicker-free Dynamic Display Contrast Ratio	Anti-glare Flat 99% \$RGB 10000000:1 Ves Edge-lit
Screen treatment Curvature Display Color Gamut Filcker-free Dynamic Display Contrast Ratio Detachable stand	Anti-glare Flat 99% \$RGB Yes 10000000:1 Ves Edge-lit 1 SuperSped USB Type-C* SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 HUPS STATE ST
Screen treatment Curvature Display Color Gamut Flicker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors	Anti-glare Flat 99% SRGB 10000000:1 Ves Edge-lit 1 Huper In-Expert Supper C* Subps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 Huper In-Expert In-Exp
Screen treatment Curvature Display Color Gamut Flicker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors Hdcp	Anti-glare Flat 99% SRGB 10000000:1 Yes Edge-lit 1 SuperSpeed USB Type-C® SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 DisplayPort™ 1.2 1 DisplayPort™ 1.2 1 SignayPort™ 1.2 1 SystyPort™
Screen treatment Curvature Display Color Gamut Flicker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors	Anti-glare Flat 99% SRGB 10000000:1 Ves Edge-lit 1 Huper In-Expert Supper C* Subps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 Huper In-Expert In-Exp
Screen treatment Curvature Display Color Gamut Flicker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors Hdcp	Anti-glare Flat 99% \$4KB 10000000:1 Ves Edge-lit 1 Hundright Super-K® 5Cbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 Hundright Super-K® 5Cbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 BisplayPort™ 1.2 au 1 BisplayPort™ 1.2 au 4 Super-Super-USB Super-A 5Cbps signaling rate 1 Big-J-4S 1 Bi
Screen treatment Curvature Display Color Gamut Flicker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors Hdcp Camera	Anti-glare Flat 99% SRGB 10000000:1 Ves Edge-lit 1 Super 13-e 1 S
Screen treatment Curvature Display Color Gamut Flicker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors Hdcp Camera Microphone	Anti-glare Flat 99% SRGB 10000000:1 Yes Edge-lit 1 HUPS 1pet (2.5 SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 HUPS 1pet (3.5 Super 1.2) 1 DisplayPort™ 1.2 1 DisplayPort™ 1.2 1 Super Speed USB Type-C* SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 DisplayPort™ 1.2 1 Super Speed USB Type-C * SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 DisplayPort™ 1.2 1 Super Speed USB Type-C * SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 Super Speed USB Type-C * SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 Super Speed USB Type-C * SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 HUPS 1 Super Speed USB Type-C * SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 HUPS 1 Super Speed USB Type-C * SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 HUPS 1 Super Speed USB Type-C * SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 HUPS 1 Super Speed USB Type-C * SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 HUPS 1 Super Speed USB Type-C * SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 HUPS 1 Super Speed USB Type-C * SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 HUPS 1 Super Speed USB Type-C * SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 HUPS 1 Super Speed USB Type-C * SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 HUPS 1 Super Speed USB Type-C * SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 HUPS 1 Super Speed USB Type-C * SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 HUPS 1 Super Speed USB Type-C * SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2
Screen treatment Curvature Display Color Gamut Filcker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors Hdcp Camera Microphone Windows Hello compatible Speakers	Anti-glare Flat 99% \$RGB Yes 10000000:1 Ves Edge-lit 1 Super Speed USB Type- C** Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort** 1.2) 1 H Display Port*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort** 1.2) 1 H DisplayPort**** 1.2- out 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort*** 1.2- Scbps signaling rate (up to 65W USB Po
Screen treatment Curvature Display Color Gamut Filcker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors Hdcp Camera Microphone Microphone Microphone Speakers Speakers Speakers output power	Anti-glare Flat 99% \$RGB 10000000:1 Ves Edge-lit 1 KyperSped USB Type-C® SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 KyperSped USB Type-C® SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 ByperSped USB Type-C® SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 ByperSped USB Type-C® SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 ByperSped USB Type-C® SGbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 Ry-dS 1 Ry
Screen treatment Curvature Display Color Gamut Flicker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors Hdcp Camera Microphone Windows Hello compatible Speakers Speakers Speakers Certified collaboration software	Anti-glare Flat 99% \$RGB Yes 10000000:1 Ves Edge-lit 1 KuperSpt.ed USB Type-C® Schps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 KuperSpt.ed USB Type-C® Schps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort™ 1.2) 1 DisplayPort™ 1.2- up 1.2
Screen treatment Curvature Display Color Gamut Flicker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors Hdcp Camera Microphone Windows Hello compatible Speakers Speaker output power Certified collaboration software Management software	Anti-glare Flat 99% \$RGB 10000000:1 Ves Edge-lit 1 Hours Super
Screen treatment Curvature Display Color Gamut Flicker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors Hdcp Camera Microphone Windows Hello compatible Speaker output power Certified collaboration software Management software Management software Environmental	Anti-glare Flat 99% \$RGB Yes 10000000:1 Ves Edg- lit 1 Super Speed USB Type- C** SCBps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort** 1.2) 1 1 109/1 Jp 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Screen treatment Curoature Display Color Gamut Filcker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors Hdcp Camera Microphone Windows Hello compatible Speakers Speakers Speakers Certified collaboration software Management software ³ Environmental Power	Anti-glare Flat 99% sRGB 10000000:1 Ves Edge-lit 1 Super Speed USB Type-C* 5Gbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort** 1.2) 1 H MDF 12 Port 12 P
Screen treatment Curvature Display Color Gamut Filcker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors Hdcp Camera Microphone Microphone Microphone Windows Hello compatible Speakers Speaker output power Certified collaboration software Management software ³ Environmental Power Power Consumption	Anti-glare Flat 99% sRGB Yes 10000000:1 Yes Edge-lit 1 SuperSpeed USB Type-C* SCbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort** 1.2) 1 H DM 1.4 1 DisplayPort** 1.2 - Out 1 DisplayPort** 1.2 - Out 2 DisplayPort** 1.2 - Out 1 R J-d's Nes, DisplayPort** and HDMI Yes, SMP Independent tilt -20* to 5*; Windows Hello support (IR Sensor); Pop-up privacy; Auto focus Yes (acho cancelling) Yes 2 2 2 x S W Zoom HP Display Center; HP Display Manager Operating temperature Sta 35**C; Operating humidity: 20 to 80% non-condensing 100 - 240 WS 50/60 Hz 160 W (maximum), 51 W (typical), 0.5 W (standby)
Screen treatment Curoature Display Color Gamut Filcker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors Hdcp Camera Microphone Windows Hello compatible Speakers Speakers Speakers Certified collaboration software Management software ³ Environmental Power	Anti-glare Flat 99% sRGB 10000000:1 Ves Edge-lit 1 Super Speed USB Type-C* 5Gbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort** 1.2) 1 H MDF 12 Port 12 P
Screen treatment Curvature Display Color Gamut Filcker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors Hdcp Camera Microphone Microphone Microphone Windows Hello compatible Speakers Speaker output power Certified collaboration software Management software ³ Environmental Power Power Consumption	Anti-glare Flat 99% sRGB Yes 10000000:1 Yes Edge-lit 1 SuperSpeed USB Type-C* SCbps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort** 1.2) 1 H DM 1.4 1 DisplayPort** 1.2 - Out 1 DisplayPort** 1.2 - Out 2 DisplayPort** 1.2 - Out 1 R J-d's Nes, DisplayPort** and HDMI Yes, SMP Independent tilt -20* to 5*; Windows Hello support (IR Sensor); Pop-up privacy; Auto focus Yes (acho cancelling) Yes 2 2 2 x S W Zoom HP Display Center; HP Display Manager Operating temperature Sta 35**C; Operating humidity: 20 to 80% non-condensing 100 - 240 WS 50/60 Hz 160 W (maximum), 51 W (typical), 0.5 W (standby)
Screen treatment Curvature Display Color Gamut Flicker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors Hdcp Camera Microphone Windows Hello compatible Speakers Speaker output power Certified collaboration software Management software ³ Environmental Power Power Power	Anti-glare Flat 99% sRGB 99% sRGB 10000000-1 Yes Edge-lit 1 Super'Speed USB Type-C** Schys signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort** 1.2) 1 H DisplayPort** 1.2-out 1 N Super'Speed USB Type-A Schys signaling rate 1 X 3.5 mm Audio Jack (Pudio in/Out Combo) 1 X 4-6 1 X 3.5 mm Audio Jack (Pudio in/Out Combo) 1 X 4-7 1 Yes, DisplayPort** and HDMI 1 Yes, Style 1 Yes (echo cancelling) Yes (echo cancelling) Yes 2 X 5 W Zoom HP Display Center: HP Display Manager Operating temperature is 515°C (Derating humidity: 20 to 80% non-condensing) 100 - Val VAC 50/65 NU (Standby) 24.13 x 1.85 x 15.61 in; 61.28 x 4.7 x 39.66 cm (Without stand.)
Screen treatment Cureature Display Color Gamut Filcker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors Hdcp Camera Microphone Windows Hello compatible Speakers Speakers output power Certified collaboration software Management software ⁹ Environmental Power Power consumption Dimensions Weight Physical security features ²	Anti-glare Flat 99% sRGB Yes 100000001 Yes Edge-lit 1 SuperSpeed USB Type-C** SCapps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort** 1.2) 1 HDM 1.4 1 HDM 1.4 1 SuperSpeed USB Type-C** SCapps signaling rate (up to 65W USB Power Delivery, Alt Mode DisplayPort** 1.2) 1 HDM 1.4 1 SuperSpeed USB Type-A SCapps signaling rate 1 SuperSpeed USB Type-C** Scapps signaling
Screen treatment Curvature Display Color Gamut Filcker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors Hdcp Camera Microphone Windows Hello compatible Speakers Speakers output power Certified collaboration software Management software ⁹ Environmental Power Power consumption Dimensions Weight Physical security features ² Energy efficiency compliance Certification and compliance	Anti-glare Flat Spile S
Screen treatment Cureature Display Color Gamut Filcker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors Hdcp Camera Microphone Windows Hello compatible Speakers Speaker output power Certified collaboration software Management software ⁵ Environmental Power Power consumption Dimensions Weight Physical security features ² Energy efficiency compliance	Anti-glare Flat Plat 100000001 Yes 100000001 Yes 15-goe-Speed USB Type-C** Scops signaling rate lip to 65W USB Power Delivery, Alt Mode DisplayPort** 1.2) 15-goe-Speed USB Type-C** Scops signaling rate lip to 65W USB Power Delivery, Alt Mode DisplayPort** 1.2) 10-splayPort*** 1.2 11-splayPort*** 1.2 12-splayPort*** 1.2 13-splayPort*** 1.2 14-splayPort*** 2.3 15-splayPort*** 1.2 15-splayPort*** 2.3 15-splayPort*** 2.3 16-splayPort*** 2.3 16-splayPort*
Screen treatment Curvature Display Color Gamut Filcker-free Dynamic Display Contrast Ratio Detachable stand Backlight type Ports and Connectors Hdcp Camera Microphone Windows Hello compatible Speakers Speakers output power Certified collaboration software Management software ⁹ Environmental Power Power consumption Dimensions Weight Physical security features ² Energy efficiency compliance Certification and compliance	Anti-glare Flat Spile S

HP E27m G4 QHD USB-C Conferencing Monitor

Accessories and services (not included)

HP B300 PC Mounting Bracket



Customize an altogether better solution with the HP B300 PC Mounting Bracket, which lets you attach your HP Workstation, HP Desktop Mini, HP Chromebox or select HP Thin Client directly behind select 2017 and 2018 HP EliteDisplays and HP Z Displays.

Product number: 2DW53AA

HP Business PC Security Lock v3 Kit



Help prevent chassis tampering and secure your PC and display in workspaces and public areas with the affordable HP Business PC Security Lock v3 Kit. Product number: 3XJ17AA

HP Quick Release Bracket 2



Use the HP Quick Release Bracket 2 to attach your HP Desktop Mini to an HP display 1 and a variety of stands, arms or wall mounts. 2 The failsafe "Sure-Lock" mechanism snaps the PC securely in place, and can be further secured with a theft-deterrent security screw.

Product number: 6KD15AA

HP Single Monitor Arm



The HP Single Monitor Arm is the perfect desk accessory for your work life. Sleek and streamlined, the HP Single Monitor Arm is designed to complement the way you work.

Product number: BT861AA

HP Integrated Work Center for Desktop Mini and Thin Client



Make the most of small work spaces with an HP IWC Desktop Mini/Thin Client that lets you create a compact desktop solution by combining a display with your choice of platform and giving you convenient front access to all of its inputs.

Product number: G1V61AA

HP E27m G4 QHD USB-C Conferencing Monitor

Messaging Footnotes

- ¹ Comes with one USB-C® cable and Power Cord.
- ² Based on a monitor series with Zoom Certification as of November 2021.
- ³ Host PC requires Windows 10. HP Display Center is available on the Microsoft store.
 4 DisplayPort™ cable not included. Monitors come with one USB-C® cable to connect your PC and a Power Cord for the monitor.
- ⁵ Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 EPEAT standard. Plastics consist of 90% Post-Consumer Recycled, with 85% Recycled Information Technology Equipment (ITE) + 5% Ocean-Bound Plastics (PET).
- 6 100% outer box packaging and corrugated cushions made from sustainably sourced certified and recycled fibers.
 7 HP Display Manager software agent must be running on a web server and host PC. Some limitations may apply to legacy monitors.

Technical Specifications Footnotes

- $^1 \, All \, specifications \, represent \, the \, typical \, specifications \, provided \, by \, HP's \, component \, manufacturers; \, actual \, performance \, may \, vary \, either \, higher \, or \, lower. \, and \, be a component \, manufacturers; \, actual \, performance \, may \, vary \, either \, higher \, or \, lower. \, and \, be a component \, manufacturers; \, actual \, performance \, may \, vary \, either \, higher \, or \, lower. \, and \, be a component \, manufacturers; \, actual \, performance \, may \, vary \, either \, higher \, or \, lower. \, actual \, performance \, may \, vary \, either \, higher \, or \, lower. \, actual \, performance \, may \, vary \, either \, higher \, or \, lower. \, actual \, performance \, may \, vary \, either \, higher \, or \, lower. \, actual \, performance \, may \, vary \, either \, higher \, or \, lower. \, actual \, performance \, may \, vary \, either \, higher \, or \, lower. \, actual \, performance \, may \, vary \, either \, higher \, or \, lower. \, actual \, performance \, may \, vary \, either \, higher \, or \, lower. \, actual \, performance \, may \, actual$
- ² Lock sold separately.
- ³ EPEAT® registered where applicable. EPEAT registration varies by country. See www.epeat.net for registration status by country. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit www.epeat.net for more information.
- 4 Included cables may vary by country
- 5 External power supplies, WWAN modules, power cords, cables and peripherals excluded. Service parts obtained after purchase may not be Low Halogen. 6 Percentage of ocean-bound plastic contained in each component varies by product.

- 7 100% outer box packaging and corrugated cushions made from sustainably sourced certified and recycled fibers.

 8 DisplayPort™ 1.2 or HDMI 1.4 or USB Type C® (Alt Mode DisplayPort™ compatible) required to drive panel at its native resolution. The video card of the connected PC must be capable of supporting 2560 x 1440 at 60 Hz using one DisplayPort™, HDMI, or USB Type C® (Alt Mode DisplayPort™).
- ⁹ Host PC requires Windows 10. HP Display Center is available on the Microsoft store.



