ThinkCentre M90n-1 Nano 11AD000VHX

Product ThinkCentre M90n-1 Nano

Region EET

Country/Region Hungary

Machine Type 11AD

TopSeller TopSeller

Processor Intel Core i5-8365U (4C / 8T, 1.6 / 4.1GHz, 6MB)

Chipset Intel SoC platform

Graphics Integrated Intel UHD Graphics 620

Memory 8GB Soldered DDR4-2666

Storage 1x 256GB SSD M.2 2280 PCIe NVMe Opal2

Optical None

Speaker 1Wx1

Ethernet Intel I219-LM, 1x RJ45

WLAN + Bluetooth Intel 9560 11ac, 2x2 + BT5.0, vPro

Chassis Intrusion Switch Chassis Intrusion Switch

Kensington Cable Lock None

Adapter Cage None

Dust Filter None

VESA Mount None

Color Black

Stand None

Keyboard Calliope Wireless Keyboard, Black, Hungarian

Mouse Calliope Wireless Mouse

Power Supply 65W 88% Adapter

TUV Low Noise None

Monitor Cable None

System Management Intel vPro

Operating System Windows 10 Pro 64, Hungarian / English

Bundled Software

Base Warranty 3-year, Onsite

Bundled Service

EAN / UPC / JAN 0193638008132

End of Support 2025-08-02

Announce Date 2019-07-02

L WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifcations or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.

https://psref.lenovo.com

PSREF

Visit psref website for the latest version of Product Specifcations Reference. © Lenovo, 2020. All rights reserved.



(intel)

ThinkCentre M90n-1 Nano Platform Specifications

Product Specifications Reference (PSREF)

Processor	Intel® 8th Generation	Intel Core	e™ i3 / i5 / i7 Pro	cessor			Manageability		
	Processor	Cores / Threads	Frequency Base/Max(GHz)	Cache	Memory Support (Up to)	Integrated Graphics	Security chip	adapter to enable vPro function through wireless connection) Discrete TPM 2.0, TCG Certified	
	Core i3-8145U	2/4	2.1G / 3.9G	4 MB	DDR4-2400	UHD 620	Security features	Security slot (in rear for optional Boot sequence control	
	Core i5-8265U	4/8	1.6G / 3.9G	6 MB	DDR4-2400	UHD 620		Kensington [®] MicroSaver [®] cable) • Boot without keyboard and mouse	
	Core i5-8365U	4/8	1.6G / 4.1G	6 MB	DDR4-2400	UHD 620		 Chassis intrusion switch Power-on password Individual USB port disablement Smart USB protection, allows keyboard 	
	Core i7-8665U	4/8	1.9G / 4.8G	8 MB	DDR4-2400	UHD 620		Administrator password Administrator password Marcos protection, allows keyboard mouse only, blocks all storage devices	
Memory	8GB or 16GB / DDR4-2666* / soldered to systemboard, no sockets, non-ECC * System automatically clocks down for the processors with lower memory controller						Kevboard	Hard disk password Some: Lenovo Calliope Keyboard (USB connector), black	
Storage	Support up to two M.2 SSD Some: M.2 2280 SSD / PCIe NVMe, PCIe 3.0 x 4* Some: M.2 2242 SSD / PCIe NVMe, PCIe 3.0 x 2** Some: Intel Optane™ Memory H10 with Solid State Storage, M.2 2280, PCIe NVMe 3.0 x 4 (not support Celeron) * M.2 SSD / Optane with SSD in PCIe 3.0 x 2 M.2 slot can only run at PCIe 3.0 x2 ** 128G M.2 2242 SSD not supported on Machine Type 11AM / 11AS / 11AK / 11AL RAID 0/1 support (RAID preset only available via special bid model) None						Mouse	Some: Lenovo Traditional Keyboard (USB connector), black Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black Some: Lenovo Calliope Mouse (USB connector), black Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black	
RAID Optical							Mechanical	Nano (0.35L), black color; metal case Three M.2 slots: two for M.2 SSD (one PCIe 3.0 x4 and one PCIe 3.0 x2) and one for WLAN	
					D: 11/8 40		-	Dimensions (WxDxH) Weight (Approx.)	
Graphics	Intel UHD Graphics DisplayPort [™] , one US displays;							M90n-1 Nano 7.05" X 3.46" X 0.87" 1.11 lb (0.505 kg), (with fan, 0.35L) 179mm X 88mm X 22mm vary by config	
Monitor cable	Max resolution: 4096x2304 (DP) @60Hz; 4096x2304 (Type-C) @60Hz; Optional DP to VGA dongle, DP to HDMI dongle, Type-C to VGA dongle, Type-C to HDMI dongle, Type-C to DP dongle					, Type-C to	Mounting	Some: VESA mount bracket kit, supports VESA 75mm Some: VESA mount bracket kit with adaper holder, supports VESA 75mm Some: DIN rail mount bracket kit	
Chipset	Intel SoC (System on Chip) platform						Floor Stand	None	
Front ports (Std.)* 2x USB 3.1 Gen2, 1x USB 3.1 Type-C Gen 2, one headphone / microphone combo						Power supply	65 watts AC/DC adapter, autosensing, 88% PSU (Not for TIO models)		
Rear ports (Std.)*	jack (3.5mm) r ports (Std.)* 2x USB 3.1 Gen2, 1x USB 3.1 Type-C Gen 2 (with display function, support power-in [20V and >45W]), 1x ethernet (RJ-45), 1x DisplayPort					port	Limited warranty	Some: 1-year, limited onsite service / service upgrades available Some: 3-year, limited onsite service / service upgrades available	
	* Depending on many factors, actual data transfer speed may be lower than theoretical speed					etical speed	Preload	Preloaded operating system	
Audio support	Realtek ALC233VB /	/ internal speaker (1watt)					Some: Windows [®] 10 Pro 64-bit Some: Windows 10 Home 64-bit		
WLAN	Some: 11ac wireless, M.2 Card, Realtek RTL8822CE (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Realtek RTL8822CE (dual band),						Environment	ENERGY STAR [®] 7.1, EPEAT [™] Silver rating (North America), ErP Lot 3, TCO 8.0 TUV ultra low noise verified (on some models), RoHS, WEEE, REACH	
	Wi-Fi + Bluetooth 5.0 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Intel Wireless-AC 9462 (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, 1x1						MIL-SPEC test	MIL-STD-810H (Low Pressure [Altitude], High Temperature, Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock, Fungus, Solar Radiation)	
	 Some: 11ac wireless, M.2 Card, Intel Wireless-AC 9560 (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Intel Wireless-AC 9560 (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, Intel vPro technology support, 2x2 					nort 0x0	Accessories	For compatible accessories, please go to http://smartfind.lenovo.com	
Bluetooth Ethernet	WI-FI + Bluet Some: Bluetooth 5.0 Gigabit ethernet, Inte) wireless, el Ethernet	integrated in Wi Connection I21	-Fi + BT	combo adapter	•		Lenovo March 20	

Note: The specifications above may not be available in all regions.

Lenovo, March 2020

ThinkCentre M90n-1 Nano



(intel)

(intel)









