

PROFESSIONAL PERFORMANCE AT WIDE-VIEW DISPLAY.



Lenovo

A SLEEK 24" MONITOR WITH OUTSTANDING IMAGE QUALITY.

The sleek, stylish ThinkVision T24d-10 Monitor doesn't just display images – it presents them at over 99% sRGB color gamut and exceptionally crisp 1920 x 1200 resolutions across near-frameless 24" display. Enjoy vivid images across wide (178°/178°) viewing angles with no color distortion or reflection. With elegant slim design, the monitor fits in any workspace. Get the large visual workspace you need with a professional monitor designed to enhance productivity and make collaboration easy.

WHY YOU SHOULD BUY THE THINKVISION T24d-10 MONITOR




Performance and Productivity

Professional performance defines the WUXGA (1920 x 1200) resolution, over 99% sRGB high color gamut, 1000:1 contrast and In-Plane Switching for exceptional viewing angles across the entire 24" display.



Productivity at its Finest

A full-function stand ensures your display sports an executive look regardless of whether you swivel, tilt, pivot, or lift. Paired with near-edgeless screen, you can enjoy a clean look and seamless views across multi-monitor displays.



Ergonomic and Manageable

The ergonomic full-function stand is perfect for collaboration. It supports the new tiny clamp bracket for easy set-up of the ThinkCentre Tiny. Practical cable management effectively manages desktop clutter.

THE THINKVISION T24d-10 MONITOR IS BEST SUITED FOR

1 Users and businesses that need a highest-quality professional monitor.

2 Organizations that require highly detailed display for uses like finance or graphics.

3 Organizations that require professional quality monitors that also deliver a green advantage.



WWW.LENOVO.COM



ThinkVision T24d-10 MONITOR

SPECIFICATIONS

DISPLAY		DIMENSIONS (W x D x H)	
Panel Size	24"	Size Packed (mm)	160 x 655 x 422
Panel Type	In-Plane Switching	(inches)	6.3" x 25.79" x 16.61"
Resolution	1920 x 1200	Size Unpacked with Stand (mm)	533.2 x 260.4 x 497.4
Backlight	WLED	(inches)	20.99" x 10.25" x 19.58"
Aspect Ratio	16:10	Size Monitor Head Only (mm)	533.2 x 42.3 x 355.1
Pixel Pitch (W x H) (mm)	0.27 x 0.27	(inches)	20.99" x 1.67" x 13.98"
Dot/Pixel Per Inch (DPI/PPI)	94 PPI	Distance from Table to Panel	
Anti-Glare	Yes	Lowest Pixel at Bottom of Screen (mm / inches)	56 / 2.2"
Screen Dimensions (W x H) (mm)	518.4 x 324	Highest Pixel at Top of Screen (mm / inches)	490 / 19.29"
(inches)	20.41" x 12.75"	Stand Base Footprint Area (mm)	250 x 250
Maximum Brightness (Typical)	300 cd/m ²	(inches)	9.84" x 9.84"
Viewing Angle (H/V at CR 10:1)	178°/178°	Weight	
Contrast Ratio (Typical)	1000:1	Packed	Starting at 19.18 lbs (8.7 kg)
Dynamic Contrast Ratio	3M:1	Unpacked	Starting at 12.41 lbs (5.63 kg)
Color Gamut (CIE 1931)	99% sRGB	Monitor Head Only	Starting at 8.77 lbs (3.98 kg)
Display Colors (Typical)	16.7 Million		
Response Time			
Extreme	4 ms		
Typical	7 ms		
Off	15 ms		
SIGNAL INPUT		POWER CONSUMPTION	
Video Input Signals	VGA + DisplayPort 1.2 + HDMI 1.4	Typical	22 W
Video Cables Supplied	VGA + DisplayPort + HDMI ¹	Maximum	64 W
Video Cable Length	1.8 m	Sleep-Mode	<0.3 W
USB Hub	USB 3.0 ²	Switch Off-Mode	<0.3 W
USB Cable Supplied	Yes	Power Supply	Internal
Audio-Out	Yes (3.5 mm)	Power Voltage	100 VAC - 240 VAC
		Voltage Dynamic Frequency	50 Hz - 60 Hz
SIGNAL INTERFACE / PERFORMANCE		ENVIRONMENTAL	
Horizontal Frequency	30 kHz - 83 KHz	Temperature	
Vertical Frequency	50 Hz - 75 Hz	Operating	0°C - 40°C
Native Resolution	1920 x 1200	Non-Operating	-20°C - 60°C
Maximum Pixel Clock Speed/ Bandwidth		Humidity	
VGA	205 MHz	Operating	10% - 80%
HDMI™	165 MHz	Non-Operating	5% - 95%
DisplayPort™	165 MHz	Altitude	
Default Color Temperature	6500 K	Operating	0 m - 5000 m
Preset Display Modes	20	Non-Operating	0 ft - 40,000 ft
OSD Buttons	5	Arsenic-Free Glass	Yes
OSD Languages	English, French, German, Spanish, Italian, Japanese, Simplified Chinese, Russian	PVC-Free	Yes
		Mercury-Free	Yes
		PCC % of Plastic Resins	>85%
MECHANICAL		COMPLIANCE	
Tilt Angle (Front / Back)	-5° / 30°	EPEAT	Silver
Swivel Angle (Left / Right)	+/- 45°	ENERGY STAR Rating	8.0
Lift (mm)	110	ULE	Gold
Pivot	+/- 90°	TCO	TCO Display 7.0 / TCO Edge 2.0
VESA® Mount (mm x mm)	100 x 100	RoHS (EU 2002/95/EC)	Yes
Cable Management	Yes	China Energy Efficiency Standard	Tier 2
Kensington® Lock	Yes	Windows Certification	Windows 7 / Windows 10
Bezel Color	Business Black		
Bezel Width			
Top (mm / inches)	2 / 0.08"		
Bottom (mm / inches)	22.7 / 0.89"		
Sides (mm / inches)	2 / 0.08"		
WARRANTY AND AVAILABILITY			
Warranty		3 Years	
Geography Availability		WW	

¹ US & Canada only.

² Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: - 5 Gbit/s for USB 3.1 Gen 1; 10 Gbit/s for USB 3.1 Gen 2 & 20 Gbit/s for USB 3.2.



WWW.LENOVO.COM