



MC2425adw

Reliability. Security. Productivity.



🚺 Lexmark

MC2425adw

We back this product with a guarantee that covers repair actions including the cost of spare parts in the first four years.* The guarantee also offers you free 24-hour self-help online support and access to technical support by phone during working hours.



*Offer applies if the product is registered within 90 days from the date of purchase. Supplies and/or consumable parts, such as fuser or transfer unit, are excluded. Please refer to the detailed terms and conditions available at lexmark.com/myguarantee.

Lexmark MC2425adw

The Lexmark MC2425adw packs reliable, productive and secure colour multifunction performance into a small-footprint package with print speed up to 23 pages per minute*. It reliably handles diverse media types and sizes and comes equipped with both built-in Wi-Fi and tools to help you minimise toner consumption.



Ready when you are

- 1.2-GHz quad-core processor and 1 GB memory drives printing at up to 23 ppm.*
- Scan at up to 47 pages per minute.
- Steel frame and durable design stands up to heavy use and harsh environments.
- Long-life fuser and imaging components extend uptime.
- Unison™ Toner replacement cartridges deliver up to 3500 colour and 6000 monochrome pages**.
- Keep printing in black even when colour toner is empty.

Colour that keeps saving

- PANTONE[®] calibration, embedded colour sample pages and Lexmark Colour Replacement produce accurate, professional colour output in-house.
- Save toner with suite of tools that let you choose when and how much colour to print.

Input that works

- Reliable, flexible media handling supports cardstock, small media, and envelopes from the main tray or a convenient single-sheet feeder.
- > 251 pages of standard input can grow to 901.

Interact with ease

- 6 cm colour LCD lets you configure, interact and monitor vital system information.
- Front USB port allows walk-up printing from popular file formats without a computer.
- Compact footprint allows flexible placement in more locations.
- Connect easily via Ethernet, USB, Wi-Fi or simple mobile printing options.

Full-spectrum security

- Lexmark's full-spectrum security architecture helps keep your information safe—in the document, on the device and over the network.
- Keypoint Intelligence Buyers Lab honoured Lexmark with a prestigious BLI PaceSetter award for Document Imaging Security***.



Built for planet earth

- Energy management features reduce power consumption in active use or sleep mode.
- Standard two-sided printing saves paper.
- Recycle cartridges through the award-winning Lexmark Cartridge Collection Programme (LCCP).

*Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. **Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information. ***Award based on Western Europe data



Lexmark MC2425adw



- 1 MC2425adw with 6 cm LCD 462 x 442 x 556 mm
- 2 650-sheet duo tray 133 x 424 x 416 mm

Adjustable printer stand (not shown) 521 x 653 x 625 mm

Swivel cabinet (not shown) 263 x 476 x 600 mm



Note 1: Supports one optional tray.

Note 2: All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at http://www.lexmark.com/publications/furniture_safety/

© 2018 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint and the AirPrint Logo are trademarks of Apple, Inc. Google Cloud Print is a trademark of Google, Inc. MOPRIA®, the Mopria® Logo[™] and the Mopria® Alliance logos are trademarks, service marks, and certification marks of Mopria Alliance, Inc. in the United States and other countries. PANTONE® Goe[™] and other Pantone, Inc. trademarks are property of Pantone, Inc. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (http:// ww.openssl.org/).



3

Product specifications	Lexmark MC2425adw
Print	
Display	2.4-inch (60 mm) Color LCD display
Print speed: up to ⁶	black: 23 ppm / colour: 23 ppm
Time to first page: as fast as	black: <11.7 seconds / colour: <11.7 seconds
Print resolution	black: 1200 x 1200 dpi, 4800 Color Quality (2400 x 600 dpi) / colour: 1200 x 1200 dpi, 4800 Color Quality (2400 x 600 dpi)
Memory	standard: 1024 MB / maximum: 1024 MB
Hard Disk	Not available
Recommended monthly page volume ²	800 - 6500 pages
Maximum monthly duty cycle: up to ³	75000 pages per month
Сору	
Copy speed: up to ⁶	black: 23 cpm / colour: 23 cpm
Time to first copy: as fast as	black: 12.5 seconds / colour: 13 seconds
Scan	
Scanner type / ADF scan	Flatbed scanner with ADF / RADF (reversing duplex)
Duplex scan speed: up to	black: 21 / 23 spm / colour: 13 / 14 spm
Simplex scan speed: up to	black: 47 / 50 spm / colour: 30 / 32 spm
ADF paper input capacity: up to	50 pages
Fax	
Modem speed	Max is 33,600 bps, V.34 Half-Duplex kbps
Supplies ⁷	
Cartridge yields: up to ¹	1000-page black and colour (CMY) cartridges, 6000-page black cartridge, 2,300-page Colour (CMY) High Yield Cartridges, 3,000-page Black High Yield Cartridge, 3,500-page Colour (CMY) Extra High Yield Cartridges
Photoconductor yield: up to⁵	40,000 pages, based on average 3 pages per print job and 5% coverage
Cartridge(s) shipped with product ¹	1400-page black starter Return Program toner cartridge, 750-page colour (CMY) starter Return Program toner cartridges
Paper Handling	
Standard paper handling	250-sheet input, 150-sheet output bin, Integrated Duplex, Single-sheet manual feed
Optional paper handling	650-Sheet Duo Tray
Paper input capacity: up to	standard: 250+1 pages / maximum: 900+1 pages
Paper output capacity: up to	standard: 150 pages / maximum: 150 pages
Media types supported	Card Stock, Paper Labels, Plain Paper, Vinyl Labels, Refer to the Paper & Specialty Media Guide
Media sizes supported	10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Hagaki card, Executive, Folio, JIS-B5, Legal, Letter, Universal, Oficio, A6
General ⁴	
Standard connectivity	USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), 802.11b/g/n Wireless, Front USB 2.0 Specification Hi-Speed Certified port (Type A)
Optional network ports	Marknet N8372 WiFi Option
Noise Level: Operating	Print: 48 dBA / Copy: 54 dBA / Scan: 54 dBA
Specified operating environment	Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3048 meters, Temperature: 10 to 32°C (50 to 90°F)
Product guarantee	4-year guarantee (upon registration)
Size / Weight	HxWxD: 462 x 442 x 556 mm / 26.8 kg

All information in this brochure is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹Average continuous cartridge yield is stated number of standard pages as listed. Declared yield value in accordance with ISO/IEC 19798. ²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. 4Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details. ⁵Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. ⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds. ⁷Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.

🔨 lexmark.com