



SPECIFICATIONS

Model Name	MAG B760 TOMAHAWK WIFI DDR4
CPU Support	Support Intel® Core™ 14th/ 13th/ 12th Gen Processors, Intel® Pentium® Gold and Celeron® Processors
CPU Socket	LGA 1700
Chipset	Intel® B760 Chipset
Expansion Slots	1x PCIe 5.0 x16 slot, 1x PCIe 3.0 x16 slot, 1x PCIe 4.0 x1 slot
Display Interface	Support 4K@60Hz as specified in HDMI™ 2.1, DisplayPort 1.4 - Requires Processor Graphics
Memory Support	4 DIMMs, Dual Channel DDR4 5333+MHz (OC)
Storage	3x M.2 Gen4 x4 64Gbps slots, 4x SATA 6Gb/s ports
USB ports	1x USB 3.2 Gen 2x2 20Gbps (Type-C), 5x USB 3.2 Gen 2 10Gbps (Type-A + Type-C), 2x USB 3.2 Gen 1 5Gbps (Type-A), 8x USB 2.0
LAN	Realtek® RTL8125BG 2.5Gbps LAN
Wireless / Bluetooth	Intel® Wi-Fi 6E, Bluetooth 5.3
Audio	8-Channel (7.1) HD Audio with Audio Boost

FEATURES



Lightning Gen 5

The latest PCIe 5.0 solution with up to 128GB/s bandwidth for maximum transfer speed.



Wi-Fi 6E

The latest wireless solution supports 6GHz spectrum, MU-MIMO and BSS color technology, delivering speeds up to 2400Mbps.



2.5G Network Solution

Featuring premium 2.5G LAN to deliver better network experience.



6 Layer PCB with 2oz Thickened Copper

An Enhanced PCB design provides higher performance and long-lasting system stability without any compromise.



Lightning USB 20G

Built-in USB 3.2 Gen 2x2 port, offers 20Gbps transmission speed, 4X faster than USB 3.2 Gen 1.



M.2 Shield FROZR

M.2 thermal accessory keeps M.2 SSDs safe while preventing throttling, making them run faster.



Memory Boost

Advanced technology to deliver pure data signals for the best performance, stability and compatibility.



Core Boost


With premium layout and fully digital power design to support more cores and provide better performance.



Audio Boost

Reward your ears with studio grade sound quality for the most immersive audio experience.

CONNECTIONS



1. USB 2.0 Port
2. DisplayPort 1.4
3. USB 3.2 Gen 2 10Gbps Type-A
4. 2.5G LAN Port
5. Wi-Fi / Bluetooth Antenna
6. HD Audio Connectors
7. HDMI™ 2.1 Port
8. USB 3.2 Gen 2x2 20Gbps Type-C
9. Optical S/PDIF OUT