

GRAPHICS CARDS GeForce GTX 1660 SUPER™ AERO ITX OC










SPECIFICATIONS

Model Name	GeForce [®] GTX 1660 SUPER [™] AERO ITX OC
Graphics Processing Unit	NVIDIA [®] GeForce [®] GTX 1660 SUPER [™]
Interface	PCI Express x16 3.0
Core Clocks	Boost: 1815 MHz
CUDA [®] CORES	1408 Units
Memory Speed	14 Gbps
Memory	6GB GDDR6
Memory Bus	192-bit
Output	DL-DVI-D x 1 DisplayPort x 1 (v1.4a) HDMI x 1(Supports 4K@60Hz as specified in HDMI 2.0b)
HDCP Support	2.2
Power consumption	125 W
Power connectors	8-pin x 1
Recommended PSU	450 W
Card Dimension (mm)	179 x 127 x 42 mm
Weight (Card / Package)	561 g / 876 g
DirectX Version Support	12 API
OpenGL Version Support	4.5
Afterburner OC	<u>Y</u>
Maximum Displays	3
VR Ready	<u>Y</u>
G-SYNC [®] technology	Y
Digital Maximum Resolution	7680x4320

CONNECTIONS



FEATURES



MSI Afterburner

The ultimate overclocking software with advanced control options and real-time hardware monitor.

PERFECT IN ANY CASE

Thanks to a small form factor, MSI AERO ITX cards will fit into virtually any case.

SMALL FORM FACTOR

MSI AERO ITX cards offer the power of a full size graphics card in an incredibly small package.

VR Ready



ITX 🔁

Certified to provide the performance required for a smooth experience in your VR adventures.

NVIDIA[®] G-SYNC[®]



Gives you more of what you want in a gaming experience. Incredibly smooth, tear-free gameplay at refresh rates up to 240 Hz.

© 2022 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved. © 2022 NVIDIA, the NVIDIA logo, GeForce, SHIELD, and NVIDIA G-SYNC are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries.