

Anser 1500

PN: UPLI-LI150AN-CG01B
EAN: 6422956012540

Specifications

Capacity	1500 VA / 900 W
Type	Line-interactive
Input	
Nominal Voltage	230 VAC
Accepted Voltage Range	165 - 290 VAC
Rated Input Current	10A (Input breaker)
Frequency Range	50Hz ~ 60 Hz \pm 3Hz (Auto sensing)
Input Connector	1x IEC C14
Output	
Nominal Voltage	230 VAC
AC Voltage Regulation (Batt. Mode)	\pm 10%
Frequency Range (Batt. Mode)	50 Hz or 60Hz \pm 1%
Power Factor	\geq 0.6 @ nominal voltage (100% load)
Waveform (Batt. Mode)	Pure sine wave
Transfer Time	Typical 4 ms
Overload Protection	Inner firmware protection
AVR	
Type	1 Boost / 1 Buck
Indicators type	
LCD Display	Load level, Battery level, AC mode, Battery mode and Fault indicators
Alarm	Load Capacity, Load & Battery level, AC mode, Battery mode and Fault indicators, etc.
Protection	
Outlets type	4 x IEC C13 Battery Backup & Surge Protection 4 x IEC C13 Surge Protection RJ11/RJ45 Phone and network protection
Full protection	Overload, deep discharge, Overcharge, Over-Voltage, High Temperature, Input spike protection
Surge rating energy	Min. 810 Joules (EMI / RFI filtering)



8 x IEC C13 outlets with protection



LCD Display



Pure sine wave output

- Line-interactive
- Auto restart while AC is recovering
- Auto-Charge
- Boost and buck AVR for voltage stabilization
- Software management
- Off-Mode Charging
- Cold start function
- Emergency power off function (EPO)
- Smart SNMP card supported
- Rack design
- ECO mode for reduced power consumption in AC mode

Battery

Battery Type & Number	2 x 12V VRLA battery
Typical Recharge Time	6 - 8 hours
Functions	Hot-swappable and user-replaceable

Management

Connection port	RS232, HID USB, RJ45/RJ11, Intelligent Port (not included in the package)
Software capability	Monitor & Control over USB, LAN and Internet (SNMP card optional)

Environment

Humidity	0-95 % (non-condensing)
Temperature	0-40°C
Online heat dissipation	24 BTU/h
Noise level	Less than 50dB

Physical

Product dimensions	438 x 88 x 430 mm - 2U Metal case
Product weight	16.5 kg
Retail Pack Dimensions	566 x 550 x 231 mm
Retail Pack Weight	18.5 kg

Logistics

 Carton Box Size (LxWxH)	566 x 550 x 231 mm
 Pieces in the Carton Box	1
 Net & Gross weight / CTN	N.W.: 16.5 kg / G.W.: 18.5 kg



Certificates

