



| TR-004U | |
|--|---|
| CPU | Micro processor with hardware RAID |
| Drive Bay | 4 x 3.5-inch SATA 3Gb/s |
| Drive Compatibility | 3.5-inch SATA 6Gb/s, 3Gb/s hard disk drives 2.5-inch SATA 6Gb/s, 3Gb/s hard disk drives 2.5-inch SATA 6Gb/s, 3Gb/s solid state drives |
| Hot-swappable | Yes |
| USB 3.2 Gen 1 port | 1 x Type-C USB 3.2 Gen 1 (USB 3.2 Gen 1) |
| Form Factor | 1U Rackmount |
| Dimensions (HxWxD) | 44 × 439 × 291 mm |
| Weight (Net) | 4.03 kg |
| Weight (Gross) | 5.66 kg |
| Max. number of HDDs/SSDs supported | 4 |
| Hard Drive Type | 4 x 2.5-inch or 3.5-inch SATA 3Gb/s |
| Operating Temperature | 0 - 40 °C (32°F - 104°F) |
| Storage Temperature | -20 - 70°C (-4°F - 158°F) |
| Relative Humidity | 5-95% RH non-condensing, wet bulb: 27°C (80.6°F) |
| Power Supply Unit | Open-frame 100W, Input: 100V-240V ~ / 3.5A, 50Hz-60Hz |
| Power Consumption: HDD Sleep Mode | 4.79 W |
| Power Consumption: Operating Mode, Typical | 18.9 W |
| Fan | 2 x 40mm, 12VDC |
| System Warning | Buzzer |
| Kensington Security Slot | Yes |

Note: Use only ONAP memory modules to maintain system performance and stability. For NAS devices with more than one memory

slot, use QNAP modules with identical specifications.

Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

Product images are for illustrative purposes only and may differ from the actual product. Due to differences in monitors, colors of products may also appear different to those shown on the site.

Designs and specifications are subject to change without notice.