



VPL-MX25

XGA wireless ultra-portable
wireless projector with 2500
ANSI

Ultimate portable projector

When you've only got a short opportunity to impress your audience, you want to be in complete control.

The VPL-MX25 is the ultimate personal projector for people on the move. This projector has been designed for the style conscious professionals in a contemporary metallic chassis. Furthermore, it has been developed for maximum mobility - with a depth of 45mm and weight of only 1.7 kg, it is lightweight and easy to carry. The projector's five step Advanced Intelligent Auto Set Up feature means it is quick and simple to operate. In addition, the Off-and-Go function means it can be unplugged immediately after being switched off.

By combining an optical system that incorporates Sony's new and innovative BrightEra with Long Lasting Optics technology and a 3LCD projection system, the VPL-MX25 delivers high picture quality in XGA (1024 x 768) resolution and a high brightness of 2500 lumens. This allows professional presentations to be delivered in virtually any setting. Built-in wireless connectivity eliminates the need for computer cables. The user experience is further enhanced by built-in Microsoft Office Viewer software, supporting PDF and Microsoft Office formats, enabling presentations to be made directly from a USB storage device. The projector also has an embedded Windows Media Player which supports streaming from PC, network or USB storage device.

PrimeSupport

All Sony business projectors come supplied with a 3-year support pack which offers unique extra services and benefits.

3 years' cover

Free telephone helpdesk support in English, German, French, Italian and Spanish.

Collection and delivery anywhere in EU, Norway and Switzerland.

Features

BrightEra with Long Lasting Optics technology

This is a more advanced version of Sony's original BrightEra technology which was developed to deliver improved panel light resistance, higher brightness, higher resolution and increased panel reliability. This new technology incorporates new inorganic polarisers.

Colour Light Output - 2500 lumens

Colour Light Output is a metric that measures a projector's ability to deliver colour. Colour Light Output provides users with a simple, accurate and easy to understand way to evaluate projector Colour Performance to make better buying decisions.

Ultra-portable

Weighing in at just 1.7kg with a depth of only 45mm and a magnesium ergonomic curved edge body design, it's simply the ultimate in mobility, durability and style.

Off and Go Function

Power off, unplug and go. The fan continues to cool the VPL-MX20 after the power supply is removed, enabling users to unplug the projector immediately after use, without damaging the lamp or optics. Other projectors need to remain connected to the power supply to cool the projector after use.

Quick Start and Re-start

8 second start up and 5 second restart

Dynamic Detail Enhancer

Generates high quality images through the Interlace/Progressive conversion processor, resulting in extremely accurate image reproduction

3 Picture Modes

Presentation, Standard & Dynamic pictures modes available using Dynamic Digital Enhancer.

Digital Zoom (4x)

Highlight a portion of the image displayed by 4X for audience impact.

Advanced Intelligent Auto Set Up

5 step process: Auto Focus, Auto Tilt, Auto Keystone Correction, Auto Signal Input and Auto Pixel Alignment

Panel Key Lock

Locks the keys on the control panel so the projector can only be operated by the remote control.

Benefits

Make an impact

Sony technology ensures high resolution, vivid colour output - embedded Windows Media Player enables seamless integration of video content within your presentations.

Stress-free operation

No need to worry about PC boot-up times, incompatible connections or adjusting your picture. The VPL-MX25 lets you to present PDF and Microsoft Office format content from almost any USB storage device.

Travel light

Weighing in at just 1.7 kg and with a depth of only 45mm, the VPL-MX25 is easy and convenient to carry between meetings. And you don't even need a PC to present from.

Move fast

Be ready to present just 8 seconds after switching on and move on as soon as your presentation is finished - you can unplug immediately after switching off.

Technical Specifications

--Optical--

Projector System	0.63 inch TFT LCD panel, (BrightEra) 2,359,296 (1024 x 768 (XGA) x3) pixels
Projector Lens	Approx. 1.2 times zoom lens (manual), f=18.63 to 22.36mm, f=1.65 to 1.8
Throw Distance	30-inch Screen 0.86 to 0.99m 80-inch Screen 2.4 to 2.7m 100-inch Screen 3.0 to 3.4m
Lamp	200W Ultra high pressure lamp
Lamp Life	2000 H (Lamp mode: High) 3000 H (Lamp mode: Standard)
Screen Coverage	30inch to 150inch (30inch to 150inch auto focus operation range)
Light Output	2500 (Lamp mode: High) / 2000 (Lamp mode: Standard)
Colour Light Output	2500 (Lamp mode: High) / 2000 (Lamp mode: Standard)
Contrast	650:1
Colour System	NTSC3.58/PAL/SECAM/NTSC4.43/PAL-M/PAL-N/ PAL60 system, switched automatically/manually (NTSC4.43 is the colour system used when playing back a video recorded in NTSC on a NTSC4.43 system VCR.)

--Signals--

Resolution	750 horizontal TV lines (Video input) 1,024 x 768 dots (RGB input)
Acceptable Computer Signal	fH: 19 to 80 kHz / fV: 48 to 92 Hz Maximum input signal resolution: SXGA+ 1400 x 1050 fV: 60 Hz

Acceptable Video Signal	15 k RGB/Component 50/60 Hz, Progressive component 50/60, Hz, DTV (480/60I, 575/50I, 480/60P, 575/50P, 720/60P, 720/ 50P, 1080/60I, 1080/50I), Composite video, Y/C video
-------------------------	---

--General--

Dimensions (WxHxD)	273 × 45 × 206 mm (w/h/d) (without projecting parts)
Mass	Approx. 1.7 kg (3 lb 12 oz)
Cabinet Colour	Silver / black
Power Requirements	AC 100 to 240 V, 3.6 to 1.6 A, 50/60 Hz
Power Consumption	Max.: 290W, in Standby (Standard): 6W in Standby (Low): 2W
Heat Dissipation	990 BTU
Fan Noise	38dB (Lamp mode: standard)
Operating Temperature	0 to 35°C degrees (32 to 95°F degrees)
Operating Humidity	35 to 85% (no condensation)
Storage Temperature	-20 to 60°C degrees (-4 to 140°F Degrees)
Storage Humidity	10 to 90%

--Safety Regulations--

Safety Regulations	CB (IEC60950-1), DEMKO (EN60950-1), FCC (Class B), IC (Class B), JEITA, UL60950-1, cUL(CSA No.60950-1), VCCI, eK (K60950-1 +EMC), C-Tick (EN55022(B)), CE (LVD: EN60950-1(DEMKO), EMC)
--------------------	--

--Interfaces--

Video Inputs	Composite Video: 1 Vp-p ±2 dB sync negative (75 ohms terminated)
Input A	RGB/Component: HD D-sub15-pin, female Analogue
Network	Wireless LAN: IEEE.802.11.a/b/g
USB	USB Type A

--Supplied Accessories--

Supplied Accessories	Remote Commander RM-PJ6, Lithium Battery for Remote Commander CR2025 (1), HD D-sub 15-pin cable (2.0m) (1), Security Label, CD-ROM (Operating Instructions), Quick Reference Manual, Safety Regulations, AC Power Cord, Carrying Case (1), Warranty Card (outside of box)
----------------------	--