



G4 Doorbell

UVC-G4-Doorbell-EU* is a WiFi video doorbell with a built-in display and real-time two-way audio communication. The camera features a high-quality 5MP sensor with enhanced night vision. Image streams can be viewed in up to 1600 x 1200 (2 MP) HD at 30 FPS. UVC-G4-Doorbell-EU includes a PIR sensor for instant motion detection alerts. Integration with UniFi Protect provides an easy-to-use interface.

*Comes with EU-rated 230V / 16VAC doorbell transformer



Mechanical

| | |
|--------------------|--|
| Dimensions | 118.3 x 46.8 x 25.8 mm (4.66 x 1.84 x 1.02") |
| Weight | Without mount: 130 g (4.59 oz) With flat wall mount: 178 g (6.28 oz) With 20° wedge mount: 200 g (7.05 oz) |
| Enclosure material | Polycarbonate |
| Mount materials | Flat wall mount: aluminum alloy 20° wedge mount: polycarbonate |
| Weatherproofing | IPX4 |

Optics

| | |
|------------|--|
| Sensor | 5 MP CMOS sensor |
| Lens | Fixed focal length |
| View angle | H: 138°, V: 114°, D: 155° |
| Night mode | Built-in IR LED illumination and IR cut filter |

Video

| | |
|--------------------|-------------------|
| Video compression | H.264 |
| Resolution | 1600 x 1200 (4:3) |
| Maximum frame rate | 30 FPS |

System

| | |
|------------------------|---------------------------------------|
| Processor specs | Quad core Arm® Cortex®-A53 based chip |
| Memory information | 512 MB |
| Management interface | UniFi Protect |
| Networking interface | 802.11 ac WiFi |
| Flash memory support | 256 MB |
| Max. power consumption | 12VA |
| Power requirements | 16-24VAC, 20VA, 50/60 Hz |
| Link/activity LED | Yes |
| Button | Factory reset |
| Mounting | Flat wall/20° wedge (kits included) |
| Operating temperature | -10 to 40° C (14 to 104° F) |

| | |
|--------------------|------------------------|
| Operating humidity | 0 to 90% noncondensing |
|--------------------|------------------------|

| | |
|----------------|-------------|
| Certifications | FCC, IC, CE |
|----------------|-------------|

Audio

| | |
|------------|-----------------------------------|
| Microphone | Yes (can be disabled in software) |
|------------|-----------------------------------|

| | |
|---------|-----|
| Speaker | Yes |
|---------|-----|

Software

| | |
|---------------------|---------------|
| Controller software | UniFi Protect |
|---------------------|---------------|

| | |
|-------------|-------------------------------|
| Mobile apps | UniFi Protect iOS and Android |
|-------------|-------------------------------|

Transformer Specifications

| | |
|---------------------|---------------|
| Input rating (5, 6) | 230V, 50/60Hz |
|---------------------|---------------|

| | |
|----------------------|-------------|
| Output rating (1, 4) | 16VAC, 15VA |
|----------------------|-------------|

| | |
|-----------------------|---------------------------|
| Operating temperature | -5 to 35 °C (23 to 95° F) |
|-----------------------|---------------------------|



Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at www.ui.com/support/warranty

©2020 Ubiquiti Inc. All rights reserved. Ubiquiti, the Ubiquiti U logo, the Ubiquiti beam logo, UniFi, and UniFi Protect are trademarks or registered trademarks of Ubiquiti Networks, Inc. in the United States and in other countries. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc., registered in the U.S. and other countries. Android, Google, Google Play, the Google Play logo and other marks are trademarks of Google LLC. Arm and Cortex are registered trademarks of Arm Limited (or its subsidiaries) in the US and/or elsewhere. All other trademarks are the property of their respective owners.